

TYPE APPROVAL CERTIFICATE

This is to certify:

That the Structural Fire Protection

with type designation(s)
Firetex M90/02 - I section

Issued to

Sherwin-Williams Protective & Marine Coatings
Bolton, United Kingdom

is found to comply with
DNV GL offshore standards

Application :

Approved for use as a system for fire protection of structural steel I sections.

This Certificate is valid until **2021-11-26**.

Issued at **Høvik** on **2016-11-27**

DNV GL local station: **Manchester**

Approval Engineer: **Helge Bjørnarå**

for **DNV GL**

Petter Langnes
Head of Section

This Certificate is subject to terms and conditions overleaf. Any significant change in design or construction may render this Certificate invalid.
The validity date relates to the Type Approval Certificate and not to the approval of equipment/systems installed.

Job Id:
Certificate No: **TAF00000GW**

Product description

"Firetex M90/02" – I sections

The system is composed by a primer (Firetex C69) covered by an epoxy based intumescent coating (Firetex M90/02). The epoxy based intumescent coating is reinforced mid depth with embedded fabric (Firetex J220).

The materials are manufactured at the following locations:

- Sherwin-Williams, Bolton, UK

Application/Limitation

The thickness of "Firetex M90/02" system to be applied to avoid temperatures to rise on the steel substrate less than 200 °C, 250 °C, 300 °C, 350 °C, 400 °C, 450 °C, 500 °C, 538 °C, 550 °C, 600 °C, 650 °C, 700 °C and 750 °C for "I" sections, are given in appendix table 1-13.

The protective coating is not defined as non-combustible and should not be used in accommodation or in enclosed areas.

Minimum fabric overlap shall be not less than 50 mm. Wet density of "Firetex M90/02" is 1000 kg/m³.

The approval refers only to the fire resistance properties of the system.

The application of the protective coating is to be performed in accordance with the manufacturer's application manual. Alternative primers and topcoats may be used provided they have been tested and approved by the manufacture.

Each product is to be supplied with its manual for application and maintenance.

Type Approval documentation

Certification in accordance with Class Programme DNVGL-CP-0338, October 2015.

Initial Survey report dated 2012-04-20 from DNV Liverpool.

Test report No. 313202 dated 2012-01-18 from Exova Warringtonfire

Test report No. 305260 dated 2011-09-15 from Exova Warringtonfire

Test report No. 308082 dated 2011-09-15 from Exova Warringtonfire

Test report No. 308083 dated 2011-09-15 from Exova Warringtonfire

Test report No. 308084 dated 2011-09-15 from Exova Warringtonfire

Test report No. 309191 dated 2011-09-15 from Exova Warringtonfire

Test report No. 309192 dated 2011-09-15 from Exova Warringtonfire

Letter 309675 CL dated 2010-09-12 from Exova Warringtonfire, UK

Tests carried out

Tested according to ISO 834-3 and IMO FTP Code Part 3 (IMO Res. A.754 (18)).

Marking of product

The product or packing is to be marked with name of manufacturer and type designation.

Periodical assessment

DNV GL's surveyor is to be given permission to perform Periodical Assessments at any time during the validity of this certificate and at least every second year. The arrangement is to be in accordance with procedure described in Class Programme DNVGL-CP-0338, Section 4.

Job Id:
Certificate No: **TAF00000GW**

Appendix to certificate TAF00000GW

Table 1: Thickness of "FIRETEX M90/02" system for fire protection of "I" sections for a critical temperature rise of **200 °C**:

Hp/A	time [min]						
	30	60	90	120	150	180	210
10							
15							
20							
25							
30							
35							
40							
45							
50							
55							
60							
65							
70							
75							
80							
85							
90							
95							
100							
105							
110							
115							
120							
125							
130							
135							
140							
145							
150							
155							
160							
165							
170							
175							
180							
185							
190							
195							

Hp/A	time [min]						
	30	60	90	120	150	180	210
200							
205							
210							
215							
220							
225							
230							
235							
240							
245							
250							
255							
260							
265							
270							
275							
280							
285							
290							
295							
300							
305							
310							
315							
320							
325							
330							
332							

The maximum thickness of protection material up to the required Hp/A [m-1] shall be used.

Hp/A = Ratio between Heat perimeter and cross sectional Area of the section, [m-1]

Job Id:
Certificate No: **TAF00000GW**

Appendix to certificate TAF00000GW

Table 2: Thickness of "FIRETEX M90/02" system for fire protection of "I" sections for a critical temperature rise of **250 °C**:

Hp/A	time [min]						
	30	60	90	120	150	180	210
10							
15							
20							
25							
30							
35							
40							
45							
50							
55							
60							
65							
70							
75							
80							
85							
90							
95							
100							
105							
110							
115							
120							
125							
130							
135							
140							
145							
150							
155							
160							
165							
170							
175							
180							
185							
190							
195							

Hp/A	time [min]						
	30	60	90	120	150	180	210
200							
205							
210							
215							
220							
225							
230							
235							
240							
245							
250							
255							
260							
265							
270							
275							
280							
285							
290							
295							
300							
305							
310							
315							
320							
325							
330							
332							

The maximum thickness of protection material up to the required Hp/A [m-1] shall be used.

Hp/A = Ratio between Heat perimeter and cross sectional Area of the section, [m-1]

Job Id:
Certificate No: **TAF00000GW**

Appendix to certificate TAF00000GW

Table 3: Thickness of "FIRETEX M90/02" system for fire protection of "I" sections for a critical temperature rise of **300 °C**:

Hp/A	time [min]						
	30	60	90	120	150	180	210
10							
15							
20							
25							
30							
35							
40							
45							
50							
55							
60							
65							
70							
75							
80							
85							
90							
95							
100							
105							
110							
115							
120							
125							
130							
135							
140							
145							
150							
155							
160							
165							
170							
175							
180							
185							
190							
195							

Hp/A	time [min]						
	30	60	90	120	150	180	210
200							
205							
210							
215							
220							
225							
230							
235							
240							
245							
250							
255							
260							
265							
270							
275							
280							
285							
290							
295							
300							
305							
310							
315							
320							
325							
330							
332							

The maximum thickness of protection material up to the required Hp/A [m-1] shall be used.

Hp/A = Ratio between Heat perimeter and cross sectional Area of the section, [m-1]

Job Id:
Certificate No: **TAF00000GW**

Appendix to certificate TAF00000GW

Table 4: Thickness of "FIRETEX M90/02" system for fire protection of "I" sections for a critical temperature rise of **350 °C**:

Hp/A	time [min]						
	30	60	90	120	150	180	210
10							
15							
20							
25							
30							
35							
40							
45							
50							
55							
60							
65							
70							
75							
80							
85							
90							
95							
100							
105							
110							
115							
120							
125							
130							
135							
140							
145							
150							
155							
160							
165							
170							
175							
180							
185							
190							
195							

Hp/A	time [min]						
	30	60	90	120	150	180	210
200							
205							
210							
215							
220							
225							
230							
235							
240							
245							
250							
255							
260							
265							
270							
275							
280							
285							
290							
295							
300							
305							
310							
315							
320							
325							
330							
332							

The maximum thickness of protection material up to the required Hp/A [m-1] shall be used.

Hp/A = Ratio between Heat perimeter and cross sectional Area of the section, [m-1]

Job Id:
Certificate No: **TAF00000GW**

Appendix to certificate TAF00000GW

Table 5: Thickness of "FIRETEX M90/02" system for fire protection of "I" sections for a critical temperature rise of **400 °C**:

Hp/A	time [min]						
	30	60	90	120	150	180	210
10							
15							
20							
25							
30							
35							
40							
45							
50							
55							
60							
65							
70							
75							
80							
85							
90							
95							
100							
105							
110							
115							
120							
125							
130							
135							
140							
145							
150							
155							
160							
165							
170							
175							
180							
185							
190							
195							

Hp/A	time [min]						
	30	60	90	120	150	180	210
200							
205							
210							
215							
220							
225							
230							
235							
240							
245							
250							
255							
260							
265							
270							
275							
280							
285							
290							
295							
300							
305							
310							
315							
320							
325							
330							
332							

The maximum thickness of protection material up to the required Hp/A [m-1] shall be used.

Hp/A = Ratio between Heat perimeter and cross sectional Area of the section, [m-1]

Job Id:
Certificate No: **TAF00000GW**

Appendix to certificate TAF00000GW

Table 6: Thickness of "FIRETEX M90/02" system for fire protection of "I" sections for a critical temperature rise of **450 °C**:

Hp/A	time [min]						
	30	60	90	120	150	180	210
10							
15							
20							
25							
30							
35							
40							
45							
50							
55							
60							
65							
70							
75							
80							
85							
90							
95							
100							
105							
110							
115							
120							
125							
130							
135							
140							
145							
150							
155							
160							
165							
170							
175							
180							
185							
190							
195							

Hp/A	time [min]						
	30	60	90	120	150	180	210
200							
205							
210							
215							
220							
225							
230							
235							
240							
245							
250							
255							
260							
265							
270							
275							
280							
285							
290							
295							
300							
305							
310							
315							
320							
325							
330							
332							

The maximum thickness of protection material up to the required Hp/A [m-1] shall be used.

Hp/A = Ratio between Heat perimeter and cross sectional Area of the section, [m-1]

Job Id:
Certificate No: **TAF00000GW**

Appendix to certificate TAF00000GW

Table 7: Thickness of "FIRETEX M90/02" system for fire protection of "I" sections for a critical temperature rise of **500 °C**:

Hp/A	time [min]						
	30	60	90	120	150	180	210
10							
15							
20							
25							
30							
35							
40							
45							
50							
55							
60							
65							
70							
75							
80							
85							
90							
95							
100							
105							
110							
115							
120							
125							
130							
135							
140							
145							
150							
155							
160							
165							
170							
175							
180							
185							
190							
195							

Hp/A	time [min]						
	30	60	90	120	150	180	210
200							
205							
210							
215							
220							
225							
230							
235							
240							
245							
250							
255							
260							
265							
270							
275							
280							
285							
290							
295							
300							
305							
310							
315							
320							
325							
330							
332							

The maximum thickness of protection material up to the required Hp/A [m-1] shall be used.

Hp/A = Ratio between Heat perimeter and cross sectional Area of the section, [m-1]

Job Id:
Certificate No: **TAF00000GW**

Appendix to certificate TAF00000GW

Table 8: Thickness of "FIRETEX M90/02" system for fire protection of "I" sections for a critical temperature rise of **538 °C**:

Hp/A	time [min]						
	30	60	90	120	150	180	210
10							
15							
20							
25							
30							
35							
40							
45							
50							
55							
60							
65							
70							
75							
80							
85							
90							
95							
100							
105							
110							
115							
120							
125							
130							
135							
140							
145							
150							
155							
160							
165							
170							
175							
180							
185							
190							
195							

Hp/A	time [min]						
	30	60	90	120	150	180	210
200							
205							
210							
215							
220							
225							
230							
235							
240							
245							
250							
255							
260							
265							
270							
275							
280							
285							
290							
295							
300							
305							
310							
315							
320							
325							
330							
332							

The maximum thickness of protection material up to the required Hp/A [m^{-1}] shall be used.

Hp/A = Ratio between Heat perimeter and cross sectional Area of the section, [m^{-1}]

Job Id:
Certificate No: **TAF00000GW**

Appendix to certificate TAF00000GW

Table 9: Thickness of "FIRETEX M90/02" system for fire protection of "I" sections for a critical temperature rise of **550 °C**:

Hp/A	time [min]						
	30	60	90	120	150	180	210
10							
15							
20							
25							
30							
35							
40							
45							
50							
55							
60							
65							
70							
75							
80							
85							
90							
95							
100							
105							
110							
115							
120							
125							
130							
135							
140							
145							
150							
155							
160							
165							
170							
175							
180							
185							
190							
195							

Hp/A	time [min]						
	30	60	90	120	150	180	210
200							
205							
210							
215							
220							
225							
230							
235							
240							
245							
250							
255							
260							
265							
270							
275							
280							
285							
290							
295							
300							
305							
310							
315							
320							
325							
330							
332							

The maximum thickness of protection material up to the required Hp/A [m^{-1}] shall be used.

Hp/A = Ratio between Heat perimeter and cross sectional Area of the section, [m^{-1}]

Job Id:
Certificate No: **TAF00000GW**

Appendix to certificate TAF00000GW

Table 10: Thickness of "FIRETEX M90/02" system for fire protection of "I" sections for a critical temperature rise of **600 °C**:

Hp/A	time [min]						
	30	60	90	120	150	180	210
10							
15							
20							
25							
30							
35							
40							
45							
50							
55							
60							
65							
70							
75							
80							
85							
90							
95							
100							
105							
110							
115							
120							
125							
130							
135							
140							
145							
150							
155							
160							
165							
170							
175							
180							
185							
190							
195							

Hp/A	time [min]						
	30	60	90	120	150	180	210
200							
205							
210							
215							
220							
225							
230							
235							
240							
245							
250							
255							
260							
265							
270							
275							
280							
285							
290							
295							
300							
305							
310							
315							
320							
325							
330							
332							

The maximum thickness of protection material up to the required Hp/A [m^{-1}] shall be used.

Hp/A = Ratio between Heat perimeter and cross sectional Area of the section, [m^{-1}]

Job Id:
Certificate No: **TAF00000GW**

Appendix to certificate TAF00000GW

Table 11: Thickness of "FIRETEX M90/02" system for fire protection of "I" sections for a critical temperature rise of **650 °C**:

Hp/A	time [min]						
	30	60	90	120	150	180	210
10							
15							
20							
25							
30							
35							
40							
45							
50							
55							
60							
65							
70							
75							
80							
85							
90							
95							
100							
105							
110							
115							
120							
125							
130							
135							
140							
145							
150							
155							
160							
165							
170							
175							
180							
185							
190							
195							

Hp/A	time [min]						
	30	60	90	120	150	180	210
200							
205							
210							
215							
220							
225							
230							
235							
240							
245							
250							
255							
260							
265							
270							
275							
280							
285							
290							
295							
300							
305							
310							
315							
320							
325							
330							
332							

The maximum thickness of protection material up to the required Hp/A [m^{-1}] shall be used.

Hp/A = Ratio between Heat perimeter and cross sectional Area of the section, [m^{-1}]

Job Id:
Certificate No: **TAF00000GW**

Appendix to certificate TAF00000GW

Table 12: Thickness of "FIRETEX M90/02" system for fire protection of "I" sections for a critical temperature rise of **700 °C**:

Hp/A	time [min]						
	30	60	90	120	150	180	210
10							
15							
20							
25							
30							
35							
40							
45							
50							
55							
60							
65							
70							
75							
80							
85							
90							
95							
100							
105							
110							
115							
120							
125							
130							
135							
140							
145							
150							
155							
160							
165							
170							
175							
180							
185							
190							
195							

Hp/A	time [min]						
	30	60	90	120	150	180	210
200							
205							
210							
215							
220							
225							
230							
235							
240							
245							
250							
255							
260							
265							
270							
275							
280							
285							
290							
295							
300							
305							
310							
315							
320							
325							
330							
332							

The maximum thickness of protection material up to the required Hp/A [m^{-1}] shall be used.

Hp/A = Ratio between Heat perimeter and cross sectional Area of the section, [m^{-1}]

Job Id:
Certificate No: **TAF00000GW**

Appendix to certificate TAF00000GW

Table 13: Thickness of "FIRETEX M90/02" system for fire protection of "I" sections for a critical temperature rise of **750 °C**:

Hp/A	time [min]						
	30	60	90	120	150	180	210
10							
15							
20							
25							
30							
35							
40							
45							
50							
55							
60							
65							
70							
75							
80							
85							
90							
95							
100							
105							
110							
115							
120							
125							
130							
135							
140							
145							
150							
155							
160							
165							
170							
175							
180							
185							
190							
195							

Hp/A	time [min]						
	30	60	90	120	150	180	210
200							
205							
210							
215							
220							
225							
230							
235							
240							
245							
250							
255							
260							
265							
270							
275							
280							
285							
290							
295							
300							
305							
310							
315							
320							
325							
330							
332							

The maximum thickness of protection material up to the required Hp/A [m^{-1}] shall be used.

Hp/A = Ratio between Heat perimeter and cross sectional Area of the section, [m^{-1}]