DNV·GL

Certificate No:
TAF00001B8

TYPE APPROVAL CERTIFICATE

This is to certify:

That the Class B Door

with type designation(s)
SM-B15-NS

Issued to
Sung Mi Co., Ltd.
Gimhae-si, Gyeongsangnam-do, Republic of Korea

is found to comply with
DNV GL offshore standards
DNV GL rules for classification – Ships
DNV GL statutory interpretations DNVGL-SI-0364 – SOLAS interpretations

Application :

Product(s) approved by this certificate is/are accepted for installation on all vessels classed by DNV GL.

Issued at **Høvik** on **2020-12-10**
This Certificate is valid until **2025-12-09**.
DNV GL local station: **Gimhae Station**

Approval Engineer: **Furuseth, Thorvald**

for **DNV GL**

Mårten Schei-Nilsson
Head of Section

This Certificate is subject to terms and conditions overleaf. Any significant change in design or construction may render this Certificate invalid.
The validity date relates to the Type Approval Certificate and not to the approval of equipment/systems installed.

© DNV GL 2014. DNV GL and the Horizon Graphic are trademarks of DNV GL AS.

Product description

"SM-B15-NS"
is a single leaved hinged door. The door leaf is composed of 0.6 mm thick steel plates around an insulating core of 48 mm Hi-Wool of density 120 kg/m^3 (from KCC Corporation). The door frame consists of 1.2 mm steel plates and are fixed to the bulkhead panel by welding. The door leaf is attached to the frame with three hinges.

Total thickness of door leaf: 50 mm

The door leaves may incorporate:
- Window in the upper part of the door, type "Fire glass", from Saint-Gobain. Thickness: 16 mm
- Kick-out panel with ventilation louver in the lower part of the door.

For further details see the drawings listed under Type Approval documentation below.

Application/Limitation

The door is approved for installation in bulkheads of class B-15.

Max. clear opening of double door: 1100 mm x 2200 mm (w x h)
Max. size of single door leaf: 1131 mm x 2215 mm (w x h)
Max. clear opening of window: 400 mm x 400 mm (w x h)
Max. clear opening of kick-out panel: 620 mm x 820 mm (w x h)

Any surface materials used have to be approved for smoke and toxicity and low flame spread characteristics (IMO 2010 FTP Code parts 2 and 5) when required according to relevant rules and regulations.

The door has been successfully tested with extended test period in compliance with IMO MSC.1/Circ.1319.

Each product is to be supplied with its manual for installation, use and maintenance.

Type Approval documentation

Certification in accordance with Class Program DNVGL-CP-0338, September 2018.

Test report No. KOMERI-0402-19T0704 dated 29 March 2019 from KOMERI, Busan, Korea.

Drawing No. SMD-181217-002 (p.1-8) dated 03 February 2020 from the manufacturer.

Tests carried out

Tested according to IMO 2010 FTP Code part 3.

Marking of product

The product is to be marked with name of manufacturer, type designation and fire technical rating.

Periodical assessment

DNV GL surveyor is to be given permission to perform Periodical Assessments at any time during the validity of this certificate and at least every second year. The arrangement is to be in accordance with procedure described in Class Program DNVGL-CP-0338, Section 4.