



Certificate No:
TAF00001M2

TYPE APPROVAL CERTIFICATE

This is to certify:

That the Floor Covering

with type designation(s)
Bolidt Helideck G2 Compound

Issued to
Bolidt Kunststoftepassing B.V.
Hendrik-Ido-Ambacht, Zuid-Holland, Netherlands

is found to comply with
DNV statutory interpretations DNV-SI-0364 – SOLAS interpretations, Edition July 2021
DNV rules for classification – Ships
DNV offshore standards

Application :

Low flame spread surface material, not generating excessive quantities of smoke nor toxic products in fire.

This certificate is recognized by Transport Canada.

Product(s) approved by this certificate is/are accepted for installation on all vessels classed by DNV.

Issued at **Høvik** on **2021-11-09**

This Certificate is valid until **2026-11-08**.

for **DNV**

DNV local station: **Netherlands CMC**

Approval Engineer: **Kristin Grønnæss**

.....
Helene David-Andersen
Head of Section

This Certificate is subject to terms and conditions overleaf. Any significant change in design or construction may render this Certificate invalid.
The validity date relates to the Type Approval Certificate and not to the approval of equipment/systems installed.

LEGAL DISCLAIMER: Unless otherwise stated in the applicable contract with the holder of this document, or following from mandatory law, the liability of DNV AS, its parent companies and their subsidiaries as well as their officers, directors and employees ("DNV") arising from or in connection with the services rendered for the purpose of the issuance of this document or reliance thereon, whether in contract or in tort (including negligence), shall be limited to direct losses and under any circumstance be limited to 300,000 USD.



Form code: TA 251

Revision: 2021-03

www.dnv.com

Page 1 of 2

Product description

"Bolidt Helideck G2 Compound",
is a floor covering consisting of three components A, B and C (mixing ratio A : B : C (weight): 56.3 : 10.4 : 33.3, density 1780 kg/m³), based on modified polyol resin and aromatic polyisocyanate prepolymers applied on top of a 60 µm thick layer of "BOLIDT PRIMER PU/LP 2580".

Max. total thickness is 2.8 mm.

Application/Limitation

Approved for use as low flame spread surface material, not generating excessive quantities of smoke nor toxic products in fire.

Approved for use as floor coverings on any low flame-spread covering, steel, or non-combustible material.

Approved for all colour variations.

Max. organic content: 36 %.

Each product is to be supplied with its manual for installation and maintenance.

Type Approval documentation

Certification in accordance with Class Programme DNV-CP-0338, September 2021.

Test report No. 20668502-10a, APS4-Hau/Lov dated 9 October 2017 from DMT, Dortmund, Germany.

Test report No. 20668502-20a-3, APS4-Hau/Püs dated 9 October 2017 from DMT, Dortmund, Germany.

Tests carried out

Tested according to IMO 2010 FTP Code Part 5 and 2.

Marking of product

The product or packing is to be marked with name of manufacturer, type designation and fire-technical rating.

Transport Canada Approval

Based on the procedures laid down in the Transport Canada Publication entitled "Procedures for Approval of Life-Saving Appliances, Fire Safety Systems, Equipment and Products (TP14612)", DNV confirms that the product/s listed in this certificate is/are in accordance with Transport Canada's requirements.

Periodical assessment

DNV's surveyor is to be given permission to perform Periodical Assessments at any time during the validity of this certificate and at least every second year. The arrangement is to be in accordance with procedure described in Class Programme DNV-CP-0338, Section 4.