DNV·GL

Certificate No:
TAK000002N

TYPE APPROVAL CERTIFICATE

This is to certify:

That the Protective Coating Systems - Seawater Ballast Tanks

with type designation(s)
KOREPOX EH2030

Issued to
KCC Corporation, Ulsan Plant
Ulsan, Republic of Korea

is found to comply with
Det Norske Veritas' Type Approval Programme 1-602.1, 2011, Protective Coating Systems - Seawater Ballast Tanks and Double-side Skin Spaces
IMO Resolution MSC.215(82) Performance Standard for Protective Coatings (PSPC)
IACS Unified Interpretations SC223. For Application of SOLAS Regulation II-1/3-2 Performance Standard for Protective Coatings (PSPC) for Dedicated Seawater Ballast Tanks in All Types of Ships and Double-side Skin Spaces of Bulk Carriers.

Application :

For use in ballast tanks, double-skin spaces, cofferdams and similar areas. Surface preparation and coating application as per PSPC or manufacturer's recommendations, whichever is stricter.

Product(s) approved by this certificate is/are accepted for installation on all vessels classed by DNV GL.

This Certificate is valid until **2018-12-30**.

Issued at **Høvik** on **2015-08-24**

for **DNV GL**

DNV GL local station: **Ulsan**

Approval Engineer: **Gisle Hersvik**

Martin Strande
Head of Section

This Certificate is subject to terms and conditions overleaf. Any significant change in design or construction may render this Certificate invalid.

© DNV GL 2014. DNV GL and the Horizon Graphic are trademarks of DNV GL AS.

The validity date relates to the Type Approval Certificate and not to the approval of equipment/systems installed.

Product description

KOREPOX EH2030; two-component, epoxy based, self-priming, aluminium pigmented coating for corrosion protection of steel surfaces.

Application/Limitation

This approval is solely connected to the corrosion prevention properties of the coating material. The approval does not include any evaluation of toxicity, contamination, pollution, or fire technical properties.

KOREPOX EH2030 is approved for application on blast cleaned surfaces and on prequalified shop primed surfaces. The following shop primers have been prequalified:

Galvany Shopprimer IZ182(J)	[KCC Corp.]
Galvany Shopprimer IZ182(S)	[KCC Corp.]
Rainbow SP-09 (SP-09 Cathozinc Shop Primer, Type-2)	[Yung Chi Paint & Varnish Mfg. Co]

Surface preparation and coating application as per PSPC or manufacturer's recommendations, whichever is stricter.

The durability of the applied coating system will depend on the steel surface preparation, coating application and the environmental conditions.

The Type Approval Certificate is invalid if the formulation of the epoxy coating **KOREPOX EH2030** is changed to a degree deemed significant by DNV GL. If the formulation of any of the listed pre-qualified shop primers is changed to a degree deemed significant by DNV GL that shop primer cannot be used as part of the Protective Coating System.

Type Approval documentation
Tests carried out

Type Testing carried out in accordance with **Type Approval documentation**. The tests reported in the Korea Conformity Laboratories (KCL) and Korea Testing & Research Institute (KTR) Test Reports are carried out according to the procedures in IMO Resolution MSC.215(82)) Performance Standard for Protective Coatings (PSPC), ref. IACS UI SC223;

- Korea Conformity Laboratories (KCL) Technical Report No. KCL-PSPC-012, Rev. 00, "Ballast Tank Protective Coating Test of 2*160 μm KOREPOX EH2030(New Version) on Galvany shopprimer IZ182(J)" of 2014-04-07.
- Korea Conformity Laboratories (KCL) Technical Report No. KCL-PSPC-016, Rev. 00, "Ballast Tank Protective Coating Test of 2*160 μm KOREPOX EH2030(New Version) on SP-09" of 2014-04-07.
- KTR Technical Report No. KTR-PSPC-125, Rev. 00 "Ballast Tank Protective Coating Test of 2*160 μm EH2030 on IZ182(S)" of 2015-04-22.

Marking of product

Product/package shall be marked with *manufacturer's name and address*; **KCC Corporation (Ulsan Plant), Korea** and *type designation*; **KOREPOX EH2030**, and *date of production/batch number*.

The marking is to be carried out in such a way that it is visible, legible and indelible. The marking of product is to enable traceability to the DNV GL Type Approval Certificate.

Periodical assessment

The scope of the Periodical Assessment is to verify that the conditions stipulated for the Type Approval is complied with and that no alterations are made to the product design or choice of materials.

Periodical Assessment to be performed after two (2) years (Certificate Retention) and at renewal after four (4) years (Certificate Renewal).

The main elements of the Periodical Assessment are to:

- Ensure that **Type Approval documentation** is available.
- Review design, materials, production process, and performance with respect to possible changes, in order to ensure compliance with **Type Approval documentation** and/or referenced material specifications.
- Ensure traceability between manufacturer's product marking and the DNV GL Type Approval Certificate.

END OF CERTIFICATE