

TYPE APPROVAL CERTIFICATE

This is to certify:**That the TBT-Free Anti-Fouling Systems**with type designation(s)
Interspeed 340

Issued to

International Paint Limited
GATESHEAD, TYNE AND WEAR, United Kingdom

is found to comply with

DNV GL class programme DNVGL-CP-0110 – Type approval – Anti-fouling systems**Application :****Organotin-free controlled depletion polymer anti-fouling system.****Product(s) approved by this certificate is/are accepted for installation on all vessels classed by DNV GL.**This Certificate is valid until **2021-06-29**.Issued at **Høvik** on **2016-06-30**DNV GL local station: **Newcastle-upon-Tyne**for **DNV GL**Approval Engineer: **Gisle Hersvik**

Arnstein Gloppen
Head of Section

This Certificate is subject to terms and conditions overleaf. Any significant change in design or construction may render this Certificate invalid. The validity date relates to the Type Approval Certificate and not to the approval of equipment/systems installed.

Job Id: **262.1-022235-1**
Certificate No: **TAK00000DR**

Product description

Organotin-free controlled depletion polymer anti-fouling paint; **Interspeed 340**

Colours:

This product is available in various colours. Please contact your local International Paint Representative for details.

Active ingredients:

CAS No. 1317-39-1 Copper(1) oxide
CAS No. 12122-67-7 Zineb

Manufactured by

International Paint Limited, Stoneygate Lane, Felling, Gateshead, Tyne & Wear, NE10 0JY, United Kingdom

DNV GL local office: Newcastle-upon-Tyne

Responsibility

The Company (stated on the front page of this Certificate) takes the responsibility that both design and production are in compliance with Rules, Standards and/or Regulations listed on page 1 of this certificate.

Application/Limitation

The issuance of this certificate is solely connected to the control of the Anti-Fouling System, AFS, with regard to compliance with the International Convention on the Control of Harmful Anti-Fouling Systems on Ships.

It does not cover verification of surface preparation, corrosion protection, fire, health and safety precautions, durability of the AFS or environmental properties other than regulated by the Convention.

Type Approval documentation

- 1.
- 2.
- 3.

Tests carried out

Type Testing carried out according to **Type Approval documentation**, with the following test results, ref. Test Report from SINTEF Kjemi, Oslo, Norway of 2003-12-10:

- **Interspeed 340:** 0.12 % tin (No TBT-compounds detected)

Marking of product

Product shall be marked with *manufacturer's name*; **International Paint Limited**, *place of production* and *type designation*.

The marking is to be carried out in such a way that it is visible, legible and indelible. The marking of product is to enable traceability to the DNV GL Type Approval Certificate.

Job Id: **262.1-022235-1**
Certificate No: **TAK00000DR**

Periodical assessment

The scope of the Periodical Assessment is to verify that the conditions stipulated for the Type Approval is complied with and that no alterations are made to the product design or choice of materials.

Periodical Assessment to be performed after 2 years (Certificate Retention) and at renewal after 5 years (Certificate Renewal).

The main elements of the Periodical Assessment are to:

- Ensure that **Type Approval documentation** is available.
- Review design, materials, production process, and performance with respect to possible changes, in order to ensure compliance with **Type Approval documentation** and/or referenced material specifications.
- Ensure traceability between manufacturer's product marking and the DNV GL Type Approval Certificate.

END OF CERTIFICATE