

TYPE APPROVAL CERTIFICATE

This is to certify:**That the Protective Coating Systems - Cargo Oil Tanks**

with type designation(s)

Transpoxy Masterbond BT

Issued to

Transocean Coatings B.V.
Rotterdam, Netherlands

is found to comply with

DNV GL class programme DNVGL-CP-0139 – Type approval – Protective coating systems for cargo oil tanks**IMO Resolution MSC.288(87) Performance Standard for Protective Coatings (PSPC)****IACS Unified Interpretations SC259. For Application of SOLAS Regulation II-1/3-11****Performance Standard for Protective Coatings for Cargo Oil Tanks of Crude Oil Tankers (PSPC-COT), adopted by Resolution MSC.288(87).****Application :****For use in cargo oil tanks of crude oil tankers. Surface preparation and coating application as per PSPC or manufacturer's recommendations, whichever is stricter.****Product(s) approved by this certificate is/are accepted for installation on all vessels classed by DNV GL.**This Certificate is valid until **2021-09-29**.Issued at **Høvik** on **2016-09-30**DNV GL local station: **Rotterdam, Product Certification /Verification**for **DNV GL**Approval Engineer: **Stefan Marion**-----
Martin Strande
Head of Section

This Certificate is subject to terms and conditions overleaf. Any significant change in design or construction may render this Certificate invalid. The validity date relates to the Type Approval Certificate and not to the approval of equipment/systems installed.

Product description

Transpoxy Masterbond BT; high solids epoxy coating

Application/Limitation

This approval is solely connected to the corrosion prevention properties of the coating material. The approval does not include any evaluation of toxicity, contamination, pollution, or fire technical properties.

Transpoxy Masterbond BT is approved for application on blast cleaned surfaces and on shop primed surfaces. The following shop primers are prequalified:

Transoweld Primer	[Transocean Coatings B.V.]
SigmaWeld 199	[PPG/Sigma Coatings]
Muki Z 2001	[Jotun A/S]
Hempel's Shopprimer ZS 15890	[Hempel A/S]
Interplate 855	[International Paint]

Surface preparation and coating application as per PSPC or manufacturer's recommendations, whichever is stricter.

The durability of the applied coating system will depend on the steel surface preparation, coating application and the environmental conditions.

The Type Approval Certificate is invalid if the formulation of the epoxy coating **Transpoxy Masterbond BT** is changed to a degree deemed significant by DNV GL. If the formulation of any of the listed pre-qualified shop primers is changed to a degree deemed significant by DNV GL that shop primer cannot be used as part of the Protective Coating System.

Type Approval documentation

- 1.
- 2.
- 3.

Tests carried out

Type Testing carried out in accordance with **Type Approval documentation**. The tests carried out at COT bv, Netherlands are in accordance with procedures in IMO Resolution MSC.288(82) Performance Standard for Protective Coatings (PSPC), ref. IACS UI SC 259;

- Test Report from COT bv, Report No. LAB13-0763-REP of 2014-02-21
- Test Report from COT bv, Report No. LAB11-0957-REP of 2011-11-28
- Test Report from COT bv, Report No. LAB11-0959-REP of 2011-11-28
- Test Report from COT bv, Report No. LAB11-0961-REP of 2011-11-28
- Test Report from COT bv, Report No. LAB11-0960-REP of 2011-11-28

Marking of product

Product/package shall be marked with *manufacturer's name and address*; **Transocean Coating B.V.**, *type designation*; **Transpoxy Masterbond BT**, and *date of production/batch number*.

The marking is to be carried out in such a way that it is visible, legible and indelible. The marking of product is to enable traceability to the DNV GL Type Approval Certificate.

Job Id: **262.1-021685-1**
Certificate No: **TAK00000GB**

Periodical assessment

The scope of the Periodical Assessment is to verify that the conditions stipulated for the Type Approval is complied with and that no alterations are made to the product design or choice of materials.

Periodical Assessment to be performed after two (2) years (Certificate Retention) and at renewal after five (5) years (Certificate Renewal).

The main elements of the Periodical Assessment are to:

- Ensure that **Type Approval documentation** is available.
- Review design, materials, production process, and performance with respect to possible changes, in order to ensure compliance with **Type Approval documentation** and/or referenced material specifications.
- Ensure traceability between manufacturer's product marking and the DNV GL Type Approval Certificate.

END OF CERTIFICATE