DNV·GL

Certificate No:
TAK00001EX

TYPE APPROVAL CERTIFICATE

This is to certify:

That the Protective Coating Systems - Seawater Ballast Tanks

with type designation(s)
BANNOH 1500 and BANNOH 1500 QD

Issued to
Chugoku Marine Paints, Ltd. (Hiroshima Head Office)
Otake City, Hiroshima Pref. 739-0652,
Japan

is found to comply with
DNV GL class programme DNVGL-CP-0108 – Type approval – Protective coating systems for seawater ballast tanks and double-side skin spaces
IMO Resolution MSC.215(82) Performance Standard for Protective Coatings (PSPC)
IACS Unified Interpretations SC223. For Application of SOLAS Regulation II-1/3-2 Performance Standard for Protective Coatings (PSPC) for Dedicated Seawater Ballast Tanks in All Types of Ships and Double-side Skin Spaces of Bulk Carriers.

Application :

For use in ballast tanks, double-skin spaces, cofferdams and similar areas. Surface preparation and coating application as per PSPC or manufacturer's recommendations, whichever is stricter.

Product(s) approved by this certificate is/are accepted for installation on all vessels classed by DNV GL.

Issued at **Hamburg** on **2018-12-10**
This Certificate is valid until **2023-12-31**.
DNV GL local station: **Hiroshima**

for **DNV GL**

Approval Engineer: **Enno Brück**

Thorsten Lohmann
Head of Section

This Certificate is subject to terms and conditions overleaf. Any significant change in design or construction may render this Certificate invalid.
The validity date relates to the Type Approval Certificate and not to the approval of equipment/systems installed.

© DNV GL 2014. DNV GL and the Horizon Graphic are trademarks of DNV GL AS.

Job Id: **262.1-017777-2**
Certificate No: **TAK00001EX**

Product description

BANNOH 1500 and **BANNOH 1500 QD**; 2-component epoxy based coating for corrosion protection of steel surfaces.

Manufactured by

Chugoku Paints (Malaysia) SDN. BHD, PLO 430, Jalan Emas Dua, Pasir Gudang Industrial Estate, Pasir Gudang, Johor, Malaysia

DNV GL local office: Singapore

Responsibility

The Company (stated on the front page of this Certificate) takes the responsibility that both design and production are in compliance with Rules, Standards and/or Regulations listed on page 1 of this certificate.

Application/Limitation

This approval is solely connected to the corrosion prevention properties of the coating material. The approval does not include any evaluation of toxicity, contamination, pollution, or fire technical properties.

BANNOH 1500 and **BANNOH 1500 QD** are approved for application on blast cleaned surfaces and on shop primed surfaces. The following shop primer is prequalified:

- CERABOND 2000 [Chugoku Marine Paints, Ltd.]

Surface preparation and coating application as per PSPC or manufacturer's recommendations, whichever is stricter.

The durability of the applied coating system will depend on the steel surface preparation, coating application and the environmental conditions.

The Type Approval Certificate is invalid if the formulation of the epoxy coatings BANNOH 1500 and BANNOH 1500 QD are changed to a degree deemed significant by DNV GL. If the formulation of any of the listed pre-qualified shop primers is changed to a degree deemed significant by DNV GL that shop primer cannot be used as part of the Protective Coating System.

Tests carried out

Type Testing carried out in accordance with DNV GL CP-0108. The tests are carried out in accordance with procedures in IMO Resolution MSC.215(82) Performance Standard for Protective Coatings (PSPC), ref. IACS UI SC 223;

- DNV Technical Report No. 2011-5133/12R5QYR-31, Rev. 00 "Ballast Tank Testing of BANNOH 1500 (M2-43000A) on CERABOND 2000 (M2-10000A, M2-10000B) Shop Primer" of 2011-09-14.
- DNV Technical Report No. 2011-5140/12R5QYR-38, Rev. 00 "Ballast Tank Testing of BANNOH 1500 QD (M2-43010A) on CERABOND 2000 (M2-10000A, M2-10000B) Shop Primer" of 2011-10-05.

Marking of product

Product/package shall be marked with *manufacturer's name and address*; **Chugoku Marine Paints, Ltd.**, *place of production*, *type designation*; **BANNOH 1500 / BANNOH 1500 QD**, and *date of production/batch number*.

The marking is to be carried out in such a way that it is visible, legible and indelible. The marking of product is to enable traceability to the DNV GL Type Approval Certificate.

Periodical assessment

The scope of the Periodical Assessment is to verify that the conditions stipulated for the Type Approval is complied with and that no alterations are made to the product design or choice of materials.

Periodical Assessment to be performed after 2 and 3.5 years (Certificate Retention) and at renewal after 5 years (Certificate Renewal).

END OF CERTIFICATE