

TYPE APPROVAL CERTIFICATE

This is to certify:**That the Glass Fibre Products**

with type designation(s)

HiMax™ Glass Multiaxials**Uniaxial Fabrics; L (0°) (200 - 3500 g/m²) with or without F (50 - 600 g/m²),****Uniaxial Fabrics; T (90°) (2 - 3500 g/m²) with or without F (50 - 600 g/m²)**

Issued to

Hexcel Reinforcements UK Ltd**Cambridge, United Kingdom**

is found to comply with

DNV GL class programme DNVGL-CP-0467 – Type approval – Uni- and multi-axial multi-ply fabrics made of glass fibres**DNV GL rules for classification – High speed and light craft****DNV GL standard DNVGL-ST-0342 – Craft****Det Norske Veritas' Standards for Certification No. 2.20, Lifeboats and Rescue Boats, 2007****Application :****For use in marine vessels in accordance with stated Rules/Standards.**Issued at **Høvik** on **2019-02-24**This Certificate is valid until **2024-02-23**.DNV GL local station: **Manchester**for **DNV GL**Approval Engineer: **Gisle Hersvik**

Rikard Törnqvist
Head of Section

This Certificate is subject to terms and conditions overleaf. Any significant change in design or construction may render this Certificate invalid. The validity date relates to the Type Approval Certificate and not to the approval of equipment/systems installed.



Product description

HiMax™ Glass Multiaxials

Uni-axial Glass Fibre Products, of 0° and 90° orientation:

- E-glass uni-axial stitched and woven glass fibre fabrics
- L (0°) (200 - 3500 g/m²) with or without F (50 - 600 g/m²), and
- T (90°) (2 - 3500 g/m²) with or without F (50 - 600 g/m²).

Remarks:

L: Longitudinal

T: Transverse

F: Fleece (Micromesh/Veil/Nonwoven)

Applications/Limitations

The approval covers the weight ranges given above.

The fabric complies with the applicable requirements of DNV GL and is compatible to the laminating resin.

Any significant changes in design and / or quality of the material will render the approval invalid.

Type Approval documentation

Tests carried out

Type Testing carried out in accordance with **Type Approval documentation**.

Marking of product

Product shall be marked with *manufacturer's name*: **Hexcel Reinforcements UK Ltd, UK** and *Type Designation/Product Code, Description and Piece Number*.

The marking is to be carried out in such a way that it is visible, legible and indelible. The marking of product is to enable traceability to the DNV GL Type Approval Certificate.

Periodical assessment

The scope of the Periodical Assessment is to verify that the conditions stipulated for the Type Approval is complied with and that no alterations are made to the product design or choice of materials.

Periodical Assessment to be performed after 2 and 3.5 years (Certificate Retention) and at renewal after 5 years (Certificate Renewal).

The main elements of the Periodical Assessment are to:

- Ensure that **Type Approval documentation** is available.
- Review design, materials, production process, and performance with respect to possible changes, in order to ensure compliance with **Type Approval documentation** and/or referenced material specifications.
- Ensure traceability between manufacturer's product marking and the DNV GL Type Approval Certificate.

END OF CERTIFICATE