

TYPE APPROVAL CERTIFICATE

This is to certify:

That the TBT-Free Anti-Fouling Systems

with type designation(s)
SeaForce Shield

Issued to

Jotun A/S
SANDEFJORD, Norway

is found to comply with
DNV GL class programme DNVGL-CP-0110 – Type approval – Anti-fouling systems

Application :

Organotin-free self-polishing anti-fouling system.

Product(s) approved by this certificate is/are accepted for installation on all vessels classed by DNV GL.

This Certificate is valid until **2024-05-15**.

Issued at **Høvik** on **2019-05-16**

DNV GL local station: **Sandefjord**

for **DNV GL**

Approval Engineer: **Gisle Hersvik**

Rikard Törnqvist
Head of Section

This Certificate is subject to terms and conditions overleaf. Any significant change in design or construction may render this Certificate invalid. The validity date relates to the Type Approval Certificate and not to the approval of equipment/systems installed.

Job Id: **262.1-031207-1**
Certificate No: **TAK00001KV**

Product description

Organotin-free self-polishing hydrolysing anti-fouling paint; **SeaForce Shield**

Colours:

The product may be available in various colours. Please contact the local Jotun representative for details.

Active ingredients:

CAS No. 1317-39-1 Cuprous oxide
CAS No. 12122-67-7 Zineb

Manufactured by

Jotun COSCO Marine Coatings (Qingdao) Co., Ltd., South of Chunyang Road and East of Huaguan Road, Qingdao National High-tech Industrial Development Zone, Qingdao, Shandong 166109, P.R.China

DNV GL local station: Qingdao

Jotun Coatings (Zhangjiagang) Co. Ltd., Jiangsu Yangtze River Internat. Chemical Industry Park, Zhangjiagang Free Trade Zone, Jiangsu 215634, P.R. China

DNV GL local station: Nanjing

Chokwang Jotun Ltd., 30th Block Jisa Science Park, 1205 Jisa-dong, Gangseo-gu, Busan 618-230, South Korea.

DNV GL local station: Pusan

Jotun Paints (M) Sdn Bhd, Lot 9143, PN 38500, Kawasan Perindustrian Nilai, 71800 Nilai, Negeri Sembilan, Malaysia

DNV GL local station: Kuala Lumpur

Jotun U.A.E Ltd. (L.L.C.), P.O.Box 3671, Al Quoz Industrial Area, Dubai, U.A.E.

DNV GL local station: Dubai

Responsibility

The Company (stated on the front page of this Certificate) takes the responsibility that both design and production are in compliance with Rules, Standards and/or Regulations listed on page 1 of this certificate.

Application/Limitation

The issuance of this certificate is solely connected to the control of the Anti-Fouling System, AFS, with regard to compliance with the International Convention on the Control of Harmful Anti-Fouling Systems on Ships.

It does not cover verification of surface preparation, corrosion protection, fire, health and safety precautions, durability of the AFS or environmental properties other than regulated by the Convention.

Type Approval documentation

Tests carried out

Job Id: **262.1-031207-1**
Certificate No: **TAK00001KV**

Type Testing carried out in accordance with **Type Approval documentation**, with the following test results (ref. Test Report from Molab as, Norway of 2019-02-27):

- **SeaForce Shield:** <0.02 wt% tin

Marking of product

Product shall be marked with *manufacturer's name; place of production and type designation*.

The marking is to be carried out in such a way that it is visible, legible and indelible. The marking of product is to enable traceability to the DNV GL Type Approval Certificate.

Periodical assessment

The scope of the Periodical Assessment is to verify that the conditions stipulated for the Type Approval is complied with and that no alterations are made to the product design or choice of materials.

Periodical Assessment to be performed after 2 and 3.5 years (Certificate Retention) and at renewal after 5 years (Certificate Renewal).

The main elements of the Periodical Assessment are to:

- Ensure that **Type Approval documentation** is available.
- Review design, materials, production process, and performance with respect to possible changes, in order to ensure compliance with **Type Approval documentation** and/or referenced material specifications.
- Ensure traceability between manufacturer's product marking and the DNV GL Type Approval Certificate.

END OF CERTIFICATE