

TYPE APPROVAL CERTIFICATE

This is to certify:**That the Sandwich Core Materials**with type designation(s)
Atlas HPE 120

Issued to

NMG EUROPE S.r.l.
Gorizia, GO, Italy

is found to comply with

DNV GL class programme DNVGL-CP-0084 – Type approval – Sandwich core materials**Application :****Manufacturing of sandwich - structured composites**Issued at **Hamburg** on **2020-06-25**This Certificate is valid until **2025-06-24**.for **DNV GL**DNV GL local station: **Italy/Malta CMC**Approval Engineer: **Joachim Rehbein**

Thorsten Lohmann
Head of Section

This Certificate is subject to terms and conditions overleaf. Any significant change in design or construction may render this Certificate invalid. The validity date relates to the Type Approval Certificate and not to the approval of equipment/systems installed.

LEGAL DISCLAIMER: Unless otherwise stated in the applicable contract with the holder of this document, or following from mandatory law, the liability of DNV GL AS, its parent companies and subsidiaries as well as their officers, directors and employees ("DNV GL") arising from or in connection with the services rendered for the purpose of the issuance of this document or reliance thereon, whether in contract or in tort (including negligence), shall be limited to direct losses and under any circumstance be limited to 300,000 USD.



Job Id: **262.1-031454-1**
Certificate No: **TAK00001WW**

Product description

Atlas HPE: IPN polyether based closed cell foam

Material Properties

Variant	Nominal Density (1)	Density Range (1)	Compr. Strength (2)	Compr. Modulus (2)	Shear Strength (3)	Shear Modulus (3)
HPE 120	125	118 - 130	1.31 (1.15)	78.0 (69.0)	1.18 (1.16)	26.7 (26.30)

(1) Density according to ISO 845 in kg/m³

(2) Compressive properties according to ISO 844:2014, procedure B in MPa.

(3) Shear properties according to ISO 1922 in MPa.

All values are average values and verified by testing. The values within brackets are minimum values.

Application/Limitation

Core material for construction of FRP sandwich laminates.

The foam complies with the applicable requirements of DNV GL and is compatible to the laminating resin and/or adhesive.

Any significant changes in design and / or quality of the material will render the approval invalid.

Type Approval documentation

Assessed production site

NMG Europe S.r.l.
Via del San Michele 347/349
34170 Gorizia
Italy

Marking of product

Product shall be marked with *manufacturer's name, place of production and type designation*.

The marking is to be carried out in such a way that it is visible, legible and indelible. The marking of product is to enable traceability to the DNV GL Type Approval Certificate.

Periodical assessment

The scope of the Periodical Assessment is to verify that the conditions stipulated for the Type Approval are complied with and that no alterations are made to the product design or choice of materials. For retention of the Type Approval, a DNV GL Surveyor shall perform periodical assessment after two years (+/- 90 days) and after 3.5 years (+/- 90 days) to verify that the conditions for the approval are complied with. Reference is made to DNVGL-CP-0338.

A production site with a valid Approval of Manufacturer (AoM) certificate for material in question is exempted from the obligation concerning retention and renewal assessments.

END OF CERTIFICATE