

TYPE APPROVAL CERTIFICATE

This is to certify:**That the Protective Coating Systems - Seawater Ballast Tanks**

with type designation(s)

Jotacote F60 6A + Jotacote Universal N10

Issued to

Jotun A/S**SANDEFJORD, Norway**

is found to comply with

DNV GL class programme DNVGL-CP-0108 – Type approval – Protective coating systems for seawater ballast tanks and double-side skin spaces**IMO Resolution MSC.215(82) Performance Standard for Protective Coatings (PSPC)****IACS Unified Interpretations SC223. For Application of SOLAS Regulation II-1/3-2****Performance Standard for Protective Coatings (PSPC) for Dedicated Seawater Ballast Tanks in All Types of Ships and Double-side Skin Spaces of Bulk Carriers.****Application :****Product(s) approved by this certificate is/are accepted for installation on all vessels classed by DNV GL.**Issued at **Hamburg** on **2020-10-15**This Certificate is valid until **2025-10-14**.for **DNV GL**DNV GL local station: **Sandefjord**Approval Engineer: **Enno Brück**

Thorsten Lohmann
Head of Section

This Certificate is subject to terms and conditions overleaf. Any significant change in design or construction may render this Certificate invalid. The validity date relates to the Type Approval Certificate and not to the approval of equipment/systems installed.

LEGAL DISCLAIMER: Unless otherwise stated in the applicable contract with the holder of this document, or following from mandatory law, the liability of DNV GL AS, its parent companies and subsidiaries as well as their officers, directors and employees ("DNV GL") arising from or in connection with the services rendered for the purpose of the issuance of this document or reliance thereon, whether in contract or in tort (including negligence), shall be limited to direct losses and under any circumstance be limited to 300,000 USD.



Product description

JOTACOTE F60 6A + JOTACOTE UNIVERSAL N10, 2-component epoxy based holding primer and 2-component epoxy based, light coloured, coating for corrosion protection of steel surfaces.

Manufactured by

Nor-Maali OY, Vanhatie 20, 15240 Lahti, Finland

DNV GL local station: Helsinki

Responsibility

The Company (stated on the front page of this Certificate) takes the responsibility that both design and production are in compliance with Rules, Standards and/or Regulations listed on page 1 of this certificate.

Application/Limitation

This approval is solely connected to the corrosion prevention properties of the coating material. The approval does not include any evaluation of toxicity, contamination, pollution, or fire technical properties.

JOTACOTE F60 6A + JOTACOTE UNIVERSAL N10 is approved for application on blast cleaned surfaces and on prequalified shop primed surfaces. The following shop primers have been prequalified:

- | | |
|--------------------------------|---------------------------------|
| - MUKI Z 2001 | [Jotun A/S] |
| - MUKI Z 2008 | [Jotun A/S] |
| - Hempel's Shopprimer ZS 15890 | [Hempel A/S] |
| - TH-2 | [Yejian New Material Co., Ltd.] |
| - SigmaWeld 165 | [PPG / Sigma Coatings] |
| - Galvany IZ 182(J) | [KCC Corporation] |
| - Galvany IZ 182(S) | [KCC Corporation] |
| - KCI Zinc 1000 | [Kangnam Jevisco Co., Ltd.] |
| - Cerabond 2000 | [Chugoku Marine Paints] |

- The holding primer Jotacote F60 6A is manufactured by Jotun Paints (Europe) Ltd.

Surface preparation and coating application as per PSPC or manufacturer's recommendations, whichever is stricter.

The durability of the applied coating system will depend on the steel surface preparation, coating application and the environmental conditions.

The Type Approval Certificate is invalid if the formulation of the epoxy coatings **JOTACOTE F60 6A** and **JOTACOTE UNIVERSAL N10** are changed to a degree deemed significant by DNV GL. If the formulation of any of the listed pre-qualified shop primers is changed to a degree deemed significant by DNV GL that shop primer cannot be used as part of the Protective Coating System.

Tests carried out

Type Testing carried out in accordance with DNV GL CP-0108. The tests reported are carried out in accordance with the test procedures in IMO Resolution MSC.215(82) Performance Standard for Protective Coatings (PSPC), ref. IACS UI SC223;

- DNV GL Technical Report No. 2016-5189, Rev. 00, of 2016-08-08.
- DNV Technical Report No. 2012-5029 / 13FNOZF-5, Rev. 00, of 2012-08-17
- DNV Technical Report No. 2012-5039 / 13FNOZF-15, Rev. 00, of 2012-08-30

Job Id: **262.1-034647-1**
Certificate No: **TAK00001YM**

- DNV Technical Report No. 2012-5041 / 13FNOZF-17, Rev. 00, of 2012-08-31
- DNV Technical Report No. 2012-5042 / 13FNOZF-18, Rev. 01, of 2012-11-13.
- DNV Technical Report No. 2012-5284 / 1497VAP-14, Rev. 00, of 2013-04-04.
- DNV Technical Report No. 2012-5288 / 1497VAP-18, Rev. 00, of 2013-04-10.
- DNV GL Technical Report No. 2013-5410, Rev. 00, of 2014-02-28.
- DNV GL Technical Report No. 2015-5293, Rev. 00, of 2015-06-12.
- DNV GL Technical Report No. 2015-5567, Rev. 00, of 2015-12-03.

Marking of product

Product/package shall be marked with *manufacturer's name and address*; **Nor-Maali OY Finland**, *type designation*; **JOTACOTE F60 6A** and **JOTACOTE UNIVERSAL N10**, and *date of production/batch number*.

The marking is to be carried out in such a way that it is visible, legible and indelible. The marking of product is to enable traceability to the DNV GL Type Approval Certificate.

Periodical assessment

The scope of the Periodical Assessment is to verify that the conditions stipulated for the Type Approval is complied with and that no alterations are made to the product design or choice of materials.

Periodical Assessment (Certificate Retention) and renewal after 5 years (Certificate Renewal) shall be performed acc. DNV GL CP-0338.

END OF CERTIFICATE