



Certificate No:
TAK0000278

TYPE APPROVAL CERTIFICATE

This is to certify:

That the Protective Coating Systems - Seawater Ballast Tanks

with type designation(s)
Jotacote Universal S110 WG

Issued to

Jotun A/S
SANDEFJORD, Norway

is found to comply with

DNV class programme DNV-CP-0108 – Type approval – Protective coating systems for seawater ballast tanks and double-side skin spaces
IMO Resolution MSC.215(82) Performance Standard for Protective Coatings (PSPC)
IACS Unified Interpretations SC223. For Application of SOLAS Regulation II-1/3-2 Performance Standard for Protective Coatings (PSPC) for Dedicated Seawater Ballast Tanks in All Types of Ships and Double-side Skin Spaces of Bulk Carriers.

Application :

For use in ballast tanks, double-skin spaces, cofferdams and similar areas. Surface preparation and coating application as per PSPC or manufacturer's recommendations, whichever is stricter.

Product(s) approved by this certificate is/are accepted for installation on all vessels classed by DNV.

Issued at **Hamburg** on **2023-02-03**

This Certificate is valid until **2028-02-02**.

DNV local unit: **East & South Norway CMC**

for **DNV**

Approval Engineer: **Gisle Hersvik**

Thorsten Lohmann
Head of Section

This Certificate is subject to terms and conditions overleaf. Any significant change in design or construction may render this Certificate invalid. The validity date relates to the Type Approval Certificate and not to the approval of equipment/systems installed.

LEGAL DISCLAIMER: Unless otherwise stated in the applicable contract with the holder of this document, or following from mandatory law, the liability of DNV AS, its parent companies and their subsidiaries as well as their officers, directors and employees ("DNV") arising from or in connection with the services rendered for the purpose of the issuance of this document or reliance thereon, whether in contract or in tort (including negligence), shall be limited to direct losses and under any circumstance be limited to 300,000 USD.



Form code: TA 251

Revision: 2022-12

www.dnv.com

Page 1 of 3

Product description

Jotacote Universal S110 WG (2 x 160 µm): a two-component polyamine cured epoxy coating.

Manufactured by

Chokwang Jotun Ltd., 30th Block Jisa Science Park, 1205 Jisa-dong, Gangseo-gu, Busan 606-063, Republic of Korea

DNV local office: Busan

Responsibility

The Company (stated on the front page of this Certificate) takes the responsibility that both design and production are in compliance with Rules, Standards and/or Regulations listed on page 1 of this certificate.

Application/Limitation

This approval is solely connected to the corrosion prevention properties of the coating material. The approval does not include any evaluation of toxicity, contamination, pollution, or fire technical properties.

Jotacote Universal S110 WG (2 x 160 µm) is approved for application on blast cleaned surfaces and on prequalified shop primed surfaces. The following shop primers have been prequalified:

- | | |
|---------------------|----------------------------|
| - Muki Z 2001 | [Jotun A/S] |
| - Galvany IZ 182(J) | [KCC Corporation] |
| - Galvany IZ 182(K) | [KCC Corporation] |
| - Galvany IZ 182(S) | [KCC Corporation] |
| - Interplate 8010 | [International Paint Ltd.] |

Surface preparation and coating application according to PSPC or manufacturer's recommendations, whichever is stricter.

The durability of the applied coating system will depend on the steel surface preparation, coating application and the environmental conditions.

The Type Approval Certificate is invalid if the formulation of the epoxy coating **Jotacote Universal S110 WG** is changed to a degree deemed significant by DNV. If the formulation of the listed pre-qualified shop primers is changed to a degree deemed significant by DNV the shop primer cannot be used as part of the Protective Coating System.

Type Approval documentation

Tests carried out

Type Testing carried out in accordance with **Type Approval documentation** and DNV-CP-0108. The tests are carried out according to the procedures in IMO Resolution MSC.215(82) Performance Standard for Protective Coatings (PSPC), ref. IACS UI SC223:

- DNV Test Report No.: 2021-5396, Rev.01, "Ballast tank coating test of 2x160 Jotacote Universal S110 WG on Muki Z 2001 shop primer", dated 2022-02-23.
- DNV Test Report No.: 2021-5403, Rev.01, "Crossover coating test of 2x160 Jotacote Universal S110 WG on Galvany IZ 182(K) shop primer", dated 2022-02-23.
- DNV Test Report No.: 2021-5407, Rev.01, "Crossover coating test of 2x160 Jotacote Universal S110 WG on Interplate 8010 shop primer", dated 2022-02-23.
- KTR Test Report No.: KTR-PSPC-444, Rev.00, "Ballast tank protective coating test of 2*160 Jotacote Universal S110 WG + Jotacote Universal S110 WG on IZ182(J)", dated 2022-11-10.
- KTR Test Report No.: KTR-PSPC-441, Rev.00, "Ballast tank protective coating test of 2*160 Jotacote Universal S110 WG + Jotacote Universal S110 WG on IZ182(S)", dated 2022-11-10.

Marking of product

Product/package shall be marked with *manufacturer's name and address*; **Chokwang Jotun Ltd, Republic of Korea** *type designation* **Jotacote Universal S110 WG**, and *date of production/batch number*.



Job Id: **262.1-039188-1**
Certificate No: **TAK0000278**

The marking is to be carried out in such a way that it is visible, legible and indelible. The marking of product is to enable traceability to the DNV Type Approval Certificate.

Periodical assessment

The scope of the Periodical Assessment is to verify that the conditions stipulated for the Type Approval is complied with and that no alterations are made to the product design or choice of materials.

Periodical assessments (for Certificate Retention / Certificate Renewal) shall be performed according to DNV-CP-0338.

This certificate is only valid if required Periodical assessments are carried out with satisfactory results. To check the validity of this certificate, please look it up in <https://approvalfinder.dnv.com>

END OF CERTIFICATE