



Certificate no.:
TAK00002BD

TYPE APPROVAL CERTIFICATE

This is to certify:

that the **Carbon Fibre Products**

with type designation(s)

Quadri-axials: (0°/+45°/90°/-45°)-Series (600-2000 g/m²)

issued to

Formosa Taffeta Co., Ltd.
Yunlin County, Taiwan Region

is found to comply with

DNV class programme DNV-CP-0434 – Type approval – Uni- and multi-axial multi-ply fabrics made of carbon fibres

DNV rules for classification – High speed and light craft

DNV standard DNV-ST-0342 – Craft

Application:

For use in marine vessels according to stated Rules/Standards.

Product(s) approved by this certificate is/are accepted for installation on all vessels classed by DNV.

Issued at **Hamburg** on **2024-01-22**

This Certificate is valid until **2029-01-21**.

for **DNV**

DNV local unit: **Kaohsiung**

Approval Engineer: **Gisle Hersvik**

This Certificate is subject to terms and conditions overleaf. Any significant change in design or construction may render this Certificate invalid.
The validity date relates to the Type Approval Certificate and not to the approval of equipment/systems installed.

LEGAL DISCLAIMER: Unless otherwise stated in the applicable contract with the holder of this document, or following from mandatory law, the liability of DNV AS, its parent companies and their subsidiaries as well as their officers, directors and employees ("DNV") arising from or in connection with the services rendered for the purpose of the issuance of this document or reliance thereon, whether in contract or in tort (including negligence), shall be limited to direct losses and under any circumstance be limited to 300,000 USD.



Form code: TA 251

Revision: 2023-09

www.dnv.com

Page 1 of 2

Product description

Quadri-axial Carbon Fibre products of 0°/+45°/90°/-45° orientations.
Weight range: 600-2000 g/m²

The following indicative properties have been verified by Type Testing of laminates:

Property	Test Method	ECMF25 - 800 g/m ³		
Tensile Strength – 90°	ISO 527–4,5	693	MPa	mean
Tensile Modulus – 90°	ISO 527–4,5	49.5	GPa	mean
Compressive Strength – 90°	ISO 14126	424	MPa	mean
Compressive Modulus – 90°	ISO 14126	52.0	GPa	mean
Flexural Strength – 90°	ISO 14125	868	MPa	mean
Fibre volume fraction, FVF	-	54.8 / 51.7	%	mean
Resin	WB-02AB (YU PO Chemical Co., Ltd.), Epoxy Resin/VARTM			
Curing Procedure for Type Testing	8 hrs at 80°C, demolding temperature below 50°C			

EC: Composite materials department
F: Designated fibre

M: Multi-axial braid
25: Product weight code (FAW:800g/m²)

Legend:

mean = Mean of Type Test results

Application/Limitation

Area of application will be evaluated during approval of classified objects.

Any significant changes in design and / or quality of the material will render the approval invalid.

Type Approval documentation

Tests carried out

Type Testing carried out in accordance with **Type Approval documentation**.

Marking of product

Product shall be marked with *manufacturer's name*: **Formosa Taffeta Co., Ltd., Taiwan Region** and *type designation*, and *length/lot number/gross weight/Net weight*.

The marking is to be carried out in such a way that it is visible, legible and indelible. The marking of product is to enable traceability to the DNV Type Approval Certificate.

Periodical assessment

The scope of the Periodical Assessment is to verify that the conditions stipulated for the Type Approval is complied with and that no alterations are made to the product design or choice of materials.

Periodical assessments (for Certificate Retention / Certificate Renewal) shall be performed according to DNV-CP-0338.

This certificate is only valid if required Periodical assessments are carried out with satisfactory results. To check the validity of this certificate, please look it up in <https://approvalfinder.dnv.com>

END OF CERTIFICATE