



Certificate no.:  
**TAK00002KU**

# TYPE APPROVAL CERTIFICATE

---

## This is to certify:

that the **Protective Coating Systems - Offshore Structures**

with type designation(s)

**IZ-01HS (1x60 µm) / Rainboprime 972 (1x160 µm) / UP-450HS (1x80 µm)**

issued to

**Yung Chi Paint & Varnish Mfg. Co., Ltd.**  
**Kaohsiung, Taiwan Region**

is found to comply with

**NORSOK Standard M-501 Surface preparation and protective coating, November 2022**

## Application:

---

**For use in Coating System defined by CSDS No. 1A in accordance with the stated Standard.**

**Protection of Carbon steel in Offshore and coastal environment, non-insulated, -50°C to +80°C.**

Issued at **Hamburg** on **2025-10-23**

This Certificate is valid until **2030-10-22**.

for **DNV**

DNV local unit: **Kaohsiung**

Approval Engineer: **Gisle Hersvik**

---

This Certificate is subject to terms and conditions overleaf. Any significant change in design or construction may render this Certificate invalid.  
The validity date relates to the Type Approval Certificate and not to the approval of equipment/systems installed.

LEGAL DISCLAIMER: Unless otherwise stated in the applicable contract with the holder of this document, or following from mandatory law, the liability of DNV AS, its parent companies and their subsidiaries as well as their officers, directors and employees ("DNV") arising from or in connection with the services rendered for the purpose of the issuance of this document or reliance thereon, whether in contract or in tort (including negligence), shall be limited to direct losses and under any circumstance be limited to 300,000 USD.

## Product description

### IZ-01HS (1x60 µm) / Rainboprime 972 (1x160 µm) / UP-450HS (1x80 µm)

Description of the Coating system, tested on bare steel:

- **IZ-01HS** Inorganic Zinc Rich Primer
- **Rainboprime 972** A high solids coating based on epoxy resin with glass flake anti-corrosive pigment
- **UP-450HS** High Build Polyurethane Coating

Coating system is defined by Coating System Data Sheet (CSDS) no. 1A of NORSOK M-501, Surface preparation and protective coating, November 2022, as having a zinc silicate primer, an epoxy coat and an UV-resistant topcoat with a total Minimum Dry Film Thickness (MDFT) of 300 µm.

|                                   |                                                                                                                                                                                                              |
|-----------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Corrosivity category:             | CX, ref. NS-EN ISO 12944-2                                                                                                                                                                                   |
| Items to be coated:               | Structures, structural components, frames, base plates, enclosures, permanent lifting beams and lugs, bridges, crane boom, A-frames, lifeboat stations and rescue areas, equipment items, piping and valves. |
| Service:                          | Offshore and coastal environment, non-insulated                                                                                                                                                              |
| Operating temperature range:      | -50°C to +80°C                                                                                                                                                                                               |
| Surface preparation requirements: | Refer to NORSOK M-501:2022, CSDS no. 1A                                                                                                                                                                      |

The maximum Dry Film Thickness (DFT) for each coat shall be within the limits given in the relevant Coating Application Data Sheet (CADS).

For details on CSDS no. 1A, please refer to Annex A of NORSOK M-501:2022.

## Application/Limitation

This approval is solely connected to the corrosion prevention properties of the coating system. The approval does not include any evaluation of toxicity, contamination, pollution, or fire technical aspects.

This Type Approval certificate is not valid for designs, components, equipment, systems or products which are subject to classification by DNV.

## Type Approval documentation

### Tests carried out

Type Testing carried out in accordance with **Type Approval documentation**, ref.:

- SGS Taiwan Ltd. Test Report No. KV-24-03751A "Norsok M-501:No. 1A IZ-01HS + Rainboprime 972 + UP-450HS" of 2025-09-26.

### Marking of product

Products forming parts of the coating system shall be marked with *manufacturer's name*: **Yung Chi Paint & Varnish Mfg. Co. Ltd., Taiwan Region**, *type designations*, *lot no.* and *manufacturing date*.

The marking is to be carried out in such a way that it is visible, legible and indelible.

### Periodical assessment

The scope of the Periodical Assessment is to verify that the conditions stipulated for the Type Approval is complied with and that no alterations are made to the product design or choice of materials.

Periodical assessments (for Certificate Retention / Certificate Renewal) shall be performed according to DNV-CP-0338.

This certificate is only valid if required Periodical assessments are carried out with satisfactory results. To check the validity of this certificate, please look it up in <https://approvalfinder.dnv.com>



END OF CERTIFICATE

Job ID: **262.1-041736-1**  
Certificate no.: **TAK00002KU**