



Certificate no.:
TAK00002N1

TYPE APPROVAL CERTIFICATE

This is to certify:

that the **Protective Coating Systems - Seawater Ballast Tanks**

with type designation(s)
Jotacote Universal N10

issued to

Jotun A/S
SANDEFJORD, Norway

is found to comply with

DNV class programme DNV-CP-0108 – Type approval – Protective coating systems for seawater ballast tanks and double-side skin spaces
IMO Resolution MSC.215(82) Performance Standard for Protective Coatings (PSPC)
IACS Unified Interpretations SC223. For Application of SOLAS Regulation II-1/3-2 Performance Standard for Protective Coatings (PSPC) for Dedicated Seawater Ballast Tanks in All Types of Ships and Double-side Skin Spaces of Bulk Carriers.
DNV rules for classification – Ships

Application:

For use in ballast tanks, double-skin spaces, cofferdams and similar areas. Surface preparation and coating application according to PSPC or manufacturer's recommendations, whichever is stricter.

Product(s) approved by this certificate is/are accepted for installation on all vessels classed by DNV.

Issued at **Hamburg** on **2026-02-16**

This Certificate is valid until **2031-02-15**.

DNV local unit: **Sandefjord**

for **DNV**

Approval Engineer: **Gisle Hersvik**

.....

This Certificate is subject to terms and conditions overleaf. Any significant change in design or construction may render this Certificate invalid. The validity date relates to the Type Approval Certificate and not to the approval of equipment/systems installed.

LEGAL DISCLAIMER: Unless otherwise stated in the applicable contract with the holder of this document, or following from mandatory law, the liability of DNV AS, its parent companies and their subsidiaries as well as their officers, directors and employees ("DNV") arising from or in connection with the services rendered for the purpose of the issuance of this document or reliance thereon, whether in contract or in tort (including negligence), shall be limited to direct losses and under any circumstance be limited to USD 300 000.

Product description

Jotacote Universal N10, 2-component epoxy-based coating for corrosion protection of steel surfaces.

Manufactured by

Jotun Brasil Importacao, Exportacao e Industria de Tintas Ltda., Estrada Ademar Ferreira Torres, S/N Caluge - Itaboraí (RJ) CEP 24808-520, Brazil

DNV local station: Rio de Janeiro

Responsibility

The Company (stated on the front page of this Certificate) takes the responsibility that both design and production are in compliance with Rules, Standards and/or Regulations listed on page 1 of this certificate

Application/Limitation

This approval is solely connected to the corrosion prevention properties of the coating material. The approval does not include any evaluation of toxicity, contamination, pollution, or fire technical properties.

Jotacote Universal N10 is approved for application on blast cleaned surfaces and on shop primed surfaces. The following shop primers are prequalified:

- Muki Z 2001	[Jotun AS]
- Muki Z 2008	[Jotun AS]
- Galvany Shopprimer IZ182(J)	[KCC Corp.]
- SigmaWeld 165 (Sigma Proferral MC)	[PPG Coatings]
- SigmaWeld 199	[PPG Coatings]
- Cerabond 2000	[Chugoku Marine Paints]
- CD-SG906	[Ningbo Haidun Coating]
- KCI Zinc 1000	[Kangnam Jevisco Co., Ltd.]
- TH-2	[Jiangsu Yejian Anti-Corrosion Co., Ltd.]
- Hempel's Shopprimer ZS 15820	[Hempel A/S]
- Hempel's Shopprimer ZS 15890	[Hempel A/S]
- Interplate 855	[International Paint Ltd.]
- Interplate 937	[International Paint Ltd.]

Surface preparation and coating application according to PSPC or manufacturer's recommendations, whichever is stricter.

The durability of the applied coating system will depend on the steel surface preparation, coating application and the environmental conditions.

The Type Approval Certificate is invalid if the formulation of the epoxy coating **Jotacote Universal N10** is changed to a degree deemed significant by DNV. If the formulation of any of the listed pre-qualified shop primers is changed to a degree deemed significant by DNV that shop primer cannot be used as part of the Protective Coating System.

Type Approval documentation

Tests carried out

Type Testing carried out in accordance with **Type Approval documentation** and in accordance with DNV-CP-0108. The tests are carried out in accordance with the procedures in IMO Resolution MSC.215(82) Performance Standard for Protective Coatings (PSPC), ref. IACS UI SC223:

- DNV Technical Report No. 2012-5280 / 1497VAP-10, Rev. 00, "Ballast tank coating test of Jotacote Universal N10 on Muki Z 2001 shop primer" of 2013-03-20.
- DNV Technical Report No. 2012-5291 / 1497VAP -21, Rev. 00, "Crossover test of Jotacote Universal N10 on Muki Z 2008 shop primer" of 2013-03-20.
- DNV Technical Report No. 2012-5292 / 1497VAP -22, Rev. 00, "Crossover test of Jotacote Universal N10 on Cerabond 2000 shop primer" of 2013-03-20.
- DNV Technical Report No. 2012-5293 / 1497VAP -23, Rev. 00, "Crossover test of Jotacote Universal N10 on Sigmaweld 165 shop primer" of 2013-03-20.

- DNV Technical Report No. 2012-5294 / 1497VAP -24, Rev. 00, "Crossover test of Jotacote Universal N10 on Galvany IZ 182(J) shop primer" of 2013-03-20.
- DNV GL Technical Report No. 2013-5402, Rev. 00 "Crossover coating test of Jotacote Universal N10 on CD-SG 906 shop primer" of 2014-02-18.
- DNV GL Technical Report No. 2013-5409, Rev. 00 "Crossover coating test of Jotacote Universal N10 on TH-2 shop primer" of 2014-02-28.
- DNV GL Technical Report No. 2013-5411, Rev. 00 "Crossover coating test of Jotacote Universal N10 on KCI Zinc 1000 shop primer" of 2014-02-10.
- DNV GL Technical Report No. 2014-5539, Rev. 00 "Crossover coating test of Jotacote Universal N10 on Hempel Shopprimer 15890" of 2014-09-24.
- Test and Verification Center for Ship Materials on Coating and Paintings Technical Report No. JX17049, Jotacote Universal N10 over Hempel's Shopprimer ZS 15820, of 2017-03-06
- DNV GL Technical report No. 2015-5574, Rev.00 "Crossover coating test of Jotacote Universal N10 on Sigmaweld 199 shop primer" of 2015-12-08.
- DNV GL Technical Report No. 2017-5437 / 114150WN-15, Rev. 00, "Crossover test of Jotacote Universal N10 on Interplate 855" of 2018-02-09.
- DNV GL Technical Report No. 2017-5738 / 114150WN-15, Rev. 00, "Crossover test of Jotacote Universal N10 on Interplate 937" of 2014-09-24.

Marking of Product

Product/package shall be marked with *manufacturer's name*: **Jotun AS**, *place of manufacture*, *type designation*: **Jotacote Universal N10**, and *date of production/batch number*.

The marking is to be carried out in such a way that it is visible, legible and indelible. The marking of product is to enable traceability to the DNV Type Approval Certificate.

Periodical assessment

The scope of the Periodical Assessment is to verify that the conditions stipulated for the Type Approval is complied with and that no alterations are made to the product design or choice of materials.

Periodical assessments (for Certificate Retention / Certificate Renewal) shall be performed according to DNV-CP-0338.

This certificate is only valid if required Periodical assessments are carried out with satisfactory results. To check the validity of this certificate, please look it up in <https://approvalfinder.dnv.com>

END OF CERTIFICATE