DNV·GL

Certificate No:
TAP000017J

TYPE APPROVAL CERTIFICATE

This is to certify:

That the Tube Fittings

with type designation(s)
INOXPRES, STEELPRES

Issued to
RACCORDERIE METALLICHE S.P.A.
Campitello di Marcaria MN, Italy

is found to comply with
DNV GL rules for classification – Ships Pt.4 Ch.6 Piping systems
DNVGL-OS-D101 – Marine and machinery systems and equipment, Edition January 2018
DNV GL class programme DNVGL-CP-0185 – Type approval – Mechanical joints

Application :

Product(s) approved by this certificate is/are accepted for installation on vessels classed by DNV GL.

Type:	Temperature range:	Max. working press.:	Sizes:
INOXPRES	**-55 to 200°C (dependent on the sealing)**	**16 bar**	**15,18,22,28,35,42,54,76,89 & 108 mm**
STEELPRES	**-20 to 200°C (dependent on the sealing)**	**10 bar**	**15,18,22,28,35,42,54,76,89 & 108 mm**

Issued at **Høvik** on **2018-01-25**
This Certificate is valid until **2022-12-31**.
DNV GL local station: **Milan**

Approval Engineer: **Adel Samiei**

for **DNV GL**

Marianne Spæren Marveng
Head of Section

This Certificate is subject to terms and conditions overleaf. Any significant change in design or construction may render this Certificate invalid.
The validity date relates to the Type Approval Certificate and not to the approval of equipment/systems installed.

© DNV GL 2014. DNV GL and the Horizon Graphic are trademarks of DNV GL AS.

Job Id: **262.1-007797-5**
Certificate No: **TAP000017J**

Product description

Tube fittings of Compression coupling (press type) with internal elastomer sealing rings.

Materials:
Carbon steel (Steelpres): E195NBK EN 10305-3 (1.0034)
Stainless steel (INOXPres): UNI X5CrNiMo1712 [AISI316L] EN 10217-7

Couplings designations:
(Steelpres):381/450, 381/451, 381/900, 381/901, 385, 398, 397, 382, 392/A, 392, 389, 383/000, 383/001, 383/002, 383/003, 387, 390, 391, 393/000, 322

(INOX Press): 181/150, 181/151, 181/300, 181/301, 181/450, 181/451, 181/600, 181/601, 181/900, 181/901, 197, 198, 186, 182, 189, 189/M, 192, 183/000, 183/001, 183/002, 183/003, 185/000, 185/001, 185/002, 185/003, 187, 190, 187/R, 184/000, 184/001, 184/002, 184/003, 184/002 INOX, 184/003 INOX, 191, 193/002, 193/000, 193/006, 193/001, 195/000

Application/Limitation

Couplings covered by this certificate are approved to be used in class III piping systems in below applications:

- Flammable fluids (flash point ≤ 60°C)
  - Cargo oil lines [2]
  - Crude oil washing lines [2]
  - Vent lines
- Inert gas
  - Water seal effluent lines
  - Scrubber effluent lines
  - Main Lines [1] [2]
  - Distribution lines [2]
- Flammable fluids (flash point > 60°C)
  - Cargo Oil lines [2]
  - Fuel oil lines [1]
  - Lubricating oil lines [1]
  - Hydraulic oil [1]
  - Thermal oil [1]
- Fresh water
  - Cooling water system
  - Condensate return
  - Non-essential system
- Sanitary/drains/scuppers
  - Deck drains (internal) [3]
  - Sanitary drains
  - Scuppers and discharge (overboard)
- Sounding/vent
  - Water tanks/Dry spaces
  - Oil tanks (f.p. > 60°C) [1]
- Miscellaneous
  - Starting/Control air
  - Service air (non-essential)
  - Brine
  - CO2 system
  - Steam

1) Not inside machinery spaces of category A or accommodation spaces. May be accepted in other machinery spaces provided the joints are located in easily visible and accessible positions.
2) Only in pump rooms and open decks
3) Only above bulkhead deck of passenger ships and freeboard deck of cargo ships.

Threaded joints having pipe threads where pressure-tight joints are made on the threads with parallel or tapered threads shall not be used for: (piping systems conveying toxic or flammable media) or (services where fatigue, severe erosion or crevice corrosion is expected to occur) or (when the outside diameter is greater than 60.3 mm).

The temperature rating for elastomer sealing ring:

Type of Elastomer	Temperature range
EPDM	-20 to +110 ºC
NBR/H-NBR	-10 to +70 ºC
FPM – Viton	+30 to +200 ºC
Silicone	-55 to +180 ºC

For couplings at elevated temperatures, the maximum working pressure has to be reduced with the following factors:

Temp.	-55 °C	-20 °C	20 °C	50 °C	100 °C	150 °C	200 °C
Carbon Steel	-	1	1	1	1	0,89	0,81
Stainless Steel	1	1	1	0.95	0.85	0.77	0.71

Couplings made of carbon steel (thickness greater than 6 mm) are not to be used at temperatures below 0°C unless supplied with material Charpy V-notch impact tested at 5 degrees below minimum design temperature or -20°C, whichever is smaller - Minimum average energy 27 J.

The approval is only valid when the couplings are assembled with tubing of correct temper and tolerances as recommended by the coupling manufacturer.

Type Approval documentation

Tests carried out
Leakage test, vibration & pressure pulsation, burst pressure, pull-out, vacuum and fire test.

Marking of product
For traceability to this type approval the products are to be marked with:
- Manufacturer's name or trade mark
- Type designation and dimension

Periodical assessment
For retention of the Type Approval, a DNV GL Surveyor shall perform periodical assessment after two years (+/- 90 days) and after 3.5 years (+/- 90 days) to verify that the conditions for the approval are complied with. Reference is made to DNVGL-CP-0338.