

TYPE APPROVAL CERTIFICATE

This is to certify:**That the Bulk Loading Hoses with Permanently Fitted Couplings**with type designation(s)
MUDFLAT® ST Tess Part no. 10350

Issued to

Tess AS
Lierstranda, Norwayis found to comply with
DNV GL class programme DNVGL-CP-0183 – Type approval – Flexible hoses**Application :****Product(s) approved by this certificate is/are accepted for installation on vessels classed by DNV GL.****Temperature range: -20°C to +70°C****Max. working press.: 18 bar****Sizes: 4 inches**Issued at **Høvik** on **2018-12-19**This Certificate is valid until **2022-12-31**.DNV GL local station: **Oslo Maritime and CAP**for **DNV GL**Approval Engineer: **Adel Samiei**

Marianne Spæren Marveng
Head of Section

This Certificate is subject to terms and conditions overleaf. Any significant change in design or construction may render this Certificate invalid. The validity date relates to the Type Approval Certificate and not to the approval of equipment/systems installed.



Job Id: **262.1-009105-8**
Certificate No: **TAP00001BY**

Product description

Design: Rubber hose reinforced with plies of textile yarn and built in double copper wire for grounding of static electricity.

Manufacturer of the hose: IVG Colbanchini SpA, Padova, Italy.
Hose type : PL Brine/Mudflat ST (same spec as OSM 360).
Materials: Inner tube: Nitrile / PVC.
Cover: Neoprene rubber according to ASTM C-542

Coupling manufacturer: Shand UK or IVG SpA
Material of Couplings: Carbon steel with zinc protection or AISI 316/316L

The coupling Designations and Material:

Insert: 330021, 330041, 33004, 330021, 32968, 33111, 33002 in Carbon Steel (A106)
33062, 33061, 33070, 33604, 33064, 32967 in Stainless Steel (AISI316L) -
Ferrule: 30134 in Carbon Steel (A106). 301462 in Stainless Steel (AISI316L)

Application/Limitation

This certificate is valid for the specific assembly of hose and coupling type as specified, assembled and delivered by the holder (named as "Issued to") of this certificate and below approved locations:

- TESS Vest (Norway): Stavanger, Kokstad, Sotra, Mongstad
- TESS Logistikk AS, Lierstranda, Norway
- TESS, Esbjerg, Denmark
- TESS, Aberdeen, Scotland

Each hose assembly is to be hydraulic pressure tested to 1.5 times the maximum working pressure before delivery and shall be delivered with a pressure test report with reference to this certificate. No product certificate will be required.

Hose assemblies covered by this certificate are approved for installation on DNV GL classed ships and mobile offshore units as a "Bulk loading hose" ("Rig supply hose") and may be used for transfer of the following media: Mud, Brine, Slop Water

Hoses covered by this certificate are not to be used in:

- DNV GL classed drilling units (applications covered by DNVGL-OS-E101)
- Wherever they might be subject to axial load during operation
- Wherever they might be subject to twisting during operation

Type Approval documentation

Tests carried out

Dimensional check, Burst pressure, Oil resistance, Temporary and Permanent elongation, Proof pressure test, Bending test, Electrical tests, Tension test, Break load test. (Note: The PL Brine/Mudflat ST is identical to OSM 360.)

Marking of product

For traceability to this type approval the products are to be marked with:
Manufacturer's name or trade mark, Type designation, size, Maximum working pressure

Periodical assessment

For retention of the Type Approval, a DNV GL Surveyor shall perform periodical assessment after two years (+/- 90 days) and after 3.5 years (+/- 90 days) to verify that the conditions for the approval are complied with. Reference is made to DNVGL-CP-0338.