

TYPE APPROVAL CERTIFICATE

This is to certify:**That the Plate Heat Exchanger**with type designation(s)
PHE TL6-FG

Issued to

Alfa Laval Lund AB
Lund, Skåne Län, Sweden

is found to comply with

DNV GL rules for classification – Ships Pt.4 Ch.7 Pressure equipment
DNVGL-OS-D101 – Marine and machinery systems and equipment, Edition January 2018**Application :****Product(s) approved by this certificate is/are accepted for installation on vessels classed by DNV GL.****Temperature range:** -10 to +200 °C**Design pressure:** 15.5 bar to 20 bar (Depending on maximum design temperature)**Operating media:** See certificate.Issued at **Høvik** on **2019-01-17**This Certificate is valid until **2022-12-31**.DNV GL local station: **Stockholm**for **DNV GL**Approval Engineer: **Mehdi Rowshan**

Marianne Spæren Marveng
Head of Section

This Certificate is subject to terms and conditions overleaf. Any significant change in design or construction may render this Certificate invalid. The validity date relates to the Type Approval Certificate and not to the approval of equipment/systems installed.



Product description

Plate heat exchanger type TL6-FG with tie bolted frame plates designed according to DNV GL ship rules Pt.4 Ch.7 (Parts not covered by Pt.4 Ch.7 are designed in accordance with EN13445)

Material:

Frame and Pressure plates :	P265GH (EN10028-2)
Tightening bolts:	42CrMo4 (EN10269) / Class 8.8 (EN ISO 898-1)
Nuts:	42CrMo4 (EN10269) / Class 8 (EN ISO 898-2)
Channel plates:	Stainless steel / Titanium.

Application/Limitation

Gasketed plate heat exchanger (PHE) with tie bolted frame plates of series type PHE TL6-FG approved for the medium according to limitations referred in DNV GL ship rules Pt.4 Ch.7 Sec.1 Table 2 to specify the class for the heat exchanger.

Heat exchanger plates and gaskets shall withstand and meet the requirements of the operating media and temperature.

Design Pressure for different maximum design Temperatures are shown as below:

Maximum design Temperature	Design Pressure
50°C	20,0 bar
100°C	18,0 bar
150°C	16,5 bar
180°C	16,0 bar
200°C	15,5 bar

Stainless steel channel plates grades SUS304, 316 and 316L shall not be used in seawater systems.

Corrosion allowance: 0 mm

Thickness of frame and pressure plates: Min. 29.7 mm

Type Approval documentation

Production Testing

Each heat exchanger shall be subjected to hydrostatic pressure test upon completion to at least 1.5 times the design pressure in the presence of a DNV GL Surveyor.

The hydrostatic pressure includes a differential pressure test between the chambers; each chamber is to be pressure tested.

Certification

Materials used shall have certificates according to DNV GL Rules Pt.4 Ch.7 Sec.1 [3.2.2].

Each heat exchanger shall be certified by a DNV GL surveyor and to be delivered with a DNV GL product certificate

Manufacturer of pressure vessels of class I and II shall be approved manufacturer by DNV GL.

DNV GL Approval of manufacturer is required for VL and W material certificates.

Marking of product

Job Id: **262.1-008572-4**
Certificate No: **TAP00001JR**

For traceability to this Type Approval the products should at least be marked with:

- Manufacturer's name and address
- Type designation and serial number
- Year of manufacture
- Maximum allowable working pressure
- Hydrostatic test pressure
- Temperature range.

Periodical assessment

For retention of the Type Approval, a DNV GL Surveyor shall perform periodical assessment after two years (+/- 90 days) and after 3.5 years (+/- 90 days) to verify that the conditions for the approval are complied with. Reference is made to DNVGL-CP-0338.