DNV·GL

Certificate No:
TAP000025W

TYPE APPROVAL CERTIFICATE

This is to certify:

That the Metallic Expansion Joints

with type designation(s)
FIMM

Issued to
SOPRODI S.A.S.
SARREBOURG, France

is found to comply with
DNV GL rules for classification – Ships Pt.4 Ch.6 Piping systems
DNVGL-OS-D101 – Marine and machinery systems and equipment, Edition January 2018

Application :

Product(s) approved by this certificate is/are accepted for installation on vessels classed by DNV GL.

Temperature range:	**+20°C to +110°C**
Max. working press.:	**25 bar**
Sizes:	**DN150**

Issued at **Høvik** on **2020-08-13**

This Certificate is valid until **2025-08-12**.

for **DNV GL**

DNV GL local station: **France CMC**

Approval Engineer: **Adel Samiei**

Zeinab Sharifi
Head of Section

This Certificate is subject to terms and conditions overleaf. Any significant change in design or construction may render this Certificate invalid. The validity date relates to the Type Approval Certificate and not to the approval of equipment/systems installed.

LEGAL DISCLAIMER: Unless otherwise stated in the applicable contract with the holder of this document, or following from mandatory law, the liability of DNV GL AS, its parent companies and subsidiaries as well as their officers, directors and employees ("DNV GL") arising from or in connection with the services rendered for the purpose of the issuance of this document or reliance thereon, whether in contract or in tort (including negligence), shall be limited to direct losses and under any circumstance be limited to 300,000 USD.

© DNV GL 2014. DNV GL and the Horizon Graphic are trademarks of DNV GL AS.

Product description
Single expansion bellows made of ASME 240 (316L) of 9 convolutions (3 plies x thk. 0.5 mm) designed according to EJMA 10th edition; with Collar made of A240 (316L) and Pipe made of A312 (316L).
The product is protected with braids made of Stainless-steel grade 304.

Application/Limitation
Expansion bellows covered by this certificate are found to be in compliance with the given design standard and may be used for system conveying Neon/Helium/Nitrogen.

Approved movement: 7 mm lateral (No angular and axial movements)
Approved life cycles: 1000 cycles
Limitation on velocity: 12.80 m/s

The installation shall be done according to type approval holder's procedures.

Production testing
Each expansion bellow shall be subjected to hydrostatic pressure test upon completion to at least 1.5 times the design pressure.

Certification
Whenever the piping system is subject to approval by the society, the below limitations shall be considered:
- Bellows covered by this certificate shall be delivered with test report with reference to this type approval certificate (see to DNVGL-RU-SHIP Pt.4 Ch.6 Sec.1 Table 4).
- Welding shall fulfill requirements in DNVGL-RU-SHIP Pt.2 Ch.4.
- Material of bellow shall have material certificates in accordance with DNVGL-RU-SHIP Pt.4 Ch.6 Sec.2 Table 3. Approval of manufacturer is required for VL or W material certificates.

Type Approval documentation

Marking of product
For traceability to this type approval, the compensators are to be marked with:
- Manufacturer's trademark
- Type designation (as stated in the submitted drawings)
- Size
- Maximum working pressure
- Temperature range
- The flow direction, if applicable

Periodical assessment
For retention of the Type Approval, a DNV GL Surveyor shall perform periodical assessment after two years (+/- 90 days) and after 3.5 years (+/- 90 days) to verify that the conditions for the approval are complied with. Reference is made to DNVGL-CP-0338.