Certificate no.:
TAP00002VZ

TYPE APPROVAL CERTIFICATE

This is to certify:

that the Evaporator

with type designation(s)
PVU3000, PVU5000, PVU8000

issued to

DongHwa Entec. Co., Ltd.

7, Noksansandan 261-ro, Gangseogu, Busan, Republic of Korea

is found to comply with

Application:

Product(s) approved by this certificate is/are accepted for installation on all vessels classed by DNV.

Issued at **Hamburg** on **2024-06-13**
This Certificate is valid until **2029-06-12**.
DNV local unit: **Gimhae Station**

Approval Engineer: **Le Loi Nguyen**

for **DNV**

This Certificate is subject to terms and conditions overleaf. Any significant change in design or construction may render this Certificate invalid.
The validity date relates to the Type Approval Certificate and not to the approval of equipment/systems installed.

LEGAL DISCLAIMER: Unless otherwise stated in the applicable contract with the holder of this document, or following from mandatory law, the liability of DNV AS, its parent companies and their subsidiaries as well as their officers, directors and employees ("DNV") arising from or in connection with the services rendered for the purpose of the issuance of this document or reliance thereon, whether in contract or in tort (including negligence), shall be limited to direct losses and under any circumstance be limited to 300,000 USD.

Product description

PVU3000, PVU5000, PVU8000	Cold side	Hot side
Design pressure (bar)	350	10
Test pressure (bar)	525	15
Medium [-]	LNG	Glycol, Water
Pressure equipment class	I	III

Application/Limitation

- The vaporizers are approved according to DNV-RU-SHIP Pt.4 Ch.7 and DNV-RU-SHIP Pt.5 Ch.7 and the materials shall be delivered with material certificates according to DNV-RU-SHIP Pt.4 Ch.7 Sec.1 Tab.5 or Tab.7,
- Manufacturing, workmanship, and testing shall be done according to DNV-RU-SHIP Pt.4 Ch.7 Sec.7,

Type Approval documentation

Tests carried out

The vaporizer is to be:

- Hydraulic pressure tested to minimum 1.5 x design pressure,
- Certified by DNV and delivered with a DNV product certificate.

Place of manufacture

20, Hwajeonsandan 1-ro 63 beon-gil, Gangseo-gu, Busa, Republic of Korea (Hwajeon factory)

Marking of product

For traceability to this type approval the products are at least to be marked with:

- the name and domicile of the manufacturer,
- the manufacturer's type designation and serial number,
- the year of manufacture,
- the design pressure,
- the design temperature in °C,
- the hydraulic test pressure, and
- DNV 's identifying mark.

Periodical assessment

The objective of the periodical assessment is to verify that the conditions for the type approval (TA) have not been altered.
The main scope of the periodical assessment will normally include:

- verification of the TA applicant’s production and quality system w.r.t. ensuring continued consistent production of the TA products at the TA applicant’s own premises and at other companies that are given the responsibility for manufacturing of the products,
- review of TA documentation and that this is still used as basis for the production,
- review of possible changes in the design, the materials and the performance of the product, and
- verification of the product marking.

For retention of the TA certificate in its validity period the periodical assessments will be carried out every two years. Unscheduled assessments for retention of the certificate may be carried out when there is reason to believe that the type approval applicant has not adhered to the obligations stipulated in the type approval certificate.

End of Certificate