DNV·GL

Certificate No:
TAS00000GH

TYPE APPROVAL CERTIFICATE

This is to certify:

That the Cargo Securing Devices

with type designation(s)
Semi-Automatic Twistlock

Issued to
Kunshan Lucky Sea Industry Co., Ltd.
Kunshan 100, China

is found to comply with
GL Rules for Classification and Construction I - Ship Technology

Application :

Product(s) approved by this certificate is/are accepted for installation on all vessels classed by DNV GL.

MSL, tension (kN) 250
MSL, shear (kN) 210
MSL, compr. (kN)

This Certificate is valid until **2021-06-05**.

Issued at **Hamburg** on **2016-06-06**

for **DNV GL**

DNV GL local station: **Shanghai CMC**

Approval Engineer: **Mathias Bohn**

on behalf of Andree Orth
Head of Section

This Certificate is subject to terms and conditions overleaf. Any significant change in design or construction may render this Certificate invalid.
The validity date relates to the Type Approval Certificate and not to the approval of equipment/systems installed.

© DNV GL 2014. DNV GL and the Horizon Graphic are trademarks of DNV GL AS.

Job Id: **262.1-022815-1**
Certificate No: **TAS00000GH**

Product description

Semi-Automatic Twistlock F6A

Application/Limitation

Load	Tension [kN]	Shear [kN]
Test Load	313	263
Breaking Load	500	420

Tests to be carried out:

- Production testing: At least 2% of the items delivered are to be selected and subjected to the test load.
- Material tests are to be included energy testing at -20°C, with the impact energy requirements acc. to GL rule I-1-20. The material shall be according to the approved drawings. Material certificates shall be 3.1 acc. to DIN EN 10204.

Type Approval documentation

Drawing No.	Rev.	Title
K-F6A	-	Semi-Automatic Twistlock
K-F6A/06-1A	-	Shift
K-F6A/02B	-	Body
K-F6A/04B	-	Body

Drawing approval No. DNVGL Ref.-No.: 15-063190 Date: 2015-10-13

Tests carried out

The prototype test was carried out in Kunshan, P.R. China, dated 2015-11-24 in accordance with the GL rule I-1-20.

Marking of product

Each item shall be marked by manufacturer for traceability.