DNV·GL

Certificate No:
TAS00000ZE

TYPE APPROVAL CERTIFICATE

This is to certify:

That the Rudder Bearing Bushing Material, Synthetic

with type designation(s)
Starlite "Red" #11630

Issued to
Starlite Co., Ltd. Ritto Plant
Ritto Shiga pref., Japan

is found to comply with
DNV GL class programme DNVGL-CP-0081 – Type approval – Synthetic bearing bushing materials
DNV GL rules for classification – Ships

Application :

Maximum surface pressure 10 MPa for the synthetic bearing against steel, water lubricated. The Type Approval is valid only when the installation/application of the product is according to the DNV GL Rules and the Manufacturer's recommendations.

Product(s) approved by this certificate is/are accepted for installation on all vessels classed by DNV GL.

Issued at **Høvik** on **2017-08-24**
This Certificate is valid until **2022-08-23**.
DNV GL local station: **Kobe**

Approval Engineer: **Gisle Hersvik**

for **DNV GL**

Martin Strande
Head of Section

This Certificate is subject to terms and conditions overleaf. Any significant change in design or construction may render this Certificate invalid.
The validity date relates to the Type Approval Certificate and not to the approval of equipment/systems installed.

© DNV GL 2014. DNV GL and the Horizon Graphic are trademarks of DNV GL AS.

Product description

Starlite "Red" #11630; Phenolic Resin reinforced with Cotton Fabric.

Manufactured by

Starlite Co., Ltd., Ritto Plant, 2222, Kamitoyama, Ritto-City, Shiga 520-3003, Japan

DNV GL local station: Kobe

Starlite Plastic Products (Kunshan) Co., Ltd., No. 29 Yauyi South Road, Luyang Administration Zone, Zhoushi Town, Kunshan City, Jiangsu, China

DNV GL local station: Shanghai

Responsibility

The Company (stated on the front page of this Certificate) takes the responsibility that both design and production are in compliance with Rules, Standards and/or Regulations listed on page 1 of this certificate.

Application/Limitation

Fields of Application;	- Rudder Neck Bearings - Rudder Pintle Bearings - Rudder Carrier Bearings
Lubricants;	- Water
Surface Pressure;	- 10.0 MPa, maximum (lubricated)
Max. service temperature;	- 65°C
Installation;	- Press fit - Freeze fit
Dimensions;	- As per DNV GL Rules and Manufacturer's recommendations. - Min – max diameters (OD): 25 – 1500 mm - Min – max thicknesses (WT): 5 – 100 mm

The Type Approval is valid only when the installation/application of the product is according to the specified DNV GL Rules and the Manufacturer's recommendations. Reference is made to Starlite's "Rudder Bearing Design Criterion".

In accordance with DNV GL Rules for Ships, Pt.3 Ch.14, the bushing shall be effectively secured to the bearing.

Bushing fitted by means of shrink fitting alone is not considered effectively secured. Additional physical stoppers need to be arranged to prevent the bushing from accidentally rotating or shifting in vertical direction.

The maximum surface pressure of 10 MPa will be subject to evaluation w.r.t. service experience etc. in connection with renewal of the certificate.

Any significant changes in design and/or quality of the material will render the approval invalid.

Type Approval documentation

Tests carried out

Type Testing carried out according to **Type Approval documentation**.

Marking of product

Product shall be marked with *manufacturer's name*; **Starlite Co., Ltd.**, *place of manufacture* and *type designation;* **Starlite "Red" #11630**.

The marking is to be carried out in such a way that it is visible, legible and indelible. The marking of product is to enable traceability to the DNV GL Type Approval Certificate.

Periodical assessment

The scope of the Periodical Assessment is to verify that the conditions stipulated for the Type Approval is complied with and that no alterations are made to the product design or choice of materials.

Periodical Assessment to be performed after 2 and 3.5 years (Certificate Retention) and at renewal after 5 years (Certificate Renewal).

The main elements of the Periodical Assessment are to:

- Ensure that **Type Approval documentation** is available.
- Review design, materials, production process, and performance with respect to possible changes, in order to ensure compliance with **Type Approval documentation** and/or referenced material specifications.
- Ensure traceability between manufacturer's product marking and DNV GL Type Approval Certificate.

END OF CERTIFICATE