DNV·GL

Certificate No:
TAS00001CC

TYPE APPROVAL CERTIFICATE

This is to certify:

That the Rudder Bearing Bushing Material, Synthetic

with type designation(s)
LUNA-15GR

Issued to
I-Pass Corp.
Incheon, Korea

is found to comply with
DNV GL class programme DNVGL-CP-0081 – Type approval – Synthetic bearing bushing materials
DNV GL rules for classification – Ships
DNV GL rules for classification – High speed and light craft

Application :

Maximum surface pressure 10 N/mm² for the synthetic bearing against steel, water or oil lubricated. The Type Approval is valid only when the installation/application of the product is in accordance with the specified Rules and the Manufacturer's recommendations.

Product(s) approved by this certificate is/are accepted for installation on all vessels classed by DNV GL.

Issued at **Høvik** on **2018-02-13**
This Certificate is valid until **2023-02-12**.
DNV GL local station: **Seoul**

Approval Engineer: **Gisle Hersvik**

for **DNV GL**

Rikard Törnqvist
Head of Section

This Certificate is subject to terms and conditions overleaf. Any significant change in design or construction may render this Certificate invalid.
The validity date relates to the Type Approval Certificate and not to the approval of equipment/systems installed.

© DNV GL 2014. DNV GL and the Horizon Graphic are trademarks of DNV GL AS.

Job Id: **262.1-007004-3**
Certificate No: **TAS00001CC**

Product description

LUNA-15GR: A non-elastomeric rudder bearing bushing material made from a polyester resin impregnated polyester fabric.

Place of manufacture

I-Pass Corp., 19, Bongo-daero 894 beon-gil, Gyeyang-gu, Incheon, Korea

Application/Limitation

Fields of Application;	- Steering gear - Rudder neck bearings - Rudder pintle bearings - Rudder carriers - Stabilizer bearings
Lubricants;	- Water, grease, oil
Surface Pressure;	- 10.0 MPa, maximum (lubricated)
Max. service temperature;	- 65°C
Installation;	- Press fit - Freeze fit - Adhesive bonded - Mechanical retention
Dimensions;	- As per DNV GL Rules and Manufacturer's recommendations. - Min – max diameters (OD): 30 – 2000 mm - Min – max thicknesses (WT): 5 – 200 mm - Optimum wall thickness = ((0.035 x shaft OD) + 2) mm, Ref. I-Pass Corp.'s "LUNA-15GR Synthetic Bearing Engineering Manual", Edition July 2017, pg. 9 (Design).

The Type Approval is valid only when the installation/application of the product is according to the specified DNV GL Rules and the Manufacturer's recommendations. Reference is made to I-Pass Corp.'s "LUNA-15GR Synthetic Bearing Engineering Manual", Edition July 2017.

Area of application will be evaluated during approval of classified objects if the surface pressure exceeds 5.5 N/mm², and/or for dry-running (non-lubrication) applications.

In accordance with DNV GL Rules for Ships, Pt.3 Ch.14, the bushing shall be effectively secured to the bearing.

Bushing fitted by means of shrink fitting alone is not considered effectively secured. Additional physical stoppers need to be arranged to prevent the bushing from accidentally rotating or shifting in vertical direction.

The maximum surface pressure of 10 MPa will be subject to evaluation w.r.t. service experience etc. in connection with renewal of the certificate.

Any significant changes in design and/or quality of the material will render the approval invalid.

Type Approval documentation

Tests carried out

Type Testing carried out in accordance with **Type Approval documentation**.

Marking of product

Product shall be marked with *manufacturer's name*; **I-Pass Corp., Incheon, Korea** and *LUNA-15GR*.

The marking is to be carried out in such a way that it is visible, legible and indelible. The marking of product is to enable traceability to the DNV GL Type Approval Certificate.

Periodical assessment

The scope of the Periodical Assessment is to verify that the conditions stipulated for the Type Approval is complied with and that no alterations are made to the product design or choice of materials.

Periodical Assessment to be performed after 2 and 3.5 years (Certificate Retention) and at renewal after 5 years (Certificate Renewal).

The main elements of the Periodical Assessment are to:

- Ensure that **Type Approval documentation** is available.
- Review design, materials, production process, and performance with respect to possible changes, in order to ensure compliance with **Type Approval documentation** and/or referenced material specifications.
- Ensure traceability between manufacturer's product marking and DNV GL Type Approval Certificate.

END OF CERTIFICATE