

TYPE APPROVAL CERTIFICATE

This is to certify:**That the Lifting set for Offshore containers and Portable Offshore Units**with type designation(s)
Wire rope lifting sets

Issued to

Bullivants - Handling Safety
Braeside, Victoria, Australia

is found to comply with

DNV GL standard DNVGL-ST-E271 – 2.7-1 Offshore containers, August 2017**DNV GL standard DNVGL-ST-E273 – 2.7-3 Portable offshore units, December 2016****ISO 10855-2:2018 Offshore containers and associated liftings sets – Part 2: Design, manufacture and testing of lifting sets****EN 13414-1 Wire rope slings****IMO/MSC Circular 860****Application :****1, 2, 3 and 4 leg lifting sets, with forerunner where fitted, for lifting of:**

- Offshore Containers, with Maximum Gross Mass 0 to 25000 kg,**
- Portable Offshore Units.**

Issued at **Aberdeen** on **2018-09-06**This Certificate is valid until **2023-09-05**.DNV GL local station: **Perth**for **DNV GL**Approval Engineer: **Elisabeth Legg**.....
Alex Doig
Team Lead

This Certificate is subject to terms and conditions overleaf. Any significant change in design or construction may render this Certificate invalid. The validity date relates to the Type Approval Certificate and not to the approval of equipment/systems installed.



Job Id: **262.1-007077-5**
Certificate No: **TAS00001MW**

Manufactured by

Bullivants Handling Safety WA, Welshpool, Australia
Manufacturer of sling set with wire diameter from 18mm to 90mm.

Bullivants Handling Safety, Karratha, Australia
Manufacturer of sling set with wire diameter from 18mm to 28mm.

DNV GL local office: Perth (for all Bullivants Handling Safety branch offices)

Bullivants takes responsibility that both design and production are in compliance with the Rules, Standards and/or Regulations listed on page 1 of this Type Approval Certificate.

Product description

This Type Approval Certificate replaces DNV GL Type Approval Certificate No. S-8088.

The Type Approval Certificate covers wire rope lifting sets assembled by Bullivants. These shall be assembled with turnback eye, in accordance with DNVGL-ST-E271 or DNVGL-ST-E273.

The wire rope lifting sets assembled by Bullivants consist of components from the following sub suppliers:

Component	Sub supplier (DNV GL to be informed and review all new sub suppliers)	DNV GL TAC No.
Master Link and Quad assembly	Scaw South Africa (Pty) Limited Gunnebo Industrier AB Crosby Group LLC	TAS000013Z TAS00000TE TAS000001V
Wire rope ¹⁾	Usha Martin Limited	n/a
Shackles ²⁾	Van Beest BV Crosby Group LLC	TAS000011V TAS00000HA
Ferrules ³⁾	Sahm Splice	n/a
Thimbles ⁴⁾	Crosby Group LLC	n/a

- 1) Wire ropes used in fore runner and bottom legs of lifting sets shall be 6-stranded and of type 6x19 or 6x36 and may be fibre cored or steel cored, with wire rope grades 1770 N/mm² or 1960 N/mm², in accordance to EN 12385, or equivalent.
- 2) Shackles are only considered part of the lifting set if captive (i.e. can not be removed after assembly of lifting set).
- 3) Ferrules/sleeves shall be in accordance with EN 13411-3, or equivalent.
- 4) Thimbles shall be in accordance with EN 13411-1, or equivalent.

Components shall be delivered with the following certificates:

- Master Links, Quad assemblies and Shackles: Certificates based on DNV GL Type Approval.
- Wire Ropes: To be supplied with traceable material certificates in accordance with EN 10204, inspection certificate, type 3.1.
- Thimbles and ferrules: To be supplied with a material certificate in accordance with EN 10204, test report, type 2.2.

Application/Limitation

For each delivered drum of wire rope, a test leg with one eye in each end to be prepared and tested to breaking. A reference should be made to the wire drum test report in each lifting set certificate where that wire is used.

All production testing should be carried out according to Bullivants internal procedures and to be agreed with the local DNV GL office.

The manufacturer shall issue product certificates in accordance with DNV GL-ST-E271 Section 8.5, using the certificate form No. BP/DNV/TC/0614. This certificate form is only to be used for lifting sets certified according to this Type Approval Certificate.

The WLL to be used in certificates and marked on lifting sets shall be the maximum working load limit (WLL) of the lifting set, as per the definition in DNVGL-ST-E271.

For lifting sets manufactured in accordance with DNVGL-ST-E271

Lifting sets shall be assembled according to the strength requirements described in DNVGL-ST-E271 Section 8. The angle of the sling legs from vertical should be taken into account when choosing slings. This angle should normally be 45°, but smaller angles may be used.

Special lifting sets, assembled according to the principles described in DNVGL-ST-E271 Section 8 and Appendix E, are also covered by this Type Approval. If unsymmetrical slings are to be assembled, the local DNV GL office shall be contacted to review each case, unless otherwise agreed in advance.

Note: The sling leg is not necessarily the weakest part of the lifting set. Master Link assemblies selected for lifting sets with legs at 45° may not be suitable for lifting sets with a smaller angle.

For lifting sets manufactured in accordance with DNVGL-ST-E273

Prior to selection of the lifting set, the minimum required working load limit (WLL) shall be calculated in accordance with the strength requirements in DNVGL-ST-E273 Section 7.3. The Resulting Sling Force (RSF) is provided in the DNV GL Design Verification Report (DVR) for the Portable Offshore Unit. The DVR should be made available for the lifting set manufacturer.



Job Id: **262.1-007077-5**
Certificate No: **TAS00001MW**

Type Approval documentation

Tests carried out

Prototype breaking load test of assembled wire rope sling leg.

Marking of product

For lifting sets manufactured in accordance with DNVGL-ST-E271: refer to Section 8.

For lifting sets manufactured in accordance with DNVGL-ST-E273: refer to Section 7.6.

Periodical assessment

In order to maintain the validity of the type approval certificate, periodical assessments should be carried out every 6 months.

END OF CERTIFICATE