DNV·GL

Certificate No:
TAS00001YT

TYPE APPROVAL CERTIFICATE

This is to certify:

That the Offshore Container

with type designation(s)
8 - 12ft Offshore Containers

Issued to
VG Offshore Containers International (M) Sdn Bhd
Pelabuhan Klang, Selangor, Malaysia

is found to comply with
DNV GL standard DNVGL-ST-E271 – 2.7-1 Offshore containers, August 2017
ISO 10855:2018 Offshore containers and associated liftings sets – Design, manufacture, testing, inspection and marking
IMO/MSC Circular 860

Application :

Product(s) approved by this certificate is/are accepted for installation on all vessels classed by DNV GL.

Max. gross mass (kg)	**12000**
Max. payload (kg)	**12000 - Tare***
Max. sling leg angle	**30°**
Enhancement factor	**1.413**

Issued at **Aberdeen** on **2019-03-07**
This Certificate is valid until **2024-03-06**.
DNV GL local station: **Kuala Lumpur**

Approval Engineer: **Brendan Ward**

for **DNV GL**

Alex Doig
Head of Section

This Certificate is subject to terms and conditions overleaf. Any significant change in design or construction may render this Certificate invalid.
The validity date relates to the Type Approval Certificate and not to the approval of equipment/systems installed.

© DNV GL 2014. DNV GL and the Horizon Graphic are trademarks of DNV GL AS.

Product description

Type	8ft	9ft	9.8ft	10ft	11ft	12ft
Length (mm)	2438	2750	2991	3048	3350	3660
Width (mm)	2438	2438	2438	2438	2438	2438
Height (mm)	from 2438 to 2750					
Tare mass* (kg)	2000	2125	2200	2250	2375	2500

*) Tare mass is to be confirmed by weighing. The sum of the tare mass and the payload shall never exceed the maximum gross mass as it is stated on the front page of this certificate.

Application/Limitation

Design temperature : -20 °C
Minimum shackle bolt diameter : 28.2 mm

The DNV GL surveyor shall witness all important production and testing events and issue a certificate for each container. The certificate is only valid when the container is fitted with a DNVGL-ST-E271 certified lifting set.

Type Approval documentation

Tests carried out

Prototypes VG4963 and VG5535 tested according to the requirements.

Marking of product

Each container to be marked in accordance with DNV GL / ISO requirements, including:
- Data and inspection plates
- DNV GL emblem for offshore containers
- VL mark to be hard stamped on the data plate
- Manufacturer's Serial Number to be welded on frame

Periodical assessment

In order to maintain the validity of the type approval certificate, periodical assessments should be carried out according to DNVGL-CP-0338 at 2 and 3.5 year intervals. Periodical assessments will, when possible, be harmonised with other surveys and audits carried out.

END OF CERTIFICATE