

# TYPE APPROVAL CERTIFICATE

**This is to certify:****That the Lifting set for Offshore containers and Portable Offshore Units**with type designation(s)  
**Wire rope lifting sets**

Issued to

**Anchor Industries (Pty) Ltd**  
**Cape Town, South Africa**

is found to comply with

**DNV GL standard DNVGL-ST-E271 – 2.7-1 Offshore containers, August 2017****DNV GL standard DNVGL-ST-E273 – 2.7-3 Portable offshore units, December 2016****ISO 10855-2:2018 Offshore containers and associated liftings sets – Part 2: Design, manufacture and testing of lifting sets****EN 13414-1 Wire rope slings****IMO/MSC Circular 860****Application :****1-, 2, 3 and 4 leg lifting sets, with forerunner where fitted, for lifting of:**

- offshore containers with maximum gross mass 0 to 25000 kg,**
- portable offshore units**

Issued at **Aberdeen** on **2019-11-04**This Certificate is valid until **2024-11-03**.for **DNV GL**DNV GL local station: **Cape Town**Approval Engineer: **Ronald Quiballo**

---

**Elisabeth Legg**  
**Principal Engineer**

This Certificate is subject to terms and conditions overleaf. Any significant change in design or construction may render this Certificate invalid. The validity date relates to the Type Approval Certificate and not to the approval of equipment/systems installed.



Job Id: **262.1-018499-3**  
Certificate No: **TAS000024U**

## Product description

This Type Approval Certificate replaces S-8682.

The Type Approval Certificate covers wire rope lifting sets from 12 mm to 77 mm assembled with Flemish eye and turnback eye by Anchor Industries (Pty) Ltd., in accordance with DNVGL-ST-E271 or DNVGL-ST-E273.

The wire rope lifting sets assembled by Anchor Industries (Pty) Ltd. consist of components from the following sub suppliers:

| Component                   | Sub supplier<br>(DNV GL to be informed and review new sub suppliers)                              | DNV GL TAC number                                    |
|-----------------------------|---------------------------------------------------------------------------------------------------|------------------------------------------------------|
| Master link & quad assembly | Kjættingfabriken AS<br>Gunnebo Industrier AB<br>Scaw South Africa (Pty) Limited - McKinnon Chain  | TAS0000047<br>TAS00000TE<br>TAS000013Z<br>TAS00001BN |
| Wire rope <sup>1)</sup>     | Kiswire Neptune Sdn Bhd<br>Has Celik ve Halat San. Tic. ASj<br>Jiangsu Langshan Wire Rope Co. Ltd | N/A                                                  |
| Shackles <sup>2)</sup>      | Van Beest B.V.<br><br>Crosby Group LLC                                                            | TAS000011V<br>TAS00001D0<br>TAS00000HA               |
| Ferrules <sup>3)</sup>      | Wirop Ind. Co. Ltd.                                                                               | N/A                                                  |
| Thimbles <sup>4)</sup>      | Qindao Power Rigging<br>GN Rope Fittings<br>Van Beest B.V.                                        | N/A                                                  |

- 1) Wire ropes used in fore runner and bottom legs of lifting sets shall be 6-stranded and of type 6x19 or 6x36 and may be fibre cored or steel cored, with wire rope grades 1770 N/mm<sup>2</sup> or 1960 N/mm<sup>2</sup>, in accordance to EN 12385, or equivalent.
- 2) Shackles are only considered part of the lifting set if captive (i.e. can not be removed after assembly of lifting set).
- 3) Ferrules/sleeves shall be in accordance with EN 13411-3, or equivalent.
- 4) Thimbles shall be in accordance with EN 13411-1, or equivalent.

Components should be delivered with the following certificates:

- Master Links, Quad assemblies and Shackles: Certificates based on DNV GL Type Approval.
- Wire Ropes: To be supplied with traceable material certificates in accordance with EN 10204, inspection certificate, type 3.1.
- Thimbles and ferrules: To be supplied with a material certificate in accordance with EN 10204, test report, type 2.2.

## Application/Limitation

For each delivered drum of wire rope, a test leg with one eye in each end shall be prepared and tested to breaking. A reference should be made to the wire drum test report in each sling set certificate where that wire is used.

All production testing should be done in accordance with Anchor Industries (Pty) Ltd procedures, to be agreed with the local DNV GL office.

Job Id: **262.1-018499-3**  
Certificate No: **TAS000024U**

The manufacturer shall issue product certificates in accordance with DNV GL-ST-E271 Section 8.5, using the certificate Form 205 Rev. 01/2015. This certificate is only to be used for lifting sets certified in accordance with this Type Approval Certificate.

The WLL to be referenced in certificates and marked on lifting sets shall be the maximum working load limit (WLL) of the lifting set, as per the definition in DNVGL-ST-E271.

**For lifting sets manufactured in accordance with DNVGL-ST-E271**

Lifting sets shall be assembled in accordance with the strength requirements described in DNVGL-ST-E271 Section 8. The angle of the sling legs from vertical should be taken into account when choosing slings. This angle should normally be 45°, but smaller angles may be used.

Special lifting sets, assembled in accordance with the principles described in DNVGL-ST-E271 Section 8 and Appendix E, are also covered by this Type Approval. If unsymmetrical slings are to be assembled, the local DNV GL office shall be contacted to review each case, unless otherwise agreed in advance.

*Note: The sling leg is not necessarily the weakest part of the lifting set. Master Link assemblies selected for lifting sets with legs at 45° may not be suitable for lifting sets with a smaller angle.*

**For lifting sets manufactured in accordance with DNVGL-ST-E273**

Prior to selection of the lifting set, the minimum required working load limit (WLL) shall be calculated in accordance with the strength requirements in DNVGL-ST-E273 Section 7.3. The Resulting Sling Force (RSF) is provided in the DNV GL Design Verification Report (DVR) for the Portable offshore unit. The DVR should be made available for the lifting set manufacturer.

## **Type Approval documentation**

### **Tests carried out**

Prototype breaking load test of assembled wire rope sling leg.

### **Marking of product**

For lifting sets manufactured in accordance with DNVGL-ST-E271: refer to Section 8.

For lifting sets manufactured in accordance with DNVGL-ST-E273: refer to Section 7.6.

### **Periodical assessment**

In order to maintain the validity of the type approval certificate, periodical assessments should be carried out every 12 months.

END OF CERTIFICATE