

TYPE APPROVAL CERTIFICATE

This is to certify:**That the Lifting set for Offshore containers and Portable Offshore Units**with type designation(s)
Wire Rope Lifting Sets

Issued to

Romson Oilfield Services Limited
Port Harcourt, River State, Nigeria

is found to comply with

DNV GL standard DNVGL-ST-E271 – 2.7-1 Offshore containers, August 2017**DNV GL standard DNVGL-ST-E273 – 2.7-3 Portable offshore units, December 2016****ISO 10855-2:2018 Offshore containers and associated liftings sets – Part 2: Design, manufacture and testing of lifting sets****EN 13414-1 Wire rope slings****IMO/MSC Circular 860****Application :****1, 2, 3 and 4-leg lifting sets, with forerunner where fitted, for lifting of:**

- Offshore Container, with Maximum Gross Mass 0 to 25,000 kg,**
- Portable Offshore Units**

Issued at **Aberdeen** on **2019-09-25**This Certificate is valid until **2024-09-24**.for **DNV GL**DNV GL local station: **Lagos**Approval Engineer: **Ronald Quiballo**

.....

Elisabeth Legg
Principal Engineer

This Certificate is subject to terms and conditions overleaf. Any significant change in design or construction may render this Certificate invalid. The validity date relates to the Type Approval Certificate and not to the approval of equipment/systems installed.



Job Id: **262.1-019994-2**
Certificate No: **TAS0000255**

Product description

This Type Approval Certificate replaces TAS000001B.

The Type Approval Certificate covers wire rope lifting sets, described in Appendix 1, assembled by Romson Oilfield Services Limited, in accordance with DNVGL-ST-E271 or DNVGL-ST-E273.

The wire rope lifting sets assembled by Romson Oilfield Services Limited consist of components from the following sub suppliers:

Component	Sub supplier (DNV GL to be informed and review new sub suppliers)	DNV GL TAC number
Master link & quad assembly	Crosby Group LLC	TAS000001V ⁵⁾
Wire rope ¹⁾	Bridon International Ltd. Usha Martin Ltd.	N/A
Shackles ²⁾	Crosby Group LLC	TAS00000HA
Ferrules ³⁾	SAHM SPLICE GmbH	N/A
Thimbles ⁴⁾	Crosby Group LLC	N/A

- 1) Wire ropes used in fore runner and bottom legs of lifting sets shall be 6-stranded and of type 6x19 or 6x36 and may be fibre cored or steel cored, with wire rope grades 1770 N/mm² or 1960 N/mm², in accordance to EN 12385, or equivalent.
- 2) Shackles are only considered part of the lifting set if captive (i.e. can not be removed after assembly of lifting set).
- 3) Ferrules/sleeves shall be in accordance with EN 13411-3, or equivalent.
- 4) Thimbles shall be in accordance with EN 13411-1, or equivalent.
- 5) At the time of publication, the referenced type approval is in the process of being renewed.

Components should be delivered with the following certificates:

- Master Links, Quad assemblies and Shackles: Certificates based on DNV GL Type Approval.
- Wire Ropes: To be supplied with traceable material certificates in accordance with EN 10204, inspection certificate, type 3.1.
- Thimbles and ferrules: To be supplied with a material certificate in accordance with EN 10204, test report, type 2.2.

Application/Limitation

For each delivered drum of wire rope, a test leg with one eye in each end shall be prepared and tested to breaking. A reference should be made to the wire drum test report in each sling set certificate where that wire is used.

All production testing should be done in accordance with Romson Oilfield Services Limited procedures, to be agreed with the local DNV GL office.

The manufacturer shall issue product certificates in accordance with DNV GL-ST-E271 Section 8.5, using the Romson Oilfield Services Limited Certificate No. ROMSONQAFM013. This certificate is only to be used for lifting sets certified in accordance with this Type Approval Certificate.

The WLL to be referenced in certificates and marked on lifting sets shall be the maximum working load limit (WLL) of the lifting set, as per the definition in DNVGL-ST-E271.

Job Id: **262.1-019994-2**
Certificate No: **TAS0000255**

For lifting sets manufactured in accordance with DNVGL-ST-E271

Lifting sets shall be assembled in accordance with the strength requirements described in DNVGL-ST-E271 Section 8. The angle of the sling legs from vertical should be taken into account when choosing slings. This angle should normally be 45°, but smaller angles may be used.

Special lifting sets, assembled in accordance with the principles described in DNVGL-ST-E271 Section 8 and Appendix E, are also covered by this Type Approval. If unsymmetrical slings are to be assembled, the local DNV GL office shall be contacted to review each case, unless otherwise agreed in advance.

Note: The sling leg is not necessarily the weakest part of the lifting set. Master Link assemblies selected for lifting sets with legs at 45° may not be suitable for lifting sets with a smaller angle.

For lifting sets manufactured in accordance with DNVGL-ST-E273

Prior to selection of the lifting set, the minimum required working load limit (WLL) shall be calculated in accordance with the strength requirements in DNVGL-ST-E273 Section 7.3. The Resulting Sling Force (RSF) is provided in the DNV GL Design Verification Report (DVR) for the Portable offshore unit. The DVR should be made available for the lifting set manufacturer.

Type Approval documentation

Tests carried out

Prototype breaking load test of assembled wire rope sling leg.

Marking of product

For lifting sets manufactured in accordance with DNVGL-ST-E271: refer to Section 8.

For lifting sets manufactured in accordance with DNVGL-ST-E273: refer to Section 7.6.

Periodical assessment

In order to maintain the validity of the type approval certificate, periodical assessments should be carried out every 12 months.

END OF CERTIFICATE

Job Id: **262.1-019994-2**
Certificate No: **TAS0000255**

Appendix 1

Wire rope slings with aluminium ferrules assembled by Romson Oil Field Services, covered by this Type Approval Certificate:

Product Name	Applicable Standards	Material Grades	Parameter range			
			SIZE(Ø) [mm]	WLL [t]	PL [t]	BL [t]
Steel wire rope	EN12385-4	1960 N/mm ²	48 max (Forerunner) 32 max (Sling Legs)	~25 for assembly	~131.4 ~29.0	164 72.9
Link assemblies	EN1677-4	Grade 8	25/20~40/33	~28.1	~71	~112
Shackles	EN13889	Grade 6	~35	~13.5	~27	~67.5