

TYPE APPROVAL CERTIFICATE

This is to certify:**That the Cargo Securing Devices**with type designation(s)
Semi-Automatic Twistlock TL-6GL

Issued to

Suzhou Joysea Engineering & Trading Co., Ltd.
Taicang, 100, Chinais found to comply with
DNV GL rules for classification – Ships**Application :****Product(s) approved by this certificate is/are accepted for installation on all vessels classed by DNV GL.****SWL, tension (kN) 250****SWL, shear (kN) 210****SWL, compr. (kN) 1000**Issued at **Hamburg** on **2019-11-12**This Certificate is valid until **2024-11-11**.DNV GL local station: **Shanghai**for **DNV GL**Approval Engineer: **Mark-Oliver Wobig**

Andree Orth
Head of Section

This Certificate is subject to terms and conditions overleaf. Any significant change in design or construction may render this Certificate invalid. The validity date relates to the Type Approval Certificate and not to the approval of equipment/systems installed.



Product description

Twistlock

Application/Limitation

Load	Tension [kN]	Shear [kN]	Compression [kN]
Test Load	312.5	262.5	1250
Breaking Load	500	420	

Tests to be carried out:

- Production testing: At least 2% of the items delivered are to be selected and subjected to the test load.
- Material tests are to be included energy testing at -20°C, with the impact energy requirements acc. to DNVGL-CP-0068. The material shall be according to the approved drawings. Material certificates shall be 3.1 acc. to ISO 10474.

Type Approval documentation

Drawing No.	Rev.	Title
TL-6GL		Semi-Automatic Twistlock
TL-6GL/03		Shaft
TL-6GL/01		House (Right)
TL-6GL/02		House (Left)

Test Report No.: ZS20190803

Tests carried out

The prototype test was carried out in Shanghai, P.R. China, dated 2019-08-30 in accordance with the DNVGL-CP-0068.

Marking of product

Each item shall be marked by manufacturer for traceability.

Periodical Assessment

For retention of the Type Approval, a DNVGL surveyor shall perform a survey after 2 and 3.5 years, to verify that the Type Approval is complied with.