DNV·GL

Certificate No:
TAS00002BH

TYPE APPROVAL CERTIFICATE

This is to certify:

That the Cargo Securing Devices

with type designation(s)
Container-Quick-Tie QT-ST-L

Issued to
GERMAN LASHING Robert Böck GmbH
Bremen, Germany

is found to comply with
DNV GL rules for classification – Ships

Application :

Product(s) approved by this certificate is/are accepted for installation on all vessels classed by DNV GL.
SWL, tension (kN) 250
SWL, shear (kN) 210

Issued at **Hamburg** on **2019-12-06**
This Certificate is valid until **2024-12-05**.
DNV GL local station: **Essen**

Approval Engineer: **Mark-Oliver Wobig**

for **DNV GL**

Andree Orth
Head of Section

This Certificate is subject to terms and conditions overleaf. Any significant change in design or construction may render this Certificate invalid.
The validity date relates to the Type Approval Certificate and not to the approval of equipment/systems installed.

© DNV GL 2014. DNV GL and the Horizon Graphic are trademarks of DNV GL AS.

Product description

Container-Quick-Tie

Application/Limitation

Load	Tension [kN]	Shear [kN]
Test Load	313	263
Breaking Load	500	420

Tests to be carried out:

- Production testing: At least 2% of the items delivered are to be selected and subjected to the test load.
- Material tests are to be included energy testing at -20°C, with the impact energy requirements acc. to DNVGL-CP-0068. The material shall be according to the approved drawings. Material certificates shall be 3.1 acc. to ISO 10474:2013.

Type Approval documentation

Drawing No.	Rev.	Title
QT-ST-L	a	QT-ST-L Container Quick-Tie, Standard Lower Type
QT-ST_Thread Bar		Container-Quick-Tie QT-ST, Thread Bar
QT-ST_Hammer		Container-Quick-Tie QT-ST, Hammer
QT-ST-L_Disc		Container-Quick-Tie QT-ST-L, Disc
QT-ST-L_Disc-Magnet		Container-Quick-Tie QT-ST-L, Disc Magnet
QT-ST_Span Disc		Container-Quick-Tie QT-ST, Span Disc
QT-ST_Bridge		Container-Quick-Tie QT-ST, Bridge
QT-ST_Distance Bolt		Container-Quick-Tie QT-ST, Distance Bolt
QT-ST_Spring Latch	a	QT-ST, Spring Latch

Tests carried out

The prototype test was carried out in Nanjing, P.R. China, dated 2019-12-03 in accordance with the DNVGL-CP-0068.

Marking of product

Each item shall be marked by manufacturer for traceability.

Periodical Assessment

For retention of the Type Approval, a DNVGL surveyor shall perform a survey after 2 and 3.5 years, to verify that the Type Approval is complied with.