

TYPE APPROVAL CERTIFICATE

This is to certify:**That the Offshore Container**with type designation(s)
1.2m Offshore Frame

Issued to

Uniteam Poland Sp. z o.o.
Gdansk, Poland

is found to comply with

DNV GL standard DNVGL-ST-E271 – 2.7-1 Offshore containers, August 2017
ISO 10855:2018 Offshore containers and associated liftings sets – Design, manufacture, testing, inspection and marking
IMO/MSC Circular 860**Application :****Max. gross mass (kg)** 999
Max. payload (kg) 799
Max. sling leg angle 45
Enhancement factor N/AIssued at **Aberdeen** on **2020-09-11**This Certificate is valid until **2025-09-10** .DNV GL local unit: **Gdansk**for **DNV GL**Approval Engineer: **Jack Moffatt**

Elisabeth Legg
Principal Engineer

This Certificate is subject to terms and conditions overleaf. Any significant change in design or construction may render this Certificate invalid. The validity date relates to the Type Approval Certificate and not to the approval of equipment/systems installed.

LEGAL DISCLAIMER: Unless otherwise stated in the applicable contract with the holder of this document, or following from mandatory law, the liability of DNV GL AS, its parent companies and subsidiaries as well as their officers, directors and employees ("DNV GL") arising from or in connection with the services rendered for the purpose of the issuance of this document or reliance thereon, whether in contract or in tort (including negligence), shall be limited to direct losses and under any circumstance be limited to 300,000 USD.



Job Id: **262.1-032850-1**
Certificate No: **TAS00002EU**

Manufactured by

DNV GL CIM No.: 134179

DNV GL CIM No.: 146509*

DNV GL CIM No.: 10128938*

Local DNV GL Office: Gdansk

*) The type approval will not become valid for this place of manufacture before they have built and tested a prototype.

Responsibility

Uniteam Poland Sp. z o. o. takes responsibility that both design and production are in compliance with the Rules, Standards and/or Regulations listed on page 1 of this Type Approval Certificate.

Product description

Maximum external dimensions (LxWxH) : 1200 x 900 x 1300 mm
Tare mass** : 200 kg

**) Tare mass is to be confirmed by weighing. The sum of payload and tare shall never exceed the maximum gross mass stated on the front page of this certificate.

Application/Limitation

Design temperature : -40 °C
Minimum shackle pin diameter : 21.2 mm

The DNV GL surveyor shall witness all important production and testing events and issue a certificate for each container. The certificate is only valid when the container is fitted with a DNVGL-ST-E271 certified lifting set.

Type Approval documentation

Tests carried out

Prototype no. UOGP 0171 tested in accordance with DNVGL-ST-E271.



Job Id: **262.1-032850-1**
Certificate No: **TAS00002EU**

Marking of product

Each container to be marked in accordance with DNV GL / ISO requirements, including:

- Data and inspection plates
- DNV GL emblem for offshore containers
- VL mark to be hard stamped on the data plate
- Manufacturer's Serial Number to be welded on frame

Periodical assessment

In order to maintain the validity of the type approval certificate, periodical assessments should be carried out according to DNVGL-SE-0284 at 2 and 3.5 year intervals. Periodical assessments will, when possible, be harmonised with other surveys and audits carried out.

END OF CERTIFICATE