

TYPE APPROVAL CERTIFICATE

This is to certify:**That the Weathertight hatch**with type designation(s)
Weathertight WRH-S Service hatch

Issued to

Libra-Plast A/S
HAREID, Norwayis found to comply with
DNV GL rules for classification – Ships
DNVGL-OS-C301 – Stability and watertight integrity
DNV GL rules for classification – High speed and light craft**Application :****Product(s) approved by this certificate is/are accepted for installation on all vessels classed by DNV GL.****Size** 1000 mm x 2000 mm
Pressure (kN/m²) 20 to 150Issued at **Høvik** on **2020-04-02**This Certificate is valid until **2025-04-01**.for **DNV GL**DNV GL local station: **Norway Newbuilding**Approval Engineer: **Grzegorz Wolski**

Håvard Helling
Head of Section

This Certificate is subject to terms and conditions overleaf. Any significant change in design or construction may render this Certificate invalid. The validity date relates to the Type Approval Certificate and not to the approval of equipment/systems installed.

LEGAL DISCLAIMER: Unless otherwise stated in the applicable contract with the holder of this document, or following from mandatory law, the liability of DNV GL AS, its parent companies and subsidiaries as well as their officers, directors and employees ("DNV GL") arising from or in connection with the services rendered for the purpose of the issuance of this document or reliance thereon, whether in contract or in tort (including negligence), shall be limited to direct losses and under any circumstance be limited to 300,000 USD.



Product description

Weathertight WRH-S Service hatch

Is a hatch fabricated from 6 mm thick steel main plate. Plate is reinforced by up to five stiffeners welded to the main plate by intermittent welding in middle and by double continuous welding at its ends. Edge of hatch is stiffened by gasket rim welded at 90 degree angle to the main plate.

Hatch is of single acting type with up to ten linked toggles and handle mounted centrally or close to non hinged edge of hatch.

For further details see the drawings listed under Type Approval documentation below.

Application/Limitation

The application is limited to vessels built to DNV GL rules and for a design pressure as per table below.

Light opening (width)	Light opening (length)	Stiffener spacing [mm]	Gasket rim (height) [mm]	Gasket rim (breadth) [mm]	Stiffener	Pressure [kPa]
400	600	N/A	50 80	8 8	N/A	150
600	600	N/A	50 80	8 8	N/A	105
700	700	N/A	50 80	8 8	N/A	75
800	600	340	50 80	8 8	FB 50x8	105
800	800	243	50 80	8 8	FB 50x8	85
1000	1000	230	50 80	8 8	FB 50x8	20 55
1000	1000	230	80	8	FB 80x8 FB 50x10	135 70
1000	1500	314	50 80	8 8	FB 50x8	20 40
1000	1500	314	80	8	FB 50x10 FB 80x10 L 50x50x6	50 125 105
1000	2000	285	50 80	8 8	FB 50x10	20 55
1000	2000	285	80	8	FB 80x10 L 50x50x6	75 110

Weathertight appliances are subject for hose and function testing after installation onboard the vessel, witnessed by a DNV GL surveyor, except in cases where plan approval of the hatch arrangement determines that tests are not required.

Hatches are calculated with respect to water pressure only, any other loading pattern (wheel loads etc.) is to be assessed on a case by case basis.

Hatches cannot be used as emergency exit type.

Dimensions of the light opening of the hatch can be smaller than shown on the drawings, provided that scantlings, maximum distance between the cleats and fabrication method and material are maintained.

Particular consideration shall be given if located in highly stressed areas or in areas critical to fatigue from global hull loads.



Job Id: **262.1-033236-1**
Certificate No: **TAS00002GK**

Type Approval documentation

Test report No. 740 dated 19 March 2020 from manufacturer.

Drawing No. A-3-01519 Rev. 0 dated 17 February 2020 from manufacturer.

Drawing No. A-3-01516 Rev. 1 dated 05 February 2020 from manufacturer.

Tests carried out

According to DNV GL rules for classification: Class Programme DNVGL-CP-0338, September 2018.

Marking of product

The product or packing is to be marked with name and address of manufacturer, type designation, approved pressure and certificate number.

Periodical assessment

DNV GL surveyor is to be given permission to perform a Certification Retention Survey at any time during the validity period of this certificate and at least every second year.