

TYPE APPROVAL CERTIFICATE

This is to certify:**That the Lifting set for Offshore containers and Portable Offshore Units**with type designation(s)
Wire rope lifting sets

Issued to

TECNOLOGIA EM CABOS DE ACO BRASCABO LTDA
Macaé, RJ, Brazil

is found to comply with

DNV GL standard DNVGL-ST-E271 – 2.7-1 Offshore containers, August 2017
DNV GL standard DNVGL-ST-E273 – 2.7-3 Portable offshore units, December 2016
ISO 10855-2:2018 Offshore containers and associated liftings sets – Part 2: Design, manufacture and testing of lifting sets
IMO/MSC Circular 860
EN 13414-1 Wire rope slings**Application :****1, 2, 3, and 4 leg lifting sets, with forerunner where fitted, for lifting of:**
- offshore containers, with maximum gross mass 0 to 25000 kg,
- portable offshore unitsIssued at **Aberdeen** on **2020-11-18**This Certificate is valid until **2025-11-17** .for **DNV GL**DNV GL local unit: **Macaé**Approval Engineer: **Elisabeth Legg****Alex Doig**
Team Lead

This Certificate is subject to terms and conditions overleaf. Any significant change in design or construction may render this Certificate invalid. The validity date relates to the Type Approval Certificate and not to the approval of equipment/systems installed.

LEGAL DISCLAIMER: Unless otherwise stated in the applicable contract with the holder of this document, or following from mandatory law, the liability of DNV GL AS, its parent companies and subsidiaries as well as their officers, directors and employees ("DNV GL") arising from or in connection with the services rendered for the purpose of the issuance of this document or reliance thereon, whether in contract or in tort (including negligence), shall be limited to direct losses and under any circumstance be limited to 300,000 USD.



Product description

This type approval certificate replaces TAS0000015.

This type approval certificate covers wire rope slings from 19 mm to 38 mm diameter assembled with flemish eye by Tecnologia em Cabos de Aço BRASCABO Ltda, in accordance with DNVGL-ST-E271 or DNVGL-ST-E273.

The wire rope lifting sets assembled by Tecnologia em Cabos de Aço BRASCABO Ltda consist of components from the following sub suppliers:

Component	Sub supplier (DNV GL to be informed and review new sub suppliers)	DNV GL TAC number
Master link & quad assembly	Crosby Group LLC Gunnebo Industrier AB Scaw South Africa (Pty) Limited - McKinnon Chain	TAS00002GF TAS00000TE TAS000013Z
Wire rope ¹⁾	Usha Martin Limited Aceros Camesa S.A. Union – Wireco Worldgroup Bekaert Cimaf Cabos Ltda IPH Saifc	N/A
Shackles ²⁾	Crosby Group LLC Van Beest B.V. Fischer Industria Mecanica Yoke Industrial Corp	TAS00002GA TAS000011V TAS000016U TAS0000241
Ferrules ³⁾	Tenax Aço e Ferro Ltda Crosby Group LLC Esperança Indústria e Com. de Forjados Ltda Talurit AB V&M do Brasil (manesmann)	N/A
Thimbles ⁴⁾	Fischer Indústria Mecânica Ltda Coforja Correntes e Acessórios Brasil Ltda Nautinox Artefatos Metalúrgicos Ltda	N/A

- 1) Wire ropes used in forerunner and bottom legs of lifting sets shall be 6-stranded and of type 6x19 or 6x36 and may be fibre cored or steel cored, with wire rope grades 1770 N/mm² or 1960 N/mm², in accordance with API 9A or equivalent.
- 2) Shackles are only considered part of the lifting set if captive (i.e. can not be removed after assembly of lifting set).
- 3) Ferrules/sleeves shall be in accordance with EN 13411-3, or equivalent.
- 4) Thimbles: Federal Specification FF-T-276b, Type III, or equivalent (K2, K2B).

Components should be delivered with the following certificates:

Master Links, Quad assemblies and Shackles:
Wire Ropes:

Certificates based on DNV GL Type Approval.
To be supplied with traceable material certificates in accordance with EN 10204, inspection certificate, type 3.1.

Thimbles and ferrules:

To be supplied with a material certificate in accordance with EN 10204, test report, type 2.2.

Application/Limitation

For each delivered drum of wire rope, a test leg with one eye in each end shall be prepared and tested to breaking. A reference should be made to the wire drum test report in each sling set certificate where that wire is used.

All production testing should be carried out in accordance with Tecnologia em Cabos de Aço BRASCABO Ltda internal procedures, to be agreed with the local DNV GL office.

The manufacturer shall issue product certificates in accordance with DNVGL-ST-E271 Section 8.5, using certificate form RQ 096 Rev01. This certificate form shall only be used for lifting sets certified in accordance with this type approval certificate.

The WLL to be referenced in certificates and marked on lifting sets shall be the maximum working load limit (WLL) of the lifting set, as per the definition in DNVGL-ST-E271.

For lifting sets manufactured in accordance with DNVGL-ST-E271

Lifting sets shall be assembled in accordance with the strength requirements described in DNVGL-ST-E271 section 8. The angle of the sling legs from vertical should be taken into account when choosing slings. This angle should normally be 45°, but smaller angles may be used.

Special lifting sets, assembled in accordance with the principles described in DNVGL-ST-E271 section 8 and appendix E, are also covered by this type approval. If unsymmetrical slings are to be assembled, the local DNV GL office shall be contacted to review each case, unless otherwise agreed in advance.

Note: The sling leg is not necessarily the weakest part of the lifting set. Master Link assemblies selected for lifting sets with legs at 45° may not be suitable for lifting sets with a smaller angle.

For lifting sets manufactured in accordance with DNVGL-ST-E273

Prior to selection of the lifting set, the minimum required working load limit (WLL) shall be calculated in accordance with the strength requirements in DNVGL-ST-E273 section 7.3. The resultant sling force (RSF) is provided in the DNV GL design verification report (DVR) for the portable offshore unit. The DVR should be made available for the lifting set manufacturer.

Type Approval documentation

Tests carried out

Prototype breaking load test of assembled wire rope sling leg.

Marking of product

For lifting sets manufactured in accordance with DNVGL-ST-E271: refer to Section 8.

For lifting sets manufactured in accordance with DNVGL-ST-E273: refer to Section 7.6.

Periodical assessment

In order to maintain the validity of the type approval certificate, periodical assessments should be carried out every 6 months.

END OF CERTIFICATE