DNV·GL

Certificate No:
TAS00002SC

TYPE APPROVAL CERTIFICATE

This is to certify:

That the Cargo Securing Devices

with type designation(s)
Foundation RF-2F-203/110, Foundation RF-2F-216/110, Foundation RF-2F-258/110, Foundation RF-2F-203/H

Issued to
Sclashing Shanghai Co., Ltd
Shanghai, China

is found to comply with
DNV GL rules for classification – Ships

Application :

Product(s) approved by this certificate is/are accepted for installation on all vessels classed by DNV GL.

Type	SWL, tension (kN)	SWL, shear (kN)	SWL, compr. (kN)
Foundation RF-2F-203/110	**250**	**210**	**1000**
Foundation RF-2F-216/110	**250**	**210**	**1000**
Foundation RF-2F-258/110	**250**	**210**	**1000**
Foundation RF-2F-203/H	**250**	**210**	**1000**

Issued at **Hamburg** on **2020-10-07**
This Certificate is valid until **2025-10-06**.
DNV GL local station: **Shanghai**

Approval Engineer: **Mark-Oliver Wobig**

for **DNV GL**

Andree Orth
Head of Section

This Certificate is subject to terms and conditions overleaf. Any significant change in design or construction may render this Certificate invalid. The validity date relates to the Type Approval Certificate and not to the approval of equipment/systems installed.

LEGAL DISCLAIMER: Unless otherwise stated in the applicable contract with the holder of this document, or following from mandatory law, the liability of DNV GL AS, its parent companies and subsidiaries as well as their officers, directors and employees ("DNV GL") arising from or in connection with the services rendered for the purpose of the issuance of this document or reliance thereon, whether in contract or in tort (including negligence), shall be limited to direct losses and under any circumstance be limited to 300,000 USD.

© DNV GL 2014. DNV GL and the Horizon Graphic are trademarks of DNV GL AS.

Product description

Raised Foundation

Application/Limitation

Load	Tension [kN]	Shear [kN]	Compression [kN]
Test Load	313	263	1250
Breaking Load	500	420	2000

Tests to be carried out:

- Production testing: At least 2% of the items delivered are to be selected and subjected to the test load.
- Material tests are to be included energy testing at -20°C, with the impact energy requirements acc. to DNVGL-CP-0068. The material shall be according to the approved drawings. Material certificates shall be 3.1 acc. to ISO 10474:2013.

Type Approval documentation

Drawing No.	Rev.	Title
RF-2F-Lc/H		Foundation

Test report No. ZS202008025
Drawing approval: Ref. No. 262.1-033530-1 dated 2020-10-07

Tests carried out

The prototype test was carried out in Shanghai, P.R. China, dated 2020-08-25 in accordance with the DNVGL-CP-0068.

Marking of product

Each item shall be marked by manufacturer for traceability.

Periodical Assessment

For retention of the Type Approval, a DNVGL surveyor shall perform a survey after 2 and 3.5 years, to verify that the Type Approval is complied with.