

TYPE APPROVAL CERTIFICATE

This is to certify:

That the Offshore Container

with type designation(s)
26ft (T208-A05), 28ft (MSP015), 33ft (T219-A01)

Issued to

Swire Energy Services AS
Sola, Norway

is found to comply with

DNV GL standard DNVGL-ST-E271 – 2.7-1 Offshore containers, January 2021
ISO 10855:2018 Offshore containers and associated liftings sets – Design, manufacture, testing, inspection and marking
IMO/MSC Circular 860

Application :

Type	Max. gross mass (kg)	Max. payload (kg)	Max. sling leg angle	Enhancement factor
26ft (T208-A05)	18000	11700	45	1.201
28ft (MSP015)	18290	10500	45	1.193
33ft (T219-A01)	18000	9200	45	1.201

Issued at **Aberdeen** on **2021-06-14**

This Certificate is valid until **2026-06-13** .

for **DNV**

DNV local unit: **Stavanger**

Approval Engineer: **Elisabeth Legg**

.....
Brendan Ward
Delivery Lead - Containers

This Certificate is subject to terms and conditions overleaf. Any significant change in design or construction may render this Certificate invalid.
The validity date relates to the Type Approval Certificate and not to the approval of equipment/systems installed.

LEGAL DISCLAIMER: Unless otherwise stated in the applicable contract with the holder of this document, or following from mandatory law, the liability of DNV AS, its parent companies and their subsidiaries as well as their officers, directors and employees ("DNV") arising from or in connection with the services rendered for the purpose of the issuance of this document or reliance thereon, whether in contract or in tort (including negligence), shall be limited to direct losses and under any circumstance be limited to 300,000 USD.



Manufactured by

DNV CIM No.: 134179

Local DNV Office: Gdynia

Responsibility

Swire Energy Services AS takes full responsibility that both the design and production are in compliance with the Rules, Standards and / or Regulations listed on page 1 of this type approval certificate.

Product description

This type approval replaces TAS00000HR.

Type	Maximum external dimensions (LxWxH)	Tare mass*
26ft (T208-A05)	8010 x 2990 x 3000 mm	6300 kg
28ft (MSP015)	8510 x 2990 x 3000 mm	7790 kg
33ft (T219-A01)	10010 x 2990 x 3000 mm	8800 kg

* Tare mass is to be confirmed by weighing. The sum of payload and tare shall never exceed the maximum gross mass stated on the front page of this certificate.

Application/Limitation

Type	Design temperature	Minimum shackle bolt diameter
26ft (T208-A05)	-20 °C	33.8 mm
28ft (MSP015)	-20 °C	34.8 mm
33ft (T219-A01)	-20 °C	33.8 mm

The DNV surveyor shall witness all important production and testing events and issue a certificate for each container. The certificate is only valid when the container is fitted with a DNVGL-ST-E271 certified lifting set.

Type Approval documentation

Tests carried out

Prototype No. SW26-001 and SW33-004 tested in accordance with DNVGL-ST-E271.

Marking of product

Each container to be marked in accordance with DNV / ISO requirements, including:

- Data and inspection plates
- DNV emblem for offshore containers
- VL mark to be hard stamped on the data plate
- Manufacturer's Serial Number to be welded on frame

Periodical assessment

In order to maintain the validity of the type approval certificate, periodical assessments should be carried out according to DNVGL-SE-0284 at 2 and 3.5 year intervals. Periodical assessments will, when possible, be harmonised with other surveys and audits carried out.

END OF CERTIFICATE