Certificate No:
TAS000039R

TYPE APPROVAL CERTIFICATE

This is to certify:

That the Cargo Securing Devices

with type designation(s)
Turnbuckle TB-25SL-B-T

Issued to
GERMAN LASHING Robert Böck GmbH
Bremen, **Germany**

is found to comply with
DNV GL rules for classification – Ships

Application :

Product(s) approved by this certificate is/are accepted for installation on all vessels classed by DNV.
SWL, tension (kN) 245

Issued at **Hamburg** on **2021-12-30**
This Certificate is valid until **2026-12-29**.
DNV local station: **Hamburg – CMC North/East**

Approval Engineer: **Aadil Wafdi**

for **DNV**

Andree Orth
Head of Section

This Certificate is subject to terms and conditions overleaf. Any significant change in design or construction may render this Certificate invalid.
The validity date relates to the Type Approval Certificate and not to the approval of equipment/systems installed.

LEGAL DISCLAIMER: Unless otherwise stated in the applicable contract with the holder of this document, or following from mandatory law, the liability of DNV AS, its parent companies and their subsidiaries as well as their officers, directors and employees ("DNV") arising from or in connection with the services rendered for the purpose of the issuance of this document or reliance thereon, whether in contract or in tort (including negligence), shall be limited to direct losses and under any circumstance be limited to 300,000 USD.

Product description

Turnbuckle TB-25SL-B-T

Application/Limitation

Load	Tension [kN]
Test Load	306
Breaking Load	490

Tests to be carried out:

- Production testing: At least 2% of the items delivered are to be selected and subjected to the test load.
- Material tests are to be included energy testing at -20°C, with the impact energy requirements acc. to DNVGL-CP-0068. The material shall be according to the approved drawings. Material certificates shall be 3.1 acc. to ISO 10474:2013.

Type Approval documentation

Drawing No.	Rev.	Title
TB-25SL-B-T_Complete rev b	b	Turnbuckle TB-25SL-B-T
TB-25SL_Body rev f	f	Body
TB-3AR_Knob Pocket rev d	d	Knob Pocket
TB-3AR_Lower Bridge rev f	f	Lower Bridge
TB-3SLR_Locking Plate_S rev d	d	Locking Plate S
TB-SL_Jaw Complete_e	e	Jaw Complete
TB-3_Jaw rev i	i	Jaw with internal thread Tr 32x4
TB-3SL_Clawnut_b	b	Clawnut
TB-3A Securing Bolt	i	Securing Bolt for Jaw

Drawing approval: Ref. No.: 262.1-024032-2, dated 2021.12.02
Test report No.: 1612, dated 2021-12-22

Tests carried out

The prototype test was carried out in Nanjing, P.R. China, dated 2021-12-22 in accordance with the DNVGL-CP-0068.

Marking of product

Each item shall be marked by manufacturer for traceability.

Periodical Assessment

For retention of the Type Approval, a DNVGL surveyor shall perform a survey after 2 and 3.5 years, to verify that the Type Approval is complied with.