



Certificate No:
TAS00003AB

TYPE APPROVAL CERTIFICATE

This is to certify:

That the Offshore Container

with type designation(s)
16 Cylinder Top Entry Frame

Issued to

David Ritchie (Implements) Ltd.
Forfar, Angus, United Kingdom

is found to comply with

DNV standard DNV-ST-E271 – 2.7-1 Offshore containers, January 2021 (Amended October 2021)
ISO 10855:2018 Offshore containers and associated liftings sets – Design, manufacture, testing, inspection and marking
IMO/MSC Circular 860

Application :

Max. gross mass (kg)	2120
Max. payload (kg)	570
Max. sling leg angle	45
Enhancement factor	3.351

Issued at **Aberdeen** on **2022-04-22**

This Certificate is valid until **2027-04-21** .

DNV local unit: **Aberdeen Verification**

for **DNV**

Approval Engineer: **Alex Doig**

Elisabeth Legg
Principal Engineer

This Certificate is subject to terms and conditions overleaf. Any significant change in design or construction may render this Certificate invalid.
The validity date relates to the Type Approval Certificate and not to the approval of equipment/systems installed.

LEGAL DISCLAIMER: Unless otherwise stated in the applicable contract with the holder of this document, or following from mandatory law, the liability of DNV AS, its parent companies and their subsidiaries as well as their officers, directors and employees ("DNV") arising from or in connection with the services rendered for the purpose of the issuance of this document or reliance thereon, whether in contract or in tort (including negligence), shall be limited to direct losses and under any circumstance be limited to 300,000 USD.



Form code: TA 281

Revision: 2021-10

www.dnv.com

Page 1 of 2

Product description

This type approval certificate replaces S-6105.

Type	Maximum external dimensions (LxWxH)	Tare mass*
16 Cylinder Top Entry Frame	1016 x 1016 x 1946 mm	1550 kg

*) Tare mass is to be confirmed by weighing. The sum of payload and tare shall never exceed the maximum gross mass stated on the front page of this certificate.

Application/Limitation

Design temperature : -20 °C
Min. shackle bolt diameter : 22.2 mm

The DNV surveyor shall witness all important production and testing events and issue a certificate for each container. The certificate is only valid when the container is fitted with a DNV-ST-E271 certified lifting set.

This approval does not apply to the gas cylinders to be transported by this frame. If gas cylinders are to be installed and connected to manifolds, the unit as a whole (frame and payload) shall be approved and certified according to IMDG Chapter 6.2 by an authorised certifying body.

Type Approval documentation

Tests carried out

Prototype No. CH-21-0515 tested in accordance with DNV-ST-E271.

Marking of product

Each container to be marked in accordance with DNV / ISO requirements, including:

- Data and inspection plates
- DNV emblem for offshore containers
- NV mark to be hard stamped on the data plate
- Manufacturer's Serial Number to be welded on frame

Periodical assessment

In order to maintain the validity of the type approval certificate, periodical assessments should be carried out according to DNV-SE-0284 at 2 and 3.5 year intervals. Periodical assessments will, when possible, be harmonised with other surveys and audits carried out.

END OF CERTIFICATE