



Certificate No:
TAS00003B0

TYPE APPROVAL CERTIFICATE

This is to certify:

That the portable offshore units

with type designation(s)
Frame for Hybrid Reel Unit (MFF-2030)

Issued to

QHS Scotland Ltd
Elgin, United Kingdom

is found to comply with

DNV GL standard DNVGL-ST-E273 – 2.7-3 Portable offshore units, April 2016 (Amended January 2020)

Application :

Max. gross mass (kg) 30000
Max. payload (kg) 14000
Max. sling leg angle 30

Issued at **Aberdeen** on **2022-01-19**

This Certificate is valid until **2027-01-18** .

DNV local unit: **Aberdeen**

Approval Engineer: **Elisabeth Legg**

for **DNV**

.....
Brendan Ward
Senior Engineer

This Certificate is subject to terms and conditions overleaf. Any significant change in design or construction may render this Certificate invalid.
The validity date relates to the Type Approval Certificate and not to the approval of equipment/systems installed.

LEGAL DISCLAIMER: Unless otherwise stated in the applicable contract with the holder of this document, or following from mandatory law, the liability of DNV AS, its parent companies and their subsidiaries as well as their officers, directors and employees ("DNV") arising from or in connection with the services rendered for the purpose of the issuance of this document or reliance thereon, whether in contract or in tort (including negligence), shall be limited to direct losses and under any circumstance be limited to 300,000 USD.



Form code: TA 281

Revision: 2021-10

www.dnv.com

Page 1 of 2



Job Id: 262.1-037040-1
Certificate No: TAS00003B0

Product description

Maximum external dimensions (LxWxH)	: 4920 x 3490 x 3628 mm
Tare mass*	: 16000 kg
Type	: A
Operational Class	: R45

*) Tare mass is to be confirmed by weighing. The sum of tare and payload shall never exceed the maximum gross mass stated on the front page of this certificate.

Application/Limitation

Shackle size	: 13.5 t
Resultant sling force (RSF)	: 294.9 kN
Minimum design temperature	: -20 °C

DNV surveyor to witness important production and test events and issue Form no. MOP 201 "Certificate for Portable Offshore Unit" for each unit.

Type Approval documentation

Tests carried out

Prototype BB-090 strength tested in accordance with DNV-ST-E273.

Marking of product

Marking is to be carried out in accordance with to DNV-ST-E273 section 6.

Periodical assessment

In order to maintain the validity of the type approval certificate, periodical assessments should be carried out according to DNVGL-SE-0284 at 2 and 3.5 year intervals. Periodical assessments will, when possible, be harmonised with other surveys and audits carried out.

END OF CERTIFICATE