



Certificate No:
TAS00003B6

TYPE APPROVAL CERTIFICATE

This is to certify:

That the Offshore Container

with type designation(s)
20ft to 33ft frame for MWD Unit

Issued to

True Sea Services FZC
Sharjah, United Arab Emirates

is found to comply with

DNV GL standard DNVGL-ST-E271 – 2.7-1 Offshore containers, January 2021
ISO 10855:2018 Offshore containers and associated liftings sets – Design, manufacture, testing, inspection and marking
IMO/MSC Circular 860

Application :

Type	Max. gross mass (kg)	Max. payload (kg)	Max. sling leg angle	Enhancement factor
20ft to 33ft frame for MWD Unit	13000	See comment	30	1.368

Issued at **Aberdeen** on **2022-02-02**

This Certificate is valid until **2027-02-01** .

for **DNV**

DNV local unit: **Dubai**

Approval Engineer: **Alex Doig**

.....
Elisabeth Legg
Principal Engineer

This Certificate is subject to terms and conditions overleaf. Any significant change in design or construction may render this Certificate invalid.
The validity date relates to the Type Approval Certificate and not to the approval of equipment/systems installed.

LEGAL DISCLAIMER: Unless otherwise stated in the applicable contract with the holder of this document, or following from mandatory law, the liability of DNV AS, its parent companies and their subsidiaries as well as their officers, directors and employees ("DNV") arising from or in connection with the services rendered for the purpose of the issuance of this document or reliance thereon, whether in contract or in tort (including negligence), shall be limited to direct losses and under any circumstance be limited to 300,000 USD.



Form code: TA 281

Revision: 2021-10

www.dnv.com

Page 1 of 2

Product description

Type	Maximum external dimensions (LxWxH)	Tare mass ¹
20ft frame for MWD Unit	6058 x 2438 x 2591 mm	10000 kg
33ft frame for MWD Unit	10060 x 2820 x 3200 mm	10000 kg

¹) Tare mass is to be confirmed by weighing. The sum of payload and tare shall never exceed the maximum gross mass stated on the front page of this certificate.

Application/Limitation

Design temperature	: -20 °C
Minimum shackle pin diameter	: 28.3 mm

The DNV surveyor shall witness all important production and testing events and issue a certificate for each container. The certificate is only valid when the container is fitted with a DNV-ST-E271 certified lifting set.

The 20ft unit can be classed as an ISO freight container in accordance with International Convention for Safe Containers, 1972, CSC - 2014 edition. If this frame is to be used as a freight container and transported as such in international waters it should be approved accordingly by a recognised approval organization.

Type Approval documentation

Tests carried out

Prototypes tested in accordance with DNV-ST-E271.

Marking of product

Each container to be marked in accordance with DNV / ISO requirements, including:

- Data and inspection plates
- DNV emblem for offshore containers
- NV mark to be hard stamped on the data plate
- Manufacturer's serial number to be welded on frame.

Periodical assessment

In order to maintain the validity of this type approval certificate, periodical assessments should be carried out in accordance with DNV-SE-0284 at 2 and 3.5 year intervals. Periodical assessments will, when possible, be harmonised with other surveys and audits carried out.

END OF CERTIFICATE