

TYPE APPROVAL CERTIFICATE

This is to certify:

That the **Portable Tank**

with type designation(s)
40ft ISO Container Model # 12.2K-124-ISO

Issued to

INOX India Pvt Ltd
Gujarat, India

is found to comply with

International Convention for Safe Containers, 1972 (CSC)
ISO 1496, Part 3: Tank Containers for Liquids, Gases and Pressurized Dry Bulk
DNV 2.7-4 Freight Containers
International Maritime Dangerous Goods Code (IMDG)
European Agreement Concerning the International Carriage of Dangerous Goods by Road (ADR)
Regulations Concerning the International Carriage of Dangerous Goods by Rail (RID)
Code of Federal Regulations 49

Application :

UN Portable Tank, Tank Instructions T75

Max. gross mass (kg)	34000
Max. payload (kg)	22116
Tank cap. (L)	46046
MAWP/test pr. (bar)	8.55/12.54 (124/182 psi)
Eq. shell thk. (mm)	8.81/12.22 (shell/head)

Issued at **Høvik** on **2022-02-16**

This Certificate is valid until **2027-02-15**.

for **DNV**

DNV local unit: **Mumbai**

Approval Engineer: **Igor Antonijevic**

.....
Zeinab Sharifi
Head of Section

This Certificate is subject to terms and conditions overleaf. Any significant change in design or construction may render this Certificate invalid.
The validity date relates to the Type Approval Certificate and not to the approval of equipment/systems installed.

LEGAL DISCLAIMER: Unless otherwise stated in the applicable contract with the holder of this document, or following from mandatory law, the liability of DNV AS, its parent companies and their subsidiaries as well as their officers, directors and employees ("DNV") arising from or in connection with the services rendered for the purpose of the issuance of this document or reliance thereon, whether in contract or in tort (including negligence), shall be limited to direct losses and under any circumstance be limited to 300,000 USD.



Product description

40ft CSC/ISO vacuum multi-layer insulated cryogenic tank container.

Max. external dimensions (L x W x H)	12192 x 2438 x 2591 mm
Tare Mass ¹⁾	11884 kg
Nominal thickness (shell/heads)	6.35/9.53 mm
Tank internal diameter	2260 mm
ISO Freight container designation	1AA
Size code	42
Type code	K7
Tank material, inner vessel, shell	SA-240-201.2 / SA240-201LN
Tank material, inner vessel, heads	SA-240-304 SS
Pressure Vessel Code	ASME VIII Div. 1

¹⁾Tare mass is to be confirmed by weighing. The sum of the tare mass and the payload shall never exceed the Max. gross mass as stated on the front page of this certificate.

Application/Limitation

Approved according to 6.7.4 in IMDG/ADR/RID, US DOT 49 CFR requirements.

IMDG/ADR/RID/ design approval reference number	N-NV/631/02/22
US DOT Approval reference number	SI-001-16-USA ²⁾
CSC Approval reference number	US-SI-001-16 ²⁾
Design pressure, inner vessel	9.55 bar
Setting of relief valve	8.55 bar
Metallurgical design temperature for inner tank	-196°C to + 38°C
Design vacuum	1 bar
Design temperature for framework and outer jacket	-20 °C
Allowable stacking load for 1,8g	192000 kg
Racking test load value	150 kN
Effectiveness of the insulation system (heat influx)	220 W (for NATURAL GAS, REFRIGERATED LIQUID)

²⁾ issued by Silver/Cims

Dangerous goods that can be transported and holding times

UN No.	Class	Proper shipping name (PSN)	Holding time (from 0.34 to 8.55 bar @30°C)
1972	2.1	NATURAL GAS, REFRIGERATED LIQUID	91 days (12864 kg / 36468 lb)
1038	2.1	ETHYLENE, REFRIGERATED LIQUID	187 days (21905 kg / 48293 lb)
1961	2.1	ETHANE, REFRIGERATED LIQUID	248 days (21397 kg / 47172 lb)

DNV surveyor has to witness important production and test events and issue Form no. CTT101 "Tank Container Certificate" for each container. In addition to this freight container certificate has to be issued (form no. CTC301). Each tank should be subjected to a hydraulic pressure test to test pressure.

Type Approval documentation

Tests carried out

Prototype tested according to the requirements.

Marking of product

Each container to be marked with:

- Data plate for UN tanks according to Ch. 6.7.4.15 requirements in IMDG Code, ADR and RID. Design approval number according to Application/Limitation above.
- Data plate according to DOT and CSC requirements including Allowable stacking load of 192000 kg.
- External marking according to CSC, IMDG/ADR/RID and DOT requirements
- DNV decal for freight containers
- NV mark to be hard stamped on frame
- Marking in accordance with other applicable codes

Periodical assessment



Job Id: **262.1-037201-1**
Certificate No: **TAS00003BX**

In order to maintain the validity of the type approval certificate, periodical assessments should be carried out according to DNVGL-SE-0284 at 2 and 3.5 year intervals. Periodical assessments will, when possible, be harmonized with other surveys and audits carried out.

END OF CERTIFICATE