



Certificate No:
TAS00003FY

TYPE APPROVAL CERTIFICATE

This is to certify:

That the lifting set for offshore containers

with type designation(s)
wire rope lifting sets

Issued to

Atlantic Island Supply Limited
Port-of-Spain, Trinidad and Tobago

is found to comply with

DNV standard DNV-ST-E271 – 2.7-1 Offshore containers, January 2021 (Amended October 2021)
ISO 10855-2:2018 Offshore containers and associated liftings sets – Part 2: Design, manufacture and testing of lifting sets
IMO/MSC Circular 860
EN 13414-1 Wire rope slings

Application :

1, 2, 3 and 4 leg lifting sets, with forerunner where fitted, for lifting of:
- offshore container, with maximum gross mass 0 to 25,000 kg

Issued at **Aberdeen** on **2023-01-11**

This Certificate is valid until **2028-01-10** .

for **DNV**

DNV local unit: **Houston**

Approval Engineer: **Elisabeth Legg**

.....
Brendan Ward
Senior Engineer

This Certificate is subject to terms and conditions overleaf. Any significant change in design or construction may render this Certificate invalid.
The validity date relates to the Type Approval Certificate and not to the approval of equipment/systems installed.

LEGAL DISCLAIMER: Unless otherwise stated in the applicable contract with the holder of this document, or following from mandatory law, the liability of DNV AS, its parent companies and their subsidiaries as well as their officers, directors and employees ("DNV") arising from or in connection with the services rendered for the purpose of the issuance of this document or reliance thereon, whether in contract or in tort (including negligence), shall be limited to direct losses and under any circumstance be limited to 300,000 USD.



Form code: TA 281

Revision: 2021-10

www.dnv.com

Page 1 of 3

Product description

This type approval covers wire rope lifting sets from 19.0 mm (3/4") to 38.1 mm (1.5") diameter assembled with turnback or Flemish eyes by Atlantic Island Supply Limited in accordance with DNV-ST-E271.

The wire rope lifting sets assembled by Atlantic Island Supply Limited consist of components from the following sub suppliers:

Component	Sub supplier (DNV to be informed and review new sub suppliers)	DNV type approval reference
Master link and Quad assembly	McKinnon Chain South Africa (Pty) Ltd	TAS0000337
Wire rope ¹⁾	Usha Martin Limited	N/A
Shackles ²⁾	Van Beest B.V	TAS000033J
Ferrules ³⁾	Sahm Splice	N/A
Thimbles ⁴⁾	Van Beest B.V.	N/A

1) Wire ropes used in forerunner and bottom legs of lifting sets shall be 6-stranded and of type 6x19 or 6x36 and may be fibre cored or steel cored, with wire rope grades 1960 N/mm², in accordance with EN 12385, or equivalent.

2) Shackles are only considered part of the lifting set if captive (i.e. cannot be removed after assembly of lifting set).

3) Ferrules/sleeves shall be in accordance with EN 13411-3, or equivalent.

4) Thimbles shall be in accordance with EN 13411-1, or equivalent.

Components shall be delivered with the following certificates:

- | | |
|---|--|
| - Master Links, Quad assemblies and Shackles: | Certificates based on DNV type approval. |
| - Wire Ropes: | To be supplied with traceable material certificates in accordance with EN 10204, inspection certificate, type 3.1. |
| - Thimbles and ferrules: | To be supplied with a material certificate in accordance with EN 10204, test report, type 2.2. |

Application/Limitation

For each delivered drum of wire rope, a test sample length with one eye in each end shall be prepared and tested to breaking. The test sample shall be assembled with the same terminations as required by DNV-ST-E271, i.e. with a thimble and ferrule used in each termination. A reference should be made to the wire drum test report in each sling set certificate where that wire is used.

All production testing should be carried out in accordance with Atlantic Island Supply Limited procedures, to be agreed with the local DNV office.

The WLL to be referenced in certificates and marked on lifting sets shall be the maximum working load limit (WLL) of the lifting set, as per the definition in DNV-ST-E271.

Lifting sets shall be assembled in accordance with the strength requirements described in DNV-ST-E271 section 8. The angle of the sling legs from vertical should be taken into account when choosing slings. This angle should normally be 45°, but smaller angles may be used.

Special lifting sets, assembled in accordance with the principles described in DNV-ST-E271 section 8 and appendix D, are also covered by this type approval. If unsymmetrical slings are to be assembled, the local DNV office shall be contacted to review each case, unless otherwise agreed in advance.

Note: The sling leg is not necessarily the weakest part of the lifting set. Master Link assemblies selected for lifting sets with legs at 45° may not be suitable for lifting sets with a smaller angle.

The manufacturer shall issue product certificates, in accordance with DNV-ST-E271 section 8.6, using the Atlantic Island Supply Limited form DR-QMS-OPM-06, Rev No: 00. These certificates shall only be used for lifting sets certified in accordance with this type approval certificate.



Job Id: 262.1-037731-1
Certificate No: TAS00003FY

Type Approval documentation

Tests carried out

Prototype breaking load test of assembled wire rope sling leg.

Marking of product

For lifting sets manufactured in accordance with DNV-ST-E271: refer to section 8.

Periodical assessment

In order to maintain the validity of the type approval certificate, periodical assessments should be carried out by a DNV surveyor every 6 months.

END OF CERTIFICATE