



Certificate No:
TAS00003TH

TYPE APPROVAL CERTIFICATE

This is to certify:

That the offshore container

with type designation(s)
Basket Assembly for 3-1/16" 15K Flowhead

Issued to

Worldwide Oilfield Machine, Inc.
Houston, TX, USA

is found to comply with

DNV standard DNV-ST-E271 – 2.7-1 Offshore containers, January 2021 (Amended October 2021)
ISO 10855:2018 Offshore containers and associated liftings sets – Design, manufacture, testing, inspection and marking
IMO/MSC Circular 860

Application :

Max. gross mass (kg)	6350
Max. payload (kg)	2700
Max. sling leg angle	30
Enhancement factor	1.742

Issued at **Aberdeen** on **2023-03-07**

This Certificate is valid until **2028-03-06** .

DNV local unit: **Houston**

for **DNV**

Approval Engineer: **Elisabeth Legg**

Brendan Ward
Senior Engineer

This Certificate is subject to terms and conditions overleaf. Any significant change in design or construction may render this Certificate invalid.
The validity date relates to the Type Approval Certificate and not to the approval of equipment/systems installed.

LEGAL DISCLAIMER: Unless otherwise stated in the applicable contract with the holder of this document, or following from mandatory law, the liability of DNV AS, its parent companies and their subsidiaries as well as their officers, directors and employees ("DNV") arising from or in connection with the services rendered for the purpose of the issuance of this document or reliance thereon, whether in contract or in tort (including negligence), shall be limited to direct losses and under any circumstance be limited to 300,000 USD.



Form code: TA 281

Revision: 2022-12

www.dnv.com

Page 1 of 2

Manufactured by

Responsibility

Worldwide Oilfield Machine, Inc. takes responsibility that both design and production are in compliance with the rules, standards and/or regulations listed on page 1 of this type approval certificate.

Product description

Maximum external dimensions (LxWxH) : 4623 x 2001 x 1835 mm
Tare mass* : 3650 kg

*) Tare mass shall be confirmed by weighing. The sum of the tare mass and the payload shall never exceed the maximum gross mass stated on the front page of this certificate.

Application/Limitation

Design temperature : -20 °C
Minimum shackle pin diameter : 24.9 mm

The DNV surveyor shall witness all important production and testing events and issue a certificate for each container. The certificate is only valid when the container is fitted with a DNV-ST-E271 certified lifting set.

Type Approval documentation

Tests carried out

Prototype to be tested in accordance with DNV-ST-E271.

Marking of product

Each container to be marked in accordance with DNV / ISO requirements, including:

- Data and inspection plates
- DNV emblem for offshore containers
- NV mark to be hard stamped on the data plate
- Manufacturer's Serial Number to be welded on frame

Periodical assessment

In order to maintain the validity of the type approval certificate, periodical assessments should be carried out in accordance with DNV-SE-0284 at 2 and 3.5 year intervals. Periodical assessments will, when possible, be harmonised with other surveys and audits carried out.

This certificate is only valid if required periodical assessments are carried out with satisfactory results. To check the validity of this certificate, please look it up in <https://approvalfinder.dnv.com>