Certificate No:
TAS000040W

TYPE APPROVAL CERTIFICATE

This is to certify:

That the Cargo Securing Devices

with type designation(s)
Lashing Chain 11 mm CL-11

Issued to
International Lashing Systems NV
Antwerpen, **Belgium**

is found to comply with
DNV rules for classification – Ships

Application :

Product(s) approved by this certificate is/are accepted for installation on all vessels classed by DNV.
SWL, tension (kN) 75

Issued at **Hamburg** on **2023-12-05**
This Certificate is valid until **2028-12-04**.
DNV local unit: **Belgium CMC**

Approval Engineer: **Aadil Wafdi**

for **DNV**

Andree Orth
Head of Section

This Certificate is subject to terms and conditions overleaf. Any significant change in design or construction may render this Certificate invalid.
The validity date relates to the Type Approval Certificate and not to the approval of equipment/systems installed.

LEGAL DISCLAIMER: Unless otherwise stated in the applicable contract with the holder of this document, or following from mandatory law, the liability of DNV AS, its parent companies and their subsidiaries as well as their officers, directors and employees ("DNV") arising from or in connection with the services rendered for the purpose of the issuance of this document or reliance thereon, whether in contract or in tort (including negligence), shall be limited to direct losses and under any circumstance be limited to 300,000 USD.

Product description

Lashing Chain CL-11	– Configuration LA0
Lashing Chain CL-11 with two hooks HO-1315	– Configuration LA1
Lashing Chain CL-11 with hook HO-1315 and Elephantfoot HO-1421	– Configuration LA2
Lashing Chain CL-11 with one hook HO-1315	– Configuration LA4

Application/Limitation

Load	Tension [kN]
Test Load	94
Breaking Load	150

Tests to be carried out:

- Production testing: At least 2% of the items delivered are to be selected and subjected to the test load.
- Material tests are to be included energy testing at -20°C, with the impact energy requirements acc. to DNV-CP-0068. The material shall be according to the approved drawings. Material certificates shall be 3.1 acc. to ISO 10474:2013.
- If the lashing chains are used for container lashing, the SWL will be reduced to 60 kN.

Type Approval documentation

Drawing No.	Rev.	Title
CL-11	01	Lashing Chain 11 mm
Lax.11-13xM	01	Summary Sheet Lashing Chains
HO-1315	01	C-Hook for 11 mm Lashing Chain
HO-1421	01	Elephant Foot

Drawing approval: Ref.No. 262.1-028969-2, dated 2023-09-26
Test report No.: CP-0068 dated 2023-07-20

Tests carried out

The prototype test was carried out in Yixing, P.R. China, dated 2023-07-20 in accordance with the DNV-CP-0068.

Marking of product

Each item shall be marked by manufacturer for traceability.

Periodical Assessment

For retention of the Type Approval, a DNV surveyor shall perform a survey after 2 and 3.5 years, to verify that the Type Approval is complied with.