Certificate no.:
**TAS000042Y**

# TYPE APPROVAL CERTIFICATE

## This is to certify:

**that the Cargo Securing Devices**

with type designation(s)
**Turnbuckle RS-FN/1190-1495/K38**
**Turnbuckle RS-FN/1180-1555/K38**
**Turnbuckle RS-FN/1055-1280/K38**
**Turnbuckle RS-FN/1190-1595/K38**
**Turnbuckle RS-FN/1135-1470/K38**
**Turnbuckle RS-FN/1455-1980/K38**
**Turnbuckle RS-FN/855-1180/K38**
**Turnbuckle RS-FN/1105-1530/K38**
**Turnbuckle RS-FN/1355-1830/K38**
**Turnbuckle RS-FN/1155-1730/K38**
**Turnbuckle RS-FN/855-1180/K38**
**Turnbuckle RS-FN/1345-1870/K38**
**Turnbuckle RS-FN/1315-1730/K38**
**Turnbuckle RS-FN/1140-1405/K38**

issued to
**SEC Ship's Equipment Centre Bremen GmbH & Co. KG**
**Bremen**, **Germany**

is found to comply with
**DNV rules for classification – Ships**

## Application:

**Product(s) approved by this certificate is/are accepted for installation on all vessels classed by DNV.**
**SWL, tension (kN) 250**

Issued at **Hamburg** on **2023-11-10**
This Certificate is valid until **2028-11-09**.
DNV local unit: **Hamburg – CMC North/East**

for **DNV**

Approval Engineer: **Aadil Wafdi**

.....

This Certificate is subject to terms and conditions overleaf. Any significant change in design or construction may render this Certificate invalid.
The validity date relates to the Type Approval Certificate and not to the approval of equipment/systems installed.

LEGAL DISCLAIMER: Unless otherwise stated in the applicable contract with the holder of this document, or following from mandatory law, the liability of DNV AS, its parent companies and their subsidiaries as well as their officers, directors and employees ("DNV") arising from or in connection with the services rendered for the purpose of the issuance of this document or reliance thereon, whether in contract or in tort (including negligence), shall be limited to direct losses and under any circumstance be limited to 300,000 USD.

## Product description

Turnbuckle

## Application/Limitation

| Load | Shear [kN] |
|---|---|
| Test Load | 313 |
| Breaking Load | 500 |

Tests to be carried out:

- Production testing: At least 2% of the items delivered are to be selected and subjected to the test load.
- Material tests are to be included energy testing at -20°C, with the impact energy requirements acc. to DNV-CP-0068. The material shall be according to the approved drawings. Material certificates shall be 3.1 acc. to ISO 10474:2013.

## Type Approval documentation

| Drawing No. | Rev. | Title |
|---|---|---|
| P-RS 1672 | | Turnbuckle (Spannschraube) |
| P-RS 1677 | | Turnbuckle (Spannschraube) |
| P-RS 1681 | | Turnbuckle (Spannschraube) |
| P-RS 1721 | | Turnbuckle (Spannschraube) |
| P-RS 1722 | | Turnbuckle (Spannschraube) |
| P-RS 1723 | | Turnbuckle (Spannschraube) |
| P-RS 1724 | | Turnbuckle (Spannschraube) |
| P-RS 1725 | | Turnbuckle (Spannschraube) |
| P-RS 1726 | | Turnbuckle (Spannschraube) |
| P-RS 1727 | | Turnbuckle (Spannschraube) |
| P-RS 1728 | | Turnbuckle (Spannschraube) |
| P-RS 1746 | | Turnbuckle (Spannschraube) |
| P-RS 1778 | | Turnbuckle (Spannschraube) |
| P-RS 1780 | | Turnbuckle (Spannschraube) |
| P-RS 8077C | C | Bolt |
| P-RS 8099F | F | Fork for Turnbuckles Forged Element |
| P-RS 8107C | C | Bolt for Turnbuckles |
| P-RS 8120E | E | Fork for Turnbuckles Forged Element |
| P-RS 8224 D | D | Sliding Nut |
| P-RS 8234 A | A | Headmounting (Kopfbeschlag) |
| P-RS 8235 A | A | Pipe |
| P-RS 8328 | | Fork for Turnbuckles |
| P-RS 8365 | | Fork for Turnbuckles |
| P-RS 8370 | | Fork for Turnbuckles |
| P-RS 8371 | | Fork for Turnbuckles |
| P-RS 8372 | | Fork for Turnbuckles |
| P-RS 8375 | | Fork for Turnbuckles |
| P-RS 8382 | | Fork for Turnbuckles |
| P-RS 8387 | | Fork for Turnbuckles |
| P-RS 8392 | | Fork for Turnbuckles |
| P-RS 8393 | | Fork for Turnbuckles |
| P-RS 8395 | | Fork for Turnbuckles |
| P-RS 8654 | | Fork for Turnbuckles |
| P-RS 8655 | | Fork for Turnbuckles |

Drawing approval: Ref.No. 262.040341-1, dated 2023-11-01.
Test report No.: CP-0068 dated 2023-01-09, 2023-08-18 and 2023-10-08.

## Tests carried out

The prototype test was carried out in Shanghai, P.R. China, dated 2023-01-09, 2023-08-18 and 2023-10-08 in accordance with the DNV-CP-0068.

## Marking of product

Each item shall be marked by manufacturer for traceability.

## Periodical Assessment

For retention of the Type Approval, a DNV surveyor shall perform a survey after 2 and 3.5 years, to verify that the Type Approval is complied with.