Certificate no.:
TAS0000431

TYPE APPROVAL CERTIFICATE

This is to certify:

that the Cargo Securing Devices

with type designation(s)
Flush D-Ring Type LE-8C, Flush D-Ring Type LE-8F

issued to
Container Technics NV
Wijnegem, Antwerpen, Belgium

is found to comply with
DNV class programme DNV-CP-0068 – General – Certification of container securing devices

Application:

Product(s) approved by this certificate is/are accepted for installation on all vessels classed by DNV.

	SWL, tension (kN)
Flush D-Ring Type LE-8C	**75**
Flush D-Ring Type LE-8F	**38**

Issued at **Hamburg** on **2023-11-06**

This Certificate is valid until **2028-11-05**.

for **DNV**

DNV local unit: **Belgium CMC**

Approval Engineer: **Mark-Oliver Wobig**

This Certificate is subject to terms and conditions overleaf. Any significant change in design or construction may render this Certificate invalid.
The validity date relates to the Type Approval Certificate and not to the approval of equipment/systems installed.

LEGAL DISCLAIMER: Unless otherwise stated in the applicable contract with the holder of this document, or following from mandatory law, the liability of DNV AS, its parent companies and their subsidiaries as well as their officers, directors and employees ("DNV") arising from or in connection with the services rendered for the purpose of the issuance of this document or reliance thereon, whether in contract or in tort (including negligence), shall be limited to direct losses and under any circumstance be limited to 300,000 USD.

Product description

Flush D-Rings

Application/Limitation

Load	LE-8C Tension [kN]	LE-8F Tension [kN]
Test Load	83	57
Breaking Load	150	76

Tests to be carried out:

- Production testing: At least 2% of the items delivered are to be selected and subjected to the test load.
- All welding-in pockets of support fittings shall be checked for tightness and delivered with proof issued by the manufacturer. The Society reserves the right to be present at tightness test.
- Material tests are to be included energy testing at 0°C, with the impact energy requirements acc. to DNV-CP-0068. The material shall be according to the approved drawings. Material certificates shall be issued by the society.
- The Flush D-Rings shall be used in Cargo Hold only.

Type Approval documentation

Drawing No.	Rev.	Title
LE-8F	b	Flush D-Ring (pg. 1 +2)
LE-8C	e	Flush D-Ring (pg. 1 +2)

Drawing approval: Ref.No. 262.1-019997-2, dated 2023-09-19
Test report No.: M-NP-CMCG-A1290659-1, dated 2023-07-04.

Tests carried out

The prototype test was carried out in Barlinek, Poland, dated 2023-01-13 in accordance with the DNV-CP-0068.

Marking of product

Each item shall be marked by manufacturer for traceability.

Periodical Assessment

For retention of the Type Approval, a DNV surveyor shall perform a survey after 2 and 3.5 years, to verify that the Type Approval is complied with.