



Certificate no.:
TAS0000439

TYPE APPROVAL CERTIFICATE

This is to certify:

that the portable offshore units

with type designation(s)
Lifting cage

issued to

Voe Marine Engineering Ltd
Aberdeen, United Kingdom

is found to comply with

DNV standard DNV-ST-E273 – 2.7-3 Portable offshore units, April 2016 (Amended May 2022)

Application:

Max. gross mass (kg) 440

Max. payload (kg) 210

Max. sling leg angle 0

Issued at **Aberdeen** on **2023-11-10**

This Certificate is valid until **2028-11-09**.

for **DNV**

DNV local unit: **Aberdeen**

Approval Engineer: **Elisabeth Legg**

This Certificate is subject to terms and conditions overleaf. Any significant change in design or construction may render this Certificate invalid.
The validity date relates to the Type Approval Certificate and not to the approval of equipment/systems installed.

LEGAL DISCLAIMER: Unless otherwise stated in the applicable contract with the holder of this document, or following from mandatory law, the liability of DNV AS, its parent companies and their subsidiaries as well as their officers, directors and employees ("DNV") arising from or in connection with the services rendered for the purpose of the issuance of this document or reliance thereon, whether in contract or in tort (including negligence), shall be limited to direct losses and under any circumstance be limited to 300,000 USD.



Form code: TA 281

Revision: 2023-09

www.dnv.com

Page 1 of 2

Product description

Type	Dimensions (LxWxH)	Type	Operational Class	Tare mass*
Lifting cage	1220 x 830 x 1115 mm	E	R30	230 kg

*) Tare mass is to be confirmed by weighing. The sum of tare and payload shall never exceed the maximum gross mass stated on the front page of this certificate.

Application/Limitation

Type	Resultant Sling Force (RSF)	Design temperature
Lifting cage	10 kN	-20 °C

The DNV surveyor shall witness all important production and testing events and issue a certificate on Form no. MOP 201 "Certificate for Portable Offshore Unit" for each unit.

This design verification does not apply to the gas cylinders to be transported by this frame. If gas cylinders are to be installed and connected to manifolds, the unit as a whole (frame and payload) must be approved and certified as an offshore container in accordance with DNV-ST-E271 and the IMDG Code Ch. 6.2, by an authorised certifying body.

Type Approval documentation

Tests carried out

Prototype tested in accordance with DNV-ST-E273.

Marking of product

Marking shall be carried out in accordance with to DNV-ST-E273 section 6.

Fork lift pockets are smaller size than the minimum 200 mm internal width specified in DNV-ST-E273 section 3.9.3. Each unit shall be marked with the fork lift pocket opening size clearly stencilled adjacent to the opening.

Periodical assessment

In order to maintain the validity of the type approval certificate, periodical assessments should be carried out according to DNV-SE-0284 at 2 and 3.5 year intervals. Periodical assessments will, when possible, be harmonised with other surveys and audits carried out.

This certificate is only valid if required periodical assessments are carried out with satisfactory results. To check the validity of this certificate, please look it up in <https://approvalfinder.dnv.com>.