



Certificate no.:
TAS000047G

TYPE APPROVAL CERTIFICATE

This is to certify:

that the **Portable Offshore Units**

with type designation(s)
S1254-5

issued to

SRI Energy Inc.
Sugar Land, TX, USA

is found to comply with

DNV standard DNV-ST-E273 – 2.7-3 Portable offshore units, April 2016 (Amended May 2022)

Application:

Product(s) approved by this certificate is/are accepted for installation on all vessels classed by DNV.

Max. gross mass (kg) 11800
Max. payload (kg) 8200
Max. sling leg angle 40

Issued at **Houston** on **2024-06-08**

This Certificate is valid until **2029-06-07**.

for **DNV**

DNV local unit: **Houston Offshore Services**

Approval Engineer: **Bo Cui**

.....

This Certificate is subject to terms and conditions overleaf. Any significant change in design or construction may render this Certificate invalid.
The validity date relates to the Type Approval Certificate and not to the approval of equipment/systems installed.

LEGAL DISCLAIMER: Unless otherwise stated in the applicable contract with the holder of this document, or following from mandatory law, the liability of DNV AS, its parent companies and their subsidiaries as well as their officers, directors and employees ("DNV") arising from or in connection with the services rendered for the purpose of the issuance of this document or reliance thereon, whether in contract or in tort (including negligence), shall be limited to direct losses and under any circumstance be limited to 300,000 USD.



Product description

SKID, MPD DETECTION MANIFOLD, 7-1/16"-5K 6" CLASS #1500

Application/Limitation

Design Parameter	Value
Design temperature	-20°C
POU Type	Type A, R45
Dimensions	117.20" x 95.45" x 111.01"
Type of Lifting	4 point lifting
Max. Sling Angle (from vertical)	40 deg
Shackle WLL	9.5 Tonne
Min. Shackle Pin Diameter	1.25 in

Type Approval documentation

Tests carried out

Prototype for the Skid with part number: S 1254-5, serial number: 30001549-001A tested on 05-MAR-2024 according to Standard for Certification DNV-ST-E273, April 2016.

Marking of product

Marking is to be carried out in accordance with DNV-ST-E273 Section 6

Periodical assessment

Periodical assessment to be carried out at intervals not exceeding 12 months and after substantial repair or alteration according to Standard for Certification DNV-ST-E273, 2016 edition.

END OF CERTIFICATE