Certificate no.:
TAS00004B0

TYPE APPROVAL CERTIFICATE

This is to certify:

that the offshore container

with type designation(s)
Skid for HPU

issued to
HI Energy FZC
Sharjah, **United Arab Emirates**

is found to comply with
DNV standard DNV-ST-E271 – 2.7-1 Offshore containers, March 2023
ISO 10855-1:2018 Offshore containers and associated liftings sets – Part 1: Design, manufacture and marking of offshore containers
IMO/MSC Circular 860

Application:

Max. gross mass (kg)	**2875**
Max. payload (kg)	**200**
Max. sling leg angle	**30**
Enhancement factor	**2.670**

Issued at **Aberdeen** on **2024-05-23**
This Certificate is valid until **2029-05-22**.
DNV local unit: **Abu Dhabi**

for **DNV**

Approval Engineer: **Elisabeth Legg**

This Certificate is subject to terms and conditions overleaf. Any significant change in design or construction may render this Certificate invalid.
The validity date relates to the Type Approval Certificate and not to the approval of equipment/systems installed.

LEGAL DISCLAIMER: Unless otherwise stated in the applicable contract with the holder of this document, or following from mandatory law, the liability of DNV AS, its parent companies and their subsidiaries as well as their officers, directors and employees ("DNV") arising from or in connection with the services rendered for the purpose of the issuance of this document or reliance thereon, whether in contract or in tort (including negligence), shall be limited to direct losses and under any circumstance be limited to 300,000 USD.

Manufactured by
DNV CIM Number 10139667

DNV CIM Number 10600981*

Local DNV office: Abu Dhabi

*) This manufacturer will be considered valid once a prototype has been built and tested.

Responsibility
HI Energy FZC take full responsibility that both the design and production are in compliance with the Rules, Standards and / or Regulations listed on page 1.

Product description
Maximum external dimensions (LxWxH)	: 2550 x 1362 x 1860 mm
Tare mass**	: 2675 kg

**) Tare mass is to be confirmed by weighing. The sum of tare and payload shall never exceed the maximum gross mass stated on the front page of this certificate.

Application/Limitation
Design temperature	: -20 °C
Minimum shackle pin diameter	: 21.7 mm

The DNV surveyor shall witness all important production and testing events and issue a certificate for each container. The certificate is only valid when the container is fitted with a DNV-ST-E271 certified lifting set.

Type Approval documentation

Tests carried out
Prototype tested in accordance with DNV-ST-E271.

Marking of product
Each container to be marked in accordance with DNV requirements, including:
- Data and inspection plates
- DNV emblem for offshore containers
- NV mark to be hard stamped on the data plate
- Manufacturer's serial number to be welded on frame

Periodical assessment
In order to maintain the validity of this type approval certificate, periodical assessments should be carried out in accordance with DNV-SE-0284 at 2 and 3.5 year intervals. Periodical assessments will, when possible, be harmonised with other surveys and audits carried out.

This certificate is only valid if required periodical assessments are carried out with satisfactory results. To check the validity of this certificate, please look it up in https://approvalfinder.dnv.com