Certificate no.:
TAS00004B9

TYPE APPROVAL CERTIFICATE

This is to certify:

that the Cargo Securing Devices

with type designation(s)
Raised ISO Socket single A4.1-65-HI 220-220
Raised ISO Socket double transversal A4.2-216-65-HI-452-236
Raised ISO Socket double transversal A4.2-266-65-HI-502-236
Raised ISO Socket double longitudinal A4.3-279-65-HI-513-236
Raised ISO Socket quadruple A4.4-216-279-65-HI-517-452
Raised ISO Socket quadruple A4.4-266-279-65-HI-517-502
Raised ISO Socket triple left A4.5-266-279-65-HI-517-502-L
Raised ISO Socket triple right A4.5-266-279-65-HI-517-502-R

issued to
MEC Safety Systems GmbH
Hamburg, **Germany**

is found to comply with
DNV class programme DNV-CP-0068 – General – Certification of container securing devices

Application:

Product(s) approved by this certificate is/are accepted for installation on all vessels classed by DNV.

SWL, tension (kN)	**250**
SWL, shear (kN)	**210**
SWL, compr. (kN)	**1000**

Issued at **Hamburg** on **2024-06-25**

This Certificate is valid until **2029-06-24**.

for **DNV**

DNV local unit: **Hamburg – CMC North/East**

Approval Engineer: **Aadil Wafdi**

This Certificate is subject to terms and conditions overleaf. Any significant change in design or construction may render this Certificate invalid.
The validity date relates to the Type Approval Certificate and not to the approval of equipment/systems installed.

LEGAL DISCLAIMER: Unless otherwise stated in the applicable contract with the holder of this document, or following from mandatory law, the liability of DNV AS, its parent companies and their subsidiaries as well as their officers, directors and employees ("DNV") arising from or in connection with the services rendered for the purpose of the issuance of this document or reliance thereon, whether in contract or in tort (including negligence), shall be limited to direct losses and under any circumstance be limited to 300,000 USD.

Product description

Raised ISO Socket

Application/Limitation

Load	Tension [kN]	Shear [kN]	Compression [kN]
Test Load	313	263	1250
Breaking Load	500	420	2000

Tests to be carried out:

- Production testing: At least 2% of the items delivered are to be selected and subjected to the test load.
- Material tests are to be included energy testing at -20°C, with the impact energy requirements acc. to DNV-CP-0068. The material shall be according to the approved drawings. Material certificates shall be issued by the society.

Type Approval documentation

Drawing No.	Rev.	Title
A-04-01-065-HI-220-220	1	Raised ISO Socket single
A-04-02-216-065-HI-452-236	1	Raised ISO Socket double transversal, CC=216mm
A-04-02-266-065-HI-502-236	1	Raised ISO Socket double transversal, CC=266mm
A-04-03-279-065-HI-513-236	1	Raised ISO Socket double longitudinal, CC=279mm
A-04-04-216-279-065-HI-517-452	1	Raised ISO Socket quadruple, CC=216/279mm
A-04-04-266-279-065-HI-517-502	1	Raised ISO Socket quadruple, CC=266/279mm
A-04-05-266-279-065-HI-517-502-L	1	Raised ISO Socket triple left, CC=266/279mm
A-04-05-266-279-065-HI-517-502-R	1	Raised ISO Socket triple right, CC=266/279mm

Drawing Approval: Ref.-No. 262.1-041708-1, dated 2024-05-29
Test report No.: CP-0068 dated 2024-06-13

Tests carried out

The prototype test was carried out in Dalian, P.R. China, dated 2024-06-13 in accordance with the DNV-CP-0068.

Marking of product

Each item shall be marked by manufacturer for traceability.

Periodical Assessment

For retention of the Type Approval, a DNV surveyor shall perform a survey after 2 and 3.5 years, to verify that the Type Approval is complied with.