Certificate no.:
TAS00004GU

TYPE APPROVAL CERTIFICATE

This is to certify:

that the Cargo Securing Devices

with type designation(s)
Fully Automatic Twistlock FA-9

issued to
Minato Seiki Iron Works Co., Ltd.
Ibaraki, Osaka Pref, **Japan**

is found to comply with
DNV class programme DNV-CP-0068 – General – Certification of container securing devices

Application:

Product(s) approved by this certificate is/are accepted for installation on all vessels classed by DNV.

SWL, tension (kN)	**250**
SWL, shear (kN)	**210**

Issued at **Hamburg** on **2025-03-14**

This Certificate is valid until **2030-03-13**.

for **DNV**

DNV local unit: **Japan CMC**

Approval Engineer: **Irina Geißler**

.....

This Certificate is subject to terms and conditions overleaf. Any significant change in design or construction may render this Certificate invalid.
The validity date relates to the Type Approval Certificate and not to the approval of equipment/systems installed.

LEGAL DISCLAIMER: Unless otherwise stated in the applicable contract with the holder of this document, or following from mandatory law, the liability of DNV AS, its parent companies and their subsidiaries as well as their officers, directors and employees ("DNV") arising from or in connection with the services rendered for the purpose of the issuance of this document or reliance thereon, whether in contract or in tort (including negligence), shall be limited to direct losses and under any circumstance be limited to USD 300 000.

Product description

Fully Automatic Twistlock FA-9

Application/Limitation

Load	Tension [kN]	Shear [kN]
Test Load	313	263
Breaking Load	500	420

Tests to be carried out:

- Production testing: At least 2% of the items delivered are to be selected and subjected to the test load.
- Material tests are to be included energy testing at -20°C, with the impact energy requirements acc. to DNV-CP-0068. The material shall be according to the approved drawings. Material certificates shall be 3.1 acc. to ISO 10474:2013.

Type Approval documentation

Tests carried out

The prototype test was carried out in Suzhou, China, dated 2024-11-07 in accordance with the DNV CP-0068.
The function test was carried out in Valluhn, Drehtainer GmbH, Germany, dated 2024-10-24 in accordance with the DNV CP-0068.
The applicable vertical twistlock clearance in container lashing calculations according to DNV-rules Pt.5 Ch.2 Sec.8 is 20 mm.

Marking of product

Each item shall be marked by manufacturer for traceability.

Periodical assessment

For retention of type approval, a DNV-surveyor shall perform a survey after 2 and 3.5 years, to verify that the type approval is complied with.