



Certificate no.:
TAS00004HA

TYPE APPROVAL CERTIFICATE

This is to certify:

that the **Offshore Tank Container**

with type designation(s)
4800L vertical chemical tank

issued to

Suretank Ltd
Dunleer, Co. Louth, Ireland

is found to comply with

DNV standard DNV-ST-E271 – 2.7-1 Offshore containers, March 2023
ISO 10855-1:2018 Offshore containers and associated liftings sets – Part 1: Design, manufacture and marking of offshore containers
IMO/MSC Circular 860
International Maritime Dangerous Goods Code (IMDG)
European Agreement Concerning the International Carriage of Dangerous Goods by Road (ADR)
Regulations Concerning the International Carriage of Dangerous Goods by Rail (RID)

Application:

UN Portable Offshore Tank, Tank Instruction: T14

Max. gross mass (kg)	12000
Max. payload (kg)	8500
Tank cap. (L)	4800
MAWP/test pr. (bar)	4.0 / 18.0
Eq. shell thk (mm)	6.0

Issued at **Høvik** on **2024-11-21**

This Certificate is valid until **2029-11-20**.

for **DNV**

DNV local unit: **Manchester**

Approval Engineer: **Igor Antonijevic**

This Certificate is subject to terms and conditions overleaf. Any significant change in design or construction may render this Certificate invalid.
The validity date relates to the Type Approval Certificate and not to the approval of equipment/systems installed.

LEGAL DISCLAIMER: Unless otherwise stated in the applicable contract with the holder of this document, or following from mandatory law, the liability of DNV AS, its parent companies and their subsidiaries as well as their officers, directors and employees ("DNV") arising from or in connection with the services rendered for the purpose of the issuance of this document or reliance thereon, whether in contract or in tort (including negligence), shall be limited to direct losses and under any circumstance be limited to 300,000 USD.

Product description

Designs approved according to IMDG Code, Edition 2022 Amdt. 41-22.

Max. external dimensions:	2200 x 2200 x 2450 mm
Tare mass:	3500 kg
Pressure vessel code, tank:	EN 13445
Tank diameter (Internal):	1950 mm
Nominal tank thickness, shell:	8mm
Nominal tank thickness, ends B/F / A/F:	10mm / 8.5mm
Tank material:	ASME SA-240 S31803; EN 10028-7 1.4462

Application/Limitation

IMDG/ADR/RID design approval number¹⁾: N-NV/675/11/24

¹⁾Suretank Limited is responsible for proper using of the number.

Metallurgical design temperature for tank:	-40°C to +70°C
Design temperature for framework:	-20°C
Setting of relief valve:	13.2 bar
Vacuum settings:	-1 bar
Min. shackle bolt diameter:	41.5 mm
Lifting slings Max angle of legs from vertical:	45°
Enhancement factor:	1.413

Products accepted for carriage:

- Liquids with the following Tank Instructions in the IMDG and ADR/RID code: from T1 to T14.

DNV surveyor has to witness important production and test events and issue Form no. 71.08a "Certificate for Offshore Container" and Form no. CTT101 "Tank Container Certificate" for each container.

Production strength tests (All point lifting) to be carried out according to DNV-ST-E271 and after agreement with the DNV surveyor.

The certificates are only valid when the containers are fitted with a lifting set certified according to DNV-ST-E271.

Each tank should be subjected to a hydraulic pressure test to the specified test pressure.

Items of equipment shall be arranged, protected and marked per the requirements of IMDG code section 6.7.2.5.

Verification shall be carried out by the surveyor.

Type Approval documentation

Tests carried out

Prototypes tested according to the requirements.

Marking of product

Each container to be marked with:

- Data plates for UN tanks according to IMDG Code Ch. 6.7.2.20. Design approval number according to Application/Limitation above
- Data plates according to DNV / ISO requirements
- External marking according to IMDG / DNV / ISO requirements
- DNV decal for offshore containers
- NV mark to be hard stamped on frame
- Manufacturer's Serial Number to be welded on frame

Periodical assessment

In order to maintain the validity of the type approval certificate, periodical assessments should be carried out according to DNV-SE-0284 at 2 and 3.5 year intervals. Periodical assessments will, when possible, be harmonized with other surveys and audits carried out. This certificate is only valid if required periodical assessments are carried out with satisfactory results. To check the validity of this certificate, please look it up in <https://approvalfinder.dnv.com>

END OF CERTIFICATE